

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

373 Elektronik Oel 07373020A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Lubricant

#### 1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

**1.4. Emergency telephone number:** +49 (0) 30 30 686 790 (Giftnotruf Berlin)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1A

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

Dihydro-3-(tetrapropenyl)furan-2,5-dione

**Signal word:** Danger

**Pictograms:**



##### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 2 of 12

H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P260 Do not breathe Aerosol.  
P280 Wear eye/face protection..  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P302+P352 IF ON SKIN: Wash with plenty of Water and soap..  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P314 Get medical advice/attention if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P251 Do not pierce or burn, even after use.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.  
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane			20 - < 25 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics			20 - < 25 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione			0.1 - < 1 %
	247-781-6			
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 4; H319 H317 H413			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**373 Elektronik Oel 07373020A**

Revision date: 11.09.2018

Product code: 1100443

Page 3 of 12

**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 4 of 12

#### 6.4. Reference to other sections

Safe handling: see section 7  
 Personal protection equipment: see section 8  
 Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.  
 Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.  
 When using do not eat, drink, smoke, sniff.  
 Wear personal protection equipment (refer to section 8).  
 In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

#### Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### Additional advice on limit values

a no restriction  
 b End of exposure or end of shift  
 c at long term exposure: after several previous shifts  
 d before next shift

blood (B)  
 Urine (U)

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**373 Elektronik Oel 07373020A**

Revision date: 11.09.2018

Product code: 1100443

Page 5 of 12

**Protective and hygiene measures**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
DIN EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min  
Thickness of the glove material 0,45 mm  
DIN EN 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: AX  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	solvent like

**Test method**

pH-Value (at 20 °C):

**Changes in the physical state**

Initial boiling point and boiling range:	-40 °C
Flash point:	-80 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	9,4 vol. %
Density (at 20 °C):	0,6713 g/cm <sup>3</sup> DIN 51757

**9.2. Other information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 6 of 12

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### **10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

#### **10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

#### **10.6. Hazardous decomposition products**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

### SECTION 11: Toxicological information

#### **11.1. Information on toxicological effects**

##### **Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

##### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75-28-5	isobutane				
	inhalation vapour	LC50 1237 mg/l	Mouse.		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat		
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat		
	dermal	LD50 2770 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 23,3 mg/l	Rat		
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione				
	oral	LD50 2900 mg/kg	Rat		
	dermal	LD50 6250-7500 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 1220 mg/l	Rat		
	inhalation (4 h) aerosol	LC50 5,3 mg/l	Rat		

#### **Irritation and corrosivity**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**373 Elektronik Oel 07373020A**

Revision date: 11.09.2018

Product code: 1100443

Page 7 of 12

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Vapours may cause drowsiness and dizziness. After skin contact: irritant.

**Sensitising effects**

May cause an allergic skin reaction. (Dihydro-3-(tetrapropenyl)furan-2,5-dione)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane;

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
75-28-5	isobutane					
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane					
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 100 mg/l	> 10 -	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna	
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics					
	Acute fish toxicity	LC50 mg/l	>1 - 10	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 100 mg/l	>10 -	72 h	Algae toxicity	
	Acute crustacea toxicity	EC50 mg/l	>1 - 10	48 h	Daphnia magna	
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	110 mg/l	96 h	Selenastrum capricornutum	

**12.2. Persistence and degradability**

There are no data available on the mixture itself. AOX (mg/l): 0



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 9 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane			
	OECD Guideline 301 F	98%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

#### **12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	>=4,39

#### **12.4. Mobility in soil**

No information available.

#### **12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

#### **12.6. Other adverse effects**

No information available.

#### **Further information**

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### **Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

##### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

##### **14.1. UN number:**

UN 1950

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**373 Elektronik Oel 07373020A**

Revision date: 11.09.2018

Product code: 1100443

Page 10 of 12

<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

**Marine transport (IMDG)**

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane)
<b><u>14.3. Transport hazard class(es):</u></b>	2.1
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Marine pollutant:	Yes
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS, flammable
<b><u>14.3. Transport hazard class(es):</u></b>	2.1
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 373 Elektronik Oel 07373020A

Revision date: 11.09.2018

Product code: 1100443

Page 11 of 12

#### 14.6. Special precautions for user

Warning: Flammable gases.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, &lt; 5% n-hexane; Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics; butane

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

##### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol directive (75/324/EEC)

##### National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

### SECTION 16: Other information

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**373 Elektronik Oel 07373020A**

Revision date: 11.09.2018

Product code: 1100443

Page 12 of 12

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Further Information**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:  
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*