

according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kontakt-Reiniger 375

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reiniger

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG

Street: Bürgermeister-Seidl-Str. 2 Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600 - 0 Telefax: +49 (0) 8171/1600 - 40

e-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone +49 (0) 30 30 686 790 (Giftnotruf Berlin)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: F - Highly flammable, Xn - Harmful, N - Dangerous for the environment

R phrases:

Highly flammable. Irritating to eyes.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard components for labelling

Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics

2-Propanol

Signal word: Danger

Pictograms: GHS02-GHS07-GHS08-GHS09



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 2 of 11









Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from	heat, hot surface	ces, sparks, open f	lames and other ig	gnition sources. No

smoking.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 3 of 11

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
920-750-0	Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics	25 - < 50 %
64742-49-0	F - Highly flammable, Xn - Harmful, N - Dangerous for the environment R11-51-53-65-66-67	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066	
01-2119473853-33		
200-661-7	2-Propanol	25 - < 50 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
01-2119457558-25		

Full text of R, H and EUH phrases: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 4 of 11

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Vapours can form explosive mixtures with air.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Reiniger

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Additional advice on limit values

a no restriction



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 5 of 11

b End of exposure or shift

c in long-term exposure: after several shifts

d prior to next shift

STEL (EC): Short Term Exposure Limit TWA (EC): time-weighted average

U: Urea B: Blood

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: solvent like

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point:not determinedInitial boiling point and boiling range:82 °CSublimation point:No information available.Softening point:No information available.:No information available.

Flash point: 1 °C ISO 3679

Flammability

Solid: not applicable
Gas: not applicable

Lower explosion limits: 0,9 vol. %

Upper explosion limits: 12 vol. %



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 6 of 11

Ignition temperature: No information available.

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: not determined

Density (at 20 °C): 0,7525 g/cm³ DIN 51757

Bulk density:

Water solubility:

No information available.
easily soluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: No information available. DIN 53019-1
Viscosity / kinematic: No information available. DIN EN ISO 3104

(at 40 °C)

Flow time: No information available. DIN EN ISO 2431

(at 20 °C)

Vapour density:not determinedEvaporation rate:not determinedSolvent separation test:No information available.Solvent content:No information available.

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 7 of 11

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

Acute toxicity

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
64742-49-0	1-0 Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 mg/kg	> 5000	Rat	
	dermal	LD50 mg/kg	> 2000	Rabbit	
	inhalative (4 h) vapour	LC50	> 20 mg/l	Rat	
67-63-0	2-Propanol				
	oral	LD50	5280 mg/kg	Rat	
	dermal	LD50 mg/kg	> 2000	Rabbit	
	inhalative (4 h) vapour	LC50	47,5 mg/l	Rat	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics), (2-Propanol)

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



according to Regulation (EC) No 1907/2006

	Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
64742-49-0	Hydrocarbons C7-C9, n-alkanes	Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics				
	Acute fish toxicity	LC50	>1-10 mg/l		Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	>1-10 mg/l		Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	>10-100 mg/l	48 h	Daphnia magna	
67-63-0	2-Propanol					
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	> 100 mg/l		Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-49-0	Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics	4,0
67-63-0	2-Propanol	0,05

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors Classified as hazardous waste.

Waste disposal number of used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances Classified as hazardous waste.



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 9 of 11

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons C7-C9, n-alkanes,

iso-alkanes, cyclics, 2-Propanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Limited quantity: E2

Inland waterways transport (ADN)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons C7-C9, n-alkanes,

iso-alkanes, cyclics, 2-Propanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L

Other applicable information (inland waterways transport)

Limited quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons C7-C9, n-alkanes,

iso-alkanes, cyclics, propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Marine pollutant:yesSpecial Provisions:274Limited quantity:1 LEmS:F-E, S-E

Other applicable information (marine transport)

Limited quantity: E2

Air transport (ICAO)

14.1. UN number: UN 1993



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375		
Print date: 22.06.2016	Product code: 11AA536265L0200	Page 10 of 11

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons C7-C9, n-alkanes,

iso-alkanes, cyclics, propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 L

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

Limited quantity: E2 Passenger-LQ: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

Danger releasing substance: Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclics

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): EU/CH 100

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%



according to Regulation (EC) No 1907/2006

Kontakt-Reiniger 375

Print date: 22.06.2016 Product code: 11AA536265L0200 Page 11 of 11

LD50: Lethal dose, 50%

Relevant R phrases (number and full text)

11	Highly flammable.
36	Irritating to eyes.

51 Toxic to aquatic organisms.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Relevant H and EUH statements (number and full text)

H225	Highly flammable	liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)