



# Safety Data Sheet

according to UK REACH Regulation

## 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

372 Electronic Grease 200 ml A

UFI: 7K18-H082-K002-SGVC

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Lubricant, lubricants and release products

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: TUNAP GmbH & Co. KG  
Street: Bürgermeister-Seidl-Str. 2  
Place: D-82515 Wolfratshausen  
Telephone: + 49 (0) 8171/1600 - 0      Telefax: + 49 (0) 8171/1600 - 40  
E-mail: sdb@tunap.com  
Internet: www.tunap.com

##### Supplier

Company name: TUNAP (UK) Limited  
Street: Unit 12 Tonbridge Trade Park, Ingot Way  
Place: GB Tonbridge, Kent. TN9 1GN  
Telephone: +44 (0)1732 365163  
E-mail: sdb@tunap.com  
Internet: www.tunap.co.uk

#### 1.4. Emergency telephone number:

111 NHS (National Health Service)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
Skin Irrit. 2; H315  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane  
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
2-Propanol

Signal word: Danger

Pictograms:



##### Hazard statements

H222      Extremely flammable aerosol.

**Safety Data Sheet**

according to UK REACH Regulation

**372 Electronic Grease 200 ml A**

Revision date: 22.10.2024

Product code: 1100417

Page 2 of 13

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-63-0	2-Propanol			1 - < 3 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			

Full text of H and EUH statements: see section 16.



# Safety Data Sheet

according to UK REACH Regulation

## 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 3 of 13

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	5 - < 10 %
		inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	5 - < 10 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = 5500 mg/kg	
67-63-0	200-661-7	2-Propanol	1 - < 3 %
		inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5280 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

## SECTION 6: Accidental release measures



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 4 of 13

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

##### **For non-emergency personnel**

First aider: Pay attention to self-protection!

##### **For emergency responders**

Fight fire with normal precautions from a reasonable distance.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

##### **Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

##### **Further information on handling**

Avoid contact with skin and eyes.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

##### **Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

##### **Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**Safety Data Sheet**

according to UK REACH Regulation

**372 Electronic Grease 200 ml A**

Revision date: 22.10.2024

Product code: 1100417

Page 5 of 13

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day

**Additional advice on limit values**

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

TWA (EC): time-weighted average

U: Urea

B: Blood

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.

EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 6 of 13

be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

#### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	blue
Odour:	solvent like

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-40 °C
Flammability:	not determined
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,8 vol. %
Flash point:	-80 °C
Auto-ignition temperature:	> 200 °C
pH-Value (at 20 °C):	No information available.
Density (at 20 °C):	0,796 g/cm <sup>3</sup> ASTM D 792

### 9.2. Other information

#### Information with regard to physical hazard classes

Sustaining combustion: No data available

#### Other safety characteristics

Sublimation point: No information available.

Softening point: No information available.

Pour point: No information available.

#### Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

The product is stable under normal conditions.



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 7 of 13

#### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
67-63-0	2-Propanol				
	oral	LD50 5280 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat		

#### Irritation and corrosivity



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 8 of 13

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Vapours may cause drowsiness and dizziness.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

#### Specific effects in experiment on an animal

No information available.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### Other information

No information available.

#### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

**372 Electronic Grease 200 ml A**

Revision date: 22.10.2024

Product code: 1100417

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	Acute fish toxicity	LC50 > 1-10 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 1-10 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 2,045 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EC50 >1 - 10 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
67-63-0	2-Propanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna		

**12.2. Persistence and degradability**

There are no data available on the mixture itself. AOX (mg/l): 0

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	OECD Guideline 301 F	98%	28	ECHA
	Easily biodegradable (concerning to the criteria of the OECD)			
67-63-0	2-Propanol			
	OECD Prüfrichtlinie 301E	95 %	21	
	leicht biologisch abbaubar			

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 10 of 13

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	2,36
67-63-0	2-Propanol	0,05
106-97-8	butane	2,89

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 11 of 13

Tunnel restriction code: D

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: No  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

##### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/EEC)



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 12 of 13

#### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### SECTION 16: Other information

##### Changes

This data sheet contains changes from the previous version in section(s): 1,2,9.

##### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

##### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

##### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## Safety Data Sheet

according to UK REACH Regulation

### 372 Electronic Grease 200 ml A

Revision date: 22.10.2024

Product code: 1100417

Page 13 of 13

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*