

**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

373 Elektronik Öl 200 ml A

UFI: YRJ8-P00Q-5003-4PEG

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant

**1.3. Details of the supplier of the safety data sheet**

Company name: TUNAP GmbH & Co. KG  
Street: Buergermeister-Seidl-Strasse 2  
Place: D-82515 Wolfratshausen  
Telephone: +49 (0) 8171/1600-0      Telefax: +49 (0) 8171/1600-40  
E-mail: sdb@tunap.com  
Internet: www.tunap.com

**1.4. Emergency telephone number:** 111 NHS (National Health Service)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons C7-C9, iso-alkanes

**Signal word:** Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe Aerosol.



# Safety Data Sheet

according to UK REACH Regulation

## 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 2 of 13

P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64741-66-8	Hydrocarbons C7-C9, iso-alkanes			25 - < 50 %
	921-728-3		01-2119471305-42	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene			0.1 - < 1 %
	270-128-1		01-2119491299-23	
	Repr. 2, Aquatic Chronic 3; H361f H412			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
64741-66-8	921-728-3	Hydrocarbons C7-C9, iso-alkanes	25 - < 50 %	
	inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >9,4 mg/l (dusts or mists); dermal: LD50 = > 2200 - 2500 mg/kg; oral: LD50 = > 7100 - 7800 mg/kg			
68411-46-1	270-128-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	0.1 - < 1 %	
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.



## Safety Data Sheet

according to UK REACH Regulation

### 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 3 of 13

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### **4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Danger of bursting container.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

##### **For non-emergency personnel**

First aider: Pay attention to self-protection!

##### **For emergency responders**

Fight fire with normal precautions from a reasonable distance.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 4 of 13

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 5 of 13

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64741-66-8	Hydrocarbons C7-C9, iso-alkanes			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
68411-46-1	Benzenamine, N-phenyl-,reaction products with 2,4,4-trimethylpentene			
Worker DNEL, long-term		inhalation	systemic	0,6 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,08 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,14 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	0,04 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
68411-46-1	Benzenamine, N-phenyl-,reaction products with 2,4,4-trimethylpentene	
Freshwater		0,034 mg/l
Freshwater (intermittent releases)		0,51 mg/l
Marine water		0,003 mg/l
Freshwater sediment		0,446 mg/kg
Marine sediment		0,045 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1,76 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)  
Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to



## Safety Data Sheet

according to UK REACH Regulation

### 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 6 of 13

chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

#### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	light brown
Odour:	solvent like

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-40 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	9,4 vol. %
Flash point:	-26 °C
Auto-ignition temperature:	> 200 °C
pH-Value (at 20 °C):	
Viscosity / kinematic:	< 7 mm <sup>2</sup> /s
Density (at 20 °C):	0,6713 g/cm <sup>3</sup> DIN 51757

### 9.2. Other information

#### Information with regard to physical hazard classes

Sustaining combustion: No data available

#### Other safety characteristics

Sublimation point: not determined

Softening point: not determined

Pour point: not determined

#### Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions



# Safety Data Sheet

according to UK REACH Regulation

## 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 7 of 13

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64741-66-8	Hydrocarbons C7-C9, iso-alkanes				
	oral	LD50 > 7100 - 7800 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	dermal	LD50 > 2200 - 2500 mg/kg	Rabbit	Study report (1961)	Standard acute method, applying 4 differ
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Study report (1985)	OECD Guideline 403
	inhalation (4 h) dust/mist	LC50 > 9,4 mg/l	Rat		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 > 5 mg/l	Rat		

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Vapours may cause drowsiness and dizziness. After skin contact: irritant.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction



## Safety Data Sheet

according to UK REACH Regulation

### 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 8 of 13

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C7-C9, iso-alkanes)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

#### Specific effects in experiment on an animal

No information available.

#### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### 11.2. Information on other hazards

#### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meet the criteria.

#### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.



**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64741-66-8	Hydrocarbons C7-C9, iso-alkanes					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 ca. 2,4 mg/l	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC 0,778 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	QSAR
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
68411-46-1	Benzenamine, N-phenyl-,reaction products with 2,4,4-trimethylpentene					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Danio rerio	Study report (1988)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EC50 51 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202

**12.2. Persistence and degradability**

There are no data available on the mixture itself. AOX (mg/l): 0

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64741-66-8	Hydrocarbons C7-C9, iso-alkanes	4,5
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89
68411-46-1	Benzenamine, N-phenyl-,reaction products with 2,4,4-trimethylpentene	> 6

**BCF**

CAS No	Chemical name	BCF	Species	Source
64741-66-8	Hydrocarbons C7-C9, iso-alkanes	198,7	Mytilus edulis	REACH Registration D
68411-46-1	Benzenamine, N-phenyl-,reaction products with 2,4,4-trimethylpentene	411	Cyprinus carpio	Study report (2000)

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 10 of 13

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane)
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-

**Safety Data Sheet**

according to UK REACH Regulation

**373 Elektronik Öl 200 ml A**

Revision date: 14.02.2025

Product code: 1100443

Page 11 of 13

Hazard label: 2.1  
Marine pollutant: Yes  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes  
Danger releasing substance: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

**Additional information**Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/EEC)**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1.



## Safety Data Sheet

according to UK REACH Regulation

### 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 12 of 13

#### Abbreviations and acronyms

Flam. Gas: Flammable gases  
Aerosol: Aerosols  
Liquefied gas  
Flam. Liq: Flammable liquids  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Repr: Reproductive toxicity  
STOT SE: Specific target organ toxicity - single exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA: International Air Transport Association  
IMDG: International Maritime Code for Dangerous Goods  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
ATE: Acute Toxicity Estimate  
STEL (EC) Short Term Exposure Limit  
LC50: Lethal Concentration  
EC50: half maximal Effective Concentration  
ErC50: means EC50 in terms of reduction of growth rate

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## Safety Data Sheet

according to UK REACH Regulation

### 373 Elektronik Öl 200 ml A

Revision date: 14.02.2025

Product code: 1100443

Page 13 of 13

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*