

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

101 Liquid grease 400 ml AB

UFI: 4283-W059-P00W-DWRR

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant gease

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: TUNAP GmbH & Co. KG  
Street: Bürgermeister-Seidl-Str. 2  
Place: D-82515 Wolfratshausen  
Telephone: + 49 (0) 8171/1600 - 0      Telefax: + 49 (0) 8171/1600 - 40  
E-mail: sdb@tunap.com  
Internet: www.tunap.com

**Supplier**

Company name: TUNAP (UK) Limited  
Street: Unit 12 Tonbridge Trade Park, Ingot Way  
Place: GB Tonbridge, Kent. TN9 1GN  
Telephone: +44 (0)1732 365163  
E-mail: sdb@tunap.com  
Internet: www.tunap.co.uk

**1.4. Emergency telephone number:** 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Skin Sens. 1; H317  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane  
2,6-di-tert-butyl-4-nonylphenol

Signal word: Danger

Pictograms:



**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 2 of 13

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane			10 - < 20 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
4306-88-1	2,6-di-tert-butyl-4-nonylphenol			0.1 - < 1 %
	224-320-7		01-2120759723-46	
	Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			

Full text of H and EUH statements: see section 16.



# Safety Data Sheet

according to UK REACH Regulation

## 101 Liquid grease 400 ml AB

Revision date: 16.07.2024

Product code: 1101048

Page 3 of 13

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-49-0	931-254-9	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane	10 - < 20 %
		inhalation: LC50 = 73860 mg/l (vapours); dermal: LD50 = >2920 mg/kg; oral: LD50 = >5840 mg/kg	
4306-88-1	224-320-7	2,6-di-tert-butyl-4-nonylphenol	0.1 - < 1 %
		inhalation: LC50 = >10 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = >2000 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures



## Safety Data Sheet

according to UK REACH Regulation

### 101 Liquid grease 400 ml AB

Revision date: 16.07.2024

Product code: 1101048

Page 4 of 13

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear personal protection equipment.

#### For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

#### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 5 of 13

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane			
Worker DNEL, long-term		inhalation	systemic	5306 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1131 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1301 mg/kg bw/day
4306-88-1	2,6-di-tert-butyl-4-nonylphenol			
Worker DNEL, long-term		inhalation	systemic	7,84 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1,11 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,56 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,056 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
4306-88-1	2,6-di-tert-butyl-4-nonylphenol	
Freshwater		0,000124 mg/l
Freshwater (intermittent releases)		0,00124 mg/l
Marine water		0,012 mg/l
Freshwater sediment		106 mg/kg
Marine sediment		10,6 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		21,1 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift



## Safety Data Sheet

according to UK REACH Regulation

### 101 Liquid grease 400 ml AB

Revision date: 16.07.2024

Product code: 1101048

Page 6 of 13

blood (B)  
Urine (U)

#### 8.2. Exposure controls

##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

##### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
Thickness of the glove material 0,45 mm  
EN ISO 374

##### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: AX  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

##### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	odourless

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not applicable not applicable
Lower explosion limits:	1 vol. %
Upper explosion limits:	9,4 vol. %
Flash point:	-80 °C
Auto-ignition temperature:	258 °C
Decomposition temperature:	not determined

pH-Value (at 20 °C):	7	DIN 19268
----------------------	---	-----------

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

Solubility in other solvents  
not determined



## Safety Data Sheet

according to UK REACH Regulation

### 101 Liquid grease 400 ml AB

Revision date: 16.07.2024

Product code: 1101048

Page 7 of 13

Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,785 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Oxidizing properties

Not oxidising.

##### Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

Sublimation point: No information available.

Softening point: No information available.

Pour point: No information available.

##### Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

##### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane				
	oral	LD50 >5840 mg/kg	Rat		
	dermal	LD50 >2920 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 73860 mg/l	Rat	Industrial Medicine, Vol. 39, No. 5, May	OECD Guideline 403
4306-88-1	2,6-di-tert-butyl-4-nonylphenol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2017)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 >10 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

May cause an allergic skin reaction. (2,6-di-tert-butyl-4-nonylphenol)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C6, iso-alkanes, &lt; 5 % n-hexane)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

No information available.

**SECTION 12: Ecological information**

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 9 of 13

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name		Dose		[h]   [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane							
	Aquatic toxicity							
	Acute fish toxicity	LC50 mg/l	>10 -100	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50 mg/l	13,56	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)		The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 mg/l	31,9	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)		The aquatic toxicity was estimated by a
	Fish toxicity	NOEC mg/l	4,089	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)		The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	7,138	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)		The aquatic toxicity was estimated by a
4306-88-1	2,6-di-tert-butyl-4-nonylphenol							
	Acute fish toxicity	LC50 mg/l	> 10	96 h	Oncorhynchus mykiss	REACH Registration Dossier		OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier		OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,124	48 h	Daphnia magna	REACH Registration Dossier		OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier		OECD Guideline 209

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name		Value		d	Source
	Method					
	Evaluation					
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane					
	(OECD Prüfrichtlinie 301F)		98 %		28	
	Leichtbiologisch abbaubar					

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane	3,6
74-98-6	propane	2,36
106-97-8	butane	2,89
4306-88-1	2,6-di-tert-butyl-4-nonylphenol	> 6,5



## Safety Data Sheet

according to UK REACH Regulation

### 101 Liquid grease 400 ml AB

Revision date: 16.07.2024

Product code: 1101048

Page 10 of 13

#### BCF

CAS No	Chemical name	BCF	Species	Source
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane	501,187	Pimephales promelas	QSAR in Environmenta

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 11 of 13

Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial emissions: No information available.

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 12 of 13

Directive 2004/42/EC on VOC in  
paints and varnishes:

No information available.

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/EEC)

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,6,9,11.

**Abbreviations and acronyms**

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

**Safety Data Sheet**

according to UK REACH Regulation

**101 Liquid grease 400 ml AB**

Revision date: 16.07.2024

Product code: 1101048

Page 13 of 13

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*