

according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

926 AGR Ventil Reiniger MF92600250A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP Deutschland Vertriebs GmbH & Co.	TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG		
Street:	Bürgermeister-Seidl-Str. 2			
Place:	D-82515 Wolfratshausen			
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40		
e-mail:	sdb@tunap.com			
Internet:	www.tunap.com			
1.4. Emergency telephone	+49 (0) 30 30 686 790 (Giftnotruf Berlin)			

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 3 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Dam. 1 Hazard Statements: Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling 2-aminoethanol, ethanolamine

Signal word: Danger

Pictograms:



Hazard statements

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	Shoking.
P260	Do not breathe Aerosol.
P280	Wear eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of Water and soap
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A						
Print date: 29.03.2017	Product code: 1102036	Page 2 of 10				
	present and easy to do. Continue rinsing.					
P337+P313	If eye irritation persists: Get medical advice/attention.					
P314 Get medical advice/attention if you feel unwell.						
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.					
P251	Do not pierce or burn, even after use.					
Special labelling of ce	ertain mixtures					
	< 1 % by mass of the contents are flammable.					

2.3. Other hazards

Heating causes rise in pressure with risk of bursting.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-43-5	2-aminoethanol, ethanolamine			3 - < 5 %
	205-483-3			
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, STOT SE 3, Aquatic Chronic 3; H302 H312 H332 H314 H335 H412			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % amphoteric surfactants, perfumes.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 3 of 10

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Advice on storage compatibility

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 4 of 10

provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or shift

c in long-term exposure: after several shifts

d prior to next shift

STEL (EC) : Short Term Exposure Limit

TWA (EC): time-weighted average

U: Urea

B: Blood

8.2. Exposure controls

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min Thickness of the glove material 0,45 mm DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. When exceeding the relevant workplace exposure limits, note the following: Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Filtering device with filter or ventilator filtering device of type: A Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 5 of 10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state:	Aerosol		
	Colour:	yellow		
	Odour:	Lemon		
				Test method
	pH-Value (at 20 °C):		10,7	DIN 19268
	Changes in the physical state			
	Melting point:		No information available.	
	Initial boiling point and boiling range:		100 °C	
	Flash point:		179 °C	
	Lower explosion limits:		No information available.	
	Upper explosion limits:		No information available.	
	Vapour pressure:		No information available.	
	Vapour pressure:		No information available.	
	Density:		1 g/cm³	DIN 51757
	Bulk density:		not applicable	
	Partition coefficient:		No information available.	
	Viscosity / dynamic:		No information available.	
	Viscosity / kinematic:		No information available.	
	Flow time:		not applicable	
	Vapour density:		No information available.	
	Evaporation rate:		No information available.	
	Solvent separation test:		No information available.	
	Solvent content:		No information available.	
<u>9.</u>	2. Other information			
	Solid content:		No information available.	

Data apply to technical substance: Density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 6 of 10

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with acids.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
141-43-5	2-aminoethanol, ethanolamine					
	oral	LD50	1515 mg/kg	Rat		
	dermal	LD50	1025 mg/kg	Rabbit	IUCLID	
	inhalative (4 h) aerosol	LC50	1,3 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met. No indications of human carcinogenicity exist. No indications of human germ cell mutagenicity exist. No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 7 of 10

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Aquatic toxicity Dose [h] [d] Species				Source	
141-43-5	2-aminoethanol, ethanolamine	2-aminoethanol, ethanolamine					
	Acute fish toxicity	LC50	150 mg/l	96 h	Onchorhynchus mykiss	IUCLID	
	Acute algae toxicity	ErC50	22 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50	65 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-43-5	2-aminoethanol, ethanolamine	-1,91 (25°C)

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances

Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances

Classified as hazardous waste.

SECTION 14: Transport information

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A				
Print date: 29.03.2017	Product code: 1		Page 8 of 10	
14.4. Packing group:	-			
Hazard label:	2.2			
Classification code:	5A			
Special Provisions:	190 327 344 625			
Limited quantity:	1 L			
Excepted quantity:	E0			
Transport category: Tunnel restriction code:	3 E			
Inland waterways transport (ADN)	L			
<u>14.1. UN number:</u>	UN 1950			
14.2. UN proper shipping name:	AEROSOLS			
14.3. Transport hazard class(es):	2			
14.4. Packing group:	-			
Hazard label: Classification code:	2.2 5A			
Special Provisions:	190 327 344 625			
Limited quantity:	100 027 044 020 1 L			
Excepted quantity:	E0			
Marine transport (IMDG)				
<u>14.1. UN number:</u>	UN 1950			
14.2. UN proper shipping name:	AEROSOLS			
14.3. Transport hazard class(es):	2.2			
14.4. Packing group:	-			
Hazard label:	2.2			
Marine pollutant:	no			
Special Provisions:	63, 190, 277, 327, 344,	, 959		
Limited quantity:	1000 mL			
Excepted quantity:	E0			
EmS:	F-D, S-U			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number:</u>	UN 1950			
14.2. UN proper shipping name:	AEROSOLS, non-flamr	mable		
14.3. Transport hazard class(es):	2.2			
14.4. Packing group:	-			
Hazard label:	2.2			
Special Provisions:	A98 A145 A167 A802			
Limited quantity Passenger:	30 kg G			
Passenger LQ:	Y203			
Excepted quantity:	E0			
IATA-packing instructions - Passenger:		03		
IATA-max. quantity - Passenger:		5 kg		
IATA-packing instructions - Cargo:		03 50 kg		
IATA-max. quantity - Cargo:	1:	50 kg		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	no			
14.6. Special precautions for user No dangerous good in sense of this tr	ansport regulation.			



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 9 of 10

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC):

2004/42/EC (VOC):

No information available. No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]: Calculation method. Aerosol directive (75/324/EEC)

1 - slightly water contaminating

National regulatory information

Water contaminating class (D):

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA: International Air Transport Association IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate STEL (EC) Short Term Exposure Limit LC50: Lethal Concentration EC50: half maximal Effective Concentration ErC50: means EC50 in terms of reduction of growth rate Relevant H and EUH statements (number and full text) H229 Pressurised container: May burst if heated.

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG

Safety Data Sheet



according to Regulation (EC) No 1907/2006

926 AGR Ventil Reiniger MF92600250A

Print date: 29.03.2017

Product code: 1102036

Page 10 of 10

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)