

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 1 of 16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

377 Battery Pole Protective Lacquer 07377015W

UFI: JCU3-Q05U-X00A-9MVG

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Corrosion inhibitor

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: TUNAP GmbH & Co. KG  
Street: Bürgermeister-Seidl-Str. 2  
Place: D-82515 Wolfratshausen  
Telephone: + 49 (0) 8171/1600 - 0      Telefax: + 49 (0) 8171/1600 - 40  
E-mail: sdb@tunap.com  
Internet: www.tunap.com

**Supplier**

Company name: TUNAP (UK) Limited  
Street: Unit 12 Tonbridge Trade Park, Ingot Way  
Place: GB Tonbridge, Kent. TN9 1GN  
Telephone: +44 (0)1732 365163  
E-mail: sdb@tunap.com  
Internet: www.tunap.co.uk

**1.4. Emergency telephone number:** 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

methyl acetate  
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane  
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Hydrocarbons, C9, aromatics

**Signal word:** Danger**Pictograms:**



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 2 of 16

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 3 of 16

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
115-10-6	dimethyl ether			25 - < 50 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
79-20-9	methyl acetate			10 - < 20 %
	201-185-2	607-021-00-X		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
75-28-5	isobutane			10 - < 20 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			3 - < 5 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			3 - < 5 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-95-6	Hydrocarbons, C9, aromatics			1 - < 3 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
74-98-6	propane			1 - < 3 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			0.1 - < 1 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene			0.1 - < 1 %
	918-811-1		01-2119463583-34	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 4 of 16

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
79-20-9	201-185-2	methyl acetate	10 - < 20 %
		inhalation: LC50 = 49 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 6970 mg/kg	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3 - < 5 %
		inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	3 - < 5 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = 5500 mg/kg	
64742-95-6	918-668-5	Hydrocarbons, C9, aromatics	1 - < 3 %
		dermal: LD50 = > 3160 mg/kg; oral: LD50 = ca. 7093 mg/kg	
64742-94-5	918-811-1	Hydrocarbons, C10, aromatics, <1% naphthalene	0.1 - < 1 %
		inhalation: LC50 = > 5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 5 of 16

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

##### For non-emergency personnel

First aider: Pay attention to self-protection!

##### For emergency responders

Fight fire with normal precautions from a reasonable distance.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

##### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

##### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

##### Further information on handling

Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 6 of 16

**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 7 of 16

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
115-10-6	dimethyl ether			
Worker DNEL, long-term		inhalation	systemic	1894 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	471 mg/m <sup>3</sup>
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
64742-95-6	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	151 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	7,5 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
115-10-6	dimethyl ether	
Freshwater		0,155 mg/l
Freshwater (intermittent releases)		1,549 mg/l
Marine water		0,016 mg/l
Freshwater sediment		0,681 mg/kg
Marine sediment		0,069 mg/kg
Micro-organisms in sewage treatment plants (STP)		160 mg/l
Soil		0,045 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)

Urine (U)

**8.2. Exposure controls**



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 8 of 16

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

##### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
Thickness of the glove material 0,45 mm  
EN ISO 374

##### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: AX  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

##### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	dark blue
Odour:	solvent like

#### Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	40- °C
Flammability:	not applicable not applicable
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	32 vol. %
Flash point:	-80 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value (at 20 °C):	DIN 19268
Viscosity / kinematic:	< 7 mm <sup>2</sup> /s
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 9 of 16

Density (at 20 °C): 0,84 g/cm<sup>3</sup> DIN 51757  
Relative vapour density: not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Sustaining combustion: No data available  
Self-ignition temperature  
Solid: not applicable  
Gas: not applicable  
Oxidizing properties  
Not oxidising.

##### Other safety characteristics

Evaporation rate: not determined  
Solid content: not determined  
Sublimation point: No information available.  
Softening point: No information available.  
Pour point: No information available.

##### Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

##### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
79-20-9	methyl acetate				
	oral	LD50 6970 mg/kg	Rat	Gestis	
	dermal	LD50 5000 mg/kg	Rabbit	Gestis	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
64742-95-6	Hydrocarbons, C9, aromatics				
	oral	LD50 ca. 7093 mg/kg	Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 > 3160 mg/kg	Rabbit	Study report (1984)	OECD Guideline 402
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 > 5 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

May cause drowsiness or dizziness. (methyl acetate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 11 of 16

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

**Specific effects in experiment on an animal**

No information available.

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

The product is not: Ecotoxic.



# Safety Data Sheet

according to UK REACH Regulation

## 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
79-20-9	methyl acetate					
	Acute fish toxicity	LC50 >250 - 350 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 >120 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 1026 mg/l	48 h	Daphnia magna (Big water flea)		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	Acute fish toxicity	LC50 > 1-10 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 1-10 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 2,045 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EC50 >1 - 10 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
64742-95-6	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LL50 9,2 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 7,9 mg/l	72 h	Raphidocelis subcapitata	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EL50 3,2 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene					
	Acute fish toxicity	LC50 >1-<=10 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 >1-<=10 mg/l	96 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >1-<=10 mg/l	48 h	Daphnia magna		

### 12.2. Persistence and degradability

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 13 of 16

The product has not been tested.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
79-20-9	methyl acetate				
	OECD Prüfrichtlinie 301D		70%	28	
	leicht biologisch abbaubar				
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	OECD Guideline 301 F		98%	28	ECHA
	Easily biodegradable (concerning to the criteria of the OECD)				
64742-95-6	Hydrocarbons, C9, aromatics				
			78%	28	

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
75-28-5	isobutane	2,8
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
64742-95-6	Hydrocarbons, C9, aromatics	>= 3,03
74-98-6	propane	2,36
106-97-8	butane	2,89

**BCF**

CAS No	Chemical name	BCF	Species	Source
64742-95-6	Hydrocarbons, C9, aromatics	>= 30,85		REACH Registration D

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Safety Data Sheet**

according to UK REACH Regulation

**377 Battery Pole Protective Lacquer 07377015W**

Revision date: 16.08.2023

Product code: 1102209

Page 14 of 16

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Completely emptied packages can be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 15 of 16

Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

Warning: Flammable gases.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

##### **Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/EEC)

##### **National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

### **SECTION 16: Other information**

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,6,9,11.



## Safety Data Sheet

according to UK REACH Regulation

### 377 Battery Pole Protective Lacquer 07377015W

Revision date: 16.08.2023

Product code: 1102209

Page 16 of 16

#### Abbreviations and acronyms

Flam. Gas: Flammable gases  
Aerosol: Aerosols  
Liquefied gas  
Flam. Liq: Flammable liquids  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Eye Irrit: Eye irritation  
STOT SE: Specific target organ toxicity - single exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*