Product Information



Professional **156** Oil Stabiliser

Oil stabiliser with OMC2 technology for significant friction reduction. Minimises wear and high oil consumption. Active agent concentrate for safeguarding the engine oil viscosity class over the entire inspection interval. Conforms to standard API and CCMC synthetic oil standards.



Properties

- ✓ Safeguards the viscosity class up to the next oil change
- ✓ Protects and stabilises the lubrication film even under extreme loading thanks to OMC² technology
- Helps to reduce oil consumption
- ✓ Promotes a quiet, smooth-running engine

Application area

- ✓ With insufficient oil viscosity
- On long journeys under difficult
- ✓ conditions, e.g. when towing in warm climatic zones
- ✓ With increased oil consumption

Instructions

Add to the motor oil.

Dosing

Sufficient for up to 4.5 litres of engine oil. Harmless dosing to max. 20% of the engine oil filling quantity

Notice

 The preventive oil additive achieves full efficacy with all mineral-based and synthetic engine oils, in all viscosity grades, and with all national and international specifications

Product Description	Contents	Packaging Unit	Article Number
Oil Stabiliser	300 ml	24 PCS	MP15600300AB



The information herein is the product of careful testing. It is to be considered a recommendation compliant with state of the art knowledge where use is concerned. We cannot accept any liability whatsoever in view of the multiplicity of possible uses and working methods. No contractual relationship is hence implied and no ancillary obligations arise from any contract of sale that may be made. Product information is only valid in its latest current form. TUNAP (U.K) Limited | Unit L4 Deacon Trading Estate, Morley Road, Tonbridge, Kent TN9 1RA | Telephone +44 (0) 1732 365163 | e-Mail: sales@tunap.co.uk

PI 156 20191021