Print date: 09.01.2025



# **Safety Data Sheet**

according to UK REACH Regulation

## 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

904 Interior Comfort 400 ml X6

UFI: TS78-X0XN-M00Q-D2U0

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant

### 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

### **GB CLP Regulation**

Signal word: Danger

Pictograms:



#### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

# **Precautionary statements**

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe Aerosol.

P280 Wear eye protection/face protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

# **SECTION 3: Composition/information on ingredients**

Print date: 09.01.2025



# **Safety Data Sheet**

according to UK REACH Regulation

### 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 2 of 11

#### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation	)			
106-97-8	butane			50 - < 100 %	
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Liquefied gas; H220				
8042-47-5	White mineral oil (petroleum)	5 - < 10 %			
	232-455-8		01-2119487078-27		
	Asp. Tox. 1; H304				
90622-57-4	Hydrocarbons, C11-C12, isoalkane	1 - < 3 %			
	918-167-1		01-2119472146-39		
	Flam. Liq. 3, Asp. Tox. 1; H226 H3				

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Limits, M-factors and ATE		
8042-47-5	232-455-8	White mineral oil (petroleum)	5 - < 10 %	
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			
90622-57-4	918-167-1	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	1 - < 3 %	
	inhalation: LC50 = >25 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			

# Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

## **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

# After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



according to UK REACH Regulation

## 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 3 of 11

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

## Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Danger of bursting container.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

## For non-emergency personnel

First aider: Pay attention to self-protection!

## For emergency responders

Fight fire with normal precautions from a reasonable distance.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

### 6.3. Methods and material for containment and cleaning up

## For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

# Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated



according to UK REACH Regulation

# 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 4 of 11

by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

#### Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

# Further information on handling

Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

# Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

### **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
8042-47-5	White mineral oil (petroleum)				
Worker DNEL,	long-term	inhalation	systemic	164,56 mg/m³	
Worker DNEL, long-term		dermal	systemic	217,05 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	systemic	34,78 mg/m³	
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day	

#### Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)

Urine (U)



according to UK REACH Regulation

#### 904 Interior Comfort 400 ml X6

Product code: 1102440 Page 5 of 11 Revision date: 21.11.2024

#### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

#### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

## **Environmental exposure controls**

Observe legal regulations and provisions.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: colorless, clear Odour: characteristic

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and

-0.5 °C

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: 1,4 vol. % Upper explosion limits: 9.4 vol. % -80 °C Flash point: Decomposition temperature: not determined

pH-Value (at 20 °C): **DIN 19268** 

Viscosity / kinematic:  $< 7 \text{ mm}^2/\text{s}$ 

Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined



according to UK REACH Regulation

#### 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 6 of 11

Density (at 20 °C): 0,8299 g/cm³ DIN 51757

Relative vapour density: not determined

#### 9.2. Other information

#### Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined

**Further Information** 

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

# 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

## 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

#### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

# Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

# **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

#### 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 7 of 11

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
8042-47-5	White mineral oil (petrole	eum)						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1987)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1987)	OECD Guideline 402		
	inhalation (4 h) dust/mist	LC50	>5 mg/l	Rat				
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics							
	oral	LD50 mg/kg	> 5000	Rat	Study report (1995)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1993)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50	>25 mg/l	Rat				

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

# STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

#### Specific effects in experiment on an animal

No information available.

# 11.2. Information on other hazards

#### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Other information

No information available.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

The product is not: Ecotoxic.



according to UK REACH Regulation

# 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 8 of 11

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
8042-47-5	White mineral oil (petroleum)						
	Acute fish toxicity	LL50 mg/l	> 10000		Leuciscus idus melanotus	Study report (1992)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus		
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics						
	Acute algae toxicity	ErC50 mg/l	> 1000		Pseudokirchneriella subcapitata	Study report; company data (1995)	OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,209	28 d	Oncorhynchus mykiss	Company report (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	> 1 mg/l	21 d	Daphnia magna	Study report; company data (2012)	OECD Guideline 211

# 12.2. Persistence and degradability

The product has not been tested.

# 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
8042-47-5	White mineral oil (petroleum)	> 3,5

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	144,3	calculated	Other company data (

## 12.4. Mobility in soil

The product has not been tested.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

# **Further information**

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.



according to UK REACH Regulation

#### 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 9 of 11

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

# **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: Hazard label: 2 1

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2, see SP63

Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1 14.4. Packing group: -



according to UK REACH Regulation

904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 10 of 11

Hazard label: 2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial

emissions:

Directive 2004/42/EC on VOC in

No information available.

No information available.

paints and varnishes:

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

**National regulatory information** 

Water hazard class (D): 1 - slightly hazardous to water

# **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 2,9.



according to UK REACH Regulation

## 904 Interior Comfort 400 ml X6

Revision date: 21.11.2024 Product code: 1102440 Page 11 of 11

## Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)