



Safety Data Sheet

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

974 Injector Direct Protection, Petrol MF97400200A3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Additive

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP GmbH & Co. KG	
Street:	Buergermeister-Seidl-Strasse 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600-0	Telefax: +49 (0) 8171/1600-40
E-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

1.4. Emergency telephone number:

111 NHS (National Health Service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

2-Propanol

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P273	Avoid release to the environment.
P305+P354+P338	IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



Safety Data Sheet

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 2 of 15

P337+P313

If eye irritation persists: Get medical advice/attention.

P304+P312

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P501

Dispose of contents/container according to the official regulations.

2.3. Other hazards

Endocrine disrupting properties: 2,6-di-tert-butyl-p-cresol.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	2-Propanol			50 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
	Polyether amine, polymer			5 - < 10 %
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411			
128-37-0	2,6-di-tert-butyl-p-cresol			1 - < 3 %
	204-881-4		01-2119565113-46	
	Aquatic Chronic 1; H410			
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine			0.1 - < 1 %
	701-177-3		01-2119488991-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 1; H332 H315 H318 H410			
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol			0.1 - < 1 %
	202-414-9		01-2119777867-13	
	Acute Tox. 4, Skin Corr. 1C, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H373 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	2-Propanol	50 - < 100 %
		inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5280 mg/kg	
128-37-0	204-881-4	2,6-di-tert-butyl-p-cresol	1 - < 3 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg	
	701-177-3	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	0.1 - < 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 1,37 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg	
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	0.1 - < 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = ca. 1085 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.



Safety Data Sheet

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 3 of 15

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures**General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 4 of 15

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 5 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
128-37-0	2,6-di-tert-butyl-p-cresol			
Worker DNEL, long-term		inhalation	systemic	1,76 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,435 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine			
Worker DNEL, long-term		inhalation	systemic	0,8 mg/m ³
Worker DNEL, long-term		dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,4 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,5 mg/kg bw/day
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol			
Worker DNEL, long-term		inhalation	systemic	0,46 mg/m ³
Worker DNEL, acute		inhalation	systemic	14 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,06 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	2 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 6 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
128-37-0	2,6-di-tert-butyl-p-cresol	
Freshwater		0,000199 mg/l
Freshwater (intermittent releases)		0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater sediment		0,458 mg/kg
Marine sediment		0,046 mg/kg
Secondary poisoning		16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,017 mg/l
Soil		0,054 mg/kg
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,004 mg/l
Marine water		0 mg/l
Freshwater sediment		0,057 mg/kg
Marine sediment		0,006 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		1,71 mg/kg
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	
Freshwater		0 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0 mg/l
Freshwater sediment		0,376 mg/kg
Marine sediment		0,038 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,27 mg/l
Soil		0,075 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

TWA (EC): time-weighted average

U: Urea

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to



Safety Data Sheet

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 7 of 15

chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	blue
Odour:	amine-like

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	78 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	2 vol. %
Flash point:	12 vol. %
Auto-ignition temperature:	13 °C ISO 3679
Decomposition temperature:	425 °C
pH-Value (at 20 °C):	not determined
Viscosity / kinematic: (at 40 °C)	not determined
Water solubility:	DIN 19268
Solubility in other solvents:	< 7 mm ² /s DIN EN ISO 3104
Partition coefficient n-octanol/water:	The study does not need to be conducted because the substance is known to be insoluble in water.
Vapour pressure:	not determined
Density (at 20 °C):	not determined
Relative vapour density:	0,799 g/cm ³

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 8 of 15

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	not determined
Sublimation point:	No information available.
Softening point:	No information available.
Viscosity / dynamic:	No information available. DIN 53019-1
Flow time: (at 20 °C)	No information available. DIN EN ISO 2431

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 9 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	2-Propanol				
	oral	LD50 mg/kg 5280	Rat		
	dermal	LD50 mg/kg > 2000	Rabbit		
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat		
128-37-0	2,6-di-tert-butyl-p-cresol				
	oral	LD50 mg/kg > 6000	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rat	Study report (1988)	OECD Guideline 402
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine				
	oral	LD50 mg/kg > 5000	Rat	Study report (1981)	OECD Guideline 401
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) dust/mist	LC50 1,37 mg/l	Rat		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
	oral	LD50 mg/kg ca. 1085	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 mg/kg >2000	Rabbit		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (2-Propanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 10 of 15

Endocrine disrupting properties

Endocrine disrupting properties: 2,6-di-tert-butyl-p-cresol.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	2-Propanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	
128-37-0	2,6-di-tert-butyl-p-cresol					
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Raphidocelis subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACH Registration Dossier OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	Activated sludge	Study report (2000) OECD Guideline 209
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine					
	Acute fish toxicity	LC50 mg/l	> 0,43	96 h	Leuciscus idus	REACH Registration Dossier EU Method C.1
	Acute algae toxicity	ErC50	5,1 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,53	48 h	Daphnia magna	REACH Registration Dossier EU Method C.2
	Crustacea toxicity	NOEC mg/l	>= 0,183	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	1300	3 h	Activated sludge	REACH Registration Dossier OECD Guideline 209
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol					
	Acute fish toxicity	LC50	0,3 mg/l	96 h	Danio rerio (zebrafish)	
	Acute algae toxicity	ErC50 mg/l	0,03	72 h	Desmodesmus subspicatus	Study report (2010) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,163	48 h	Daphnia magna	Study report (2010) OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 12 of 15

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
67-63-0	2-Propanol				
	OECD Prüfrichtlinie 301E		95 %	21	
	leicht biologisch abbaubar				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	2-Propanol	0,05
128-37-0	2,6-di-tert-butyl-p-cresol	5,03
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	>= 3,5
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	8,4

BCF

CAS No	Chemical name	BCF	Species	Source
128-37-0	2,6-di-tert-butyl-p-cresol	465	fish	REACH Registration D
	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	1,98	fish	BCFBAF version 3.01
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	371,8		EPIWIN calculation (

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 13 of 15

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL) (solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL) (solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL) (solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Marine pollutant: no
Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL) (solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Special Provisions: A180
Limited quantity Passenger: 1 L

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 14 of 15

Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Additional information

94/69/EC (21st ATP). The benzene content of the product is less than 0.1%. It applies the annotation P. Classification and labeling as carcinogenic is not necessary.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,6,11.

**Safety Data Sheet**

according to UK REACH Regulation

974 Injector Direct Protection, Petrol MF97400200A3

Revision date: 07.09.2023

Product code: 1102602

Page 15 of 15

Abbreviations and acronyms

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)