

## **Safety Data Sheet**

according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 1 of 16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

984 Injector Direct Protection Diesel MF98400500AB

UFI: 0NY2-90HD-P00E-KFNE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Additive

#### 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Flam. Liq. 3; H226 Asp. Tox. 1; H304 Eye Dam. 1; H318 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## **GB CLP Regulation**

### Hazard components for labelling

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2-methylpropan-1-ol; iso-butanol

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycles, < 2% aromatics

Signal word: Danger

Pictograms:







# **Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe vapours.

P273 Avoid release to the environment.



according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 2 of 16

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P317 If eye irritation persists: Get medical help.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a POISON CENTER/doctor.

### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

Endocrine disrupting properties: 2,6-di-tert-butyl-p-cresol.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation)					
64742-48-9	Hydrocarbons, C10-C13, n-alkanes	s, isoalkanes, cyclics, <2% aromatics	5	50 - < 100 %		
	918-481-9		01-2119457273-39			
	Asp. Tox. 1; H304 EUH066					
78-83-1	2-methylpropan-1-ol; iso-butanol			5 - < 10 %		
	201-148-0	603-108-00-1				
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam.	1315 H318 H335 H336				
27247-96-7	2-Ethylhexyl nitrate		5 - < 10 %			
	248-363-6		01-2119539586-27			
	Acute Tox. 4, Acute Tox. 4, Acute T	2 H302 H411 EUH044				
64742-48-9	Hydrocarbons, C10-C13, n-alkanes	s	1 - < 3 %			
	918-481-9					
	Flam. Liq. 3, Asp. Tox. 1; H226 H30					
128-37-0	2,6-di-tert-butyl-p-cresol		1 - < 3 %			
	204-881-4		01-2119565113-46			
	Aquatic Chronic 1; H410					
104-76-7	2-Ethylhexan-1-ol			1 - < 3 %		
	203-234-3		01-2119487289-20			
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit.	335				

Full text of H and EUH statements: see section 16.



### **Safety Data Sheet**

according to UK REACH Regulation

#### 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Limits, M-factors and ATE				
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 100 %			
	inhalation: LC5 mg/kg	50 = 4951 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = >8000				
78-83-1	201-148-0	2-methylpropan-1-ol; iso-butanol	5 - < 10 %			
	inhalation: LC5 mg/kg	inhalation: LC50 = > 24 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2830				
27247-96-7	248-363-6	2-Ethylhexyl nitrate	5 - < 10 %			
		50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 ; oral: LD50 = >9640 mg/kg				
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycles, < 2% aromatics	1 - < 3 %			
	inhalation: LC5 mg/kg	50 = > 4951 mg/l (vapours); dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 5000				
128-37-0	204-881-4	2,6-di-tert-butyl-p-cresol	1 - < 3 %			
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg					
104-76-7	203-234-3	2-Ethylhexan-1-ol	1 - < 3 %			
	1	50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 g; oral: LD50 = 2047 mg/kg				

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous



### **Safety Data Sheet**

according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 4 of 16

products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

#### For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

### Further information on handling

Avoid contact with skin and eyes.

## 7.2. Conditions for safe storage, including any incompatibilities



according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 5 of 16

## Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

## Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

## 7.3. Specific end use(s)

Additive

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
104-76-7	2-ethylhexan-1-ol	1	5.4		TWA (8 h)	WEL
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
27247-96-7	2-Ethylhexyl nitrate			
Worker DNEL,	long-term	inhalation	systemic	0,35 mg/m³
Worker DNEL,	long-term	dermal	systemic	1 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,52 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,025 mg/kg bw/day
128-37-0	2,6-di-tert-butyl-p-cresol			
Worker DNEL,	long-term	inhalation	systemic	1,76 mg/m³
Worker DNEL,	long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,435 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	0,25 mg/kg bw/day



### **Safety Data Sheet**

according to UK REACH Regulation

# 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 6 of 16

#### **PNEC values**

CAS No	Substance	
Environmenta	al compartment	Value
27247-96-7	2-Ethylhexyl nitrate	
Freshwater		0,0008 mg/l
Marine water		0,00008 mg/l
Freshwater s	ediment	0,00074 mg/kg
Marine sedim	nent	0,00074 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	10 mg/l
Soil		0,000191 mg/kg
128-37-0	2,6-di-tert-butyl-p-cresol	
Freshwater	-	0,000199 mg/l
Freshwater (i	intermittent releases)	0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater sediment		0,458 mg/kg
Marine sediment		0,046 mg/kg
Secondary poisoning 16,67 mg		16,67 mg/kg
Micro-organisms in sewage treatment plants (STP) 0,017 mg		0,017 mg/l
Soil		0,054 mg/kg

### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

# Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:



according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 7 of 16

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

#### **Environmental exposure controls**

Observe legal regulations and provisions.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: green Odour: solvent like

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and

100 °C

boiling range:

not applicable

Flammability:

not applicable 0,5 vol. %

Lower explosion limits:

7 vol. %

Upper explosion limits: Flash point:

33 °C ISO 3679

Auto-ignition temperature: Decomposition temperature: No information available.

pH-Value (at 20 °C):

not determined **DIN 19268** 

Viscosity / kinematic:

20,5 mm<sup>2</sup>/s DIN EN ISO 3104

(at 40 °C)

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure: Density (at 20 °C): not determined 0,8 g/cm3 DIN 51757

Relative vapour density:

not determined

### 9.2. Other information

## Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable Gas: not applicable

Oxidizing properties Not oxidising.

### Other safety characteristics

Evaporation rate: not determined No information available. Solvent separation test: Solvent content: No information available. Solid content: not determined Sublimation point: No information available. Softening point: No information available. No information available.

No information available. DIN 53019-1

Viscosity / dynamic:



### **Safety Data Sheet**

according to UK REACH Regulation

# 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 8 of 16

Flow time: (at 20 °C) No information available. DIN EN ISO 2431

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Flammable.

#### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

#### 10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

### Toxicocinetics, metabolism and distribution

No information available.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 12,5 mg/l



# **Safety Data Sheet**

according to UK REACH Regulation

# 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 9 of 16

CAS No	Chemical name								
	Exposure route	Dose	Species	Source	Method				
64742-48-9	Hydrocarbons, C10-C13,	n-alkanes, isoalkanes	, cyclics, <2% arom	atics	•				
	oral	LD50 >8000 mg/kg	Rat						
	dermal	LD50 >3160 mg/kg	Rabbit						
	inhalation (4 h) vapour	LC50 4951 mg	g/I Rat						
78-83-1	2-methylpropan-1-ol; iso-	butanol							
	oral	LD50 > 2830 mg/kg	Rat						
	dermal	LD50 > 2000 mg/kg	Rat						
	inhalation (4 h) vapour	LC50 > 24 mg	/I Rat						
27247-96-7	2-Ethylhexyl nitrate								
	oral	LD50 >9640 mg/kg	Rat						
	dermal	LD50 >4820 mg/kg	Rabbit						
	inhalation (4 h) vapour	LC50 11 mg/l	Rat						
	inhalation dust/mist	ATE 1,5 mg/l							
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycles, < 2% aromatics								
	oral	LD50 > 5000 mg/kg	Rat						
	dermal	LD50 > 3160 mg/kg	Rabbit						
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat						
128-37-0	2,6-di-tert-butyl-p-cresol								
	oral	LD50 > 6000 mg/kg	Rat	Study report (1989)	OECD Guideline 401				
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402				
104-76-7	2-Ethylhexan-1-ol								
	oral	LD50 2047 mg/kg	Rat						
	dermal	LD50 > 3000 mg/kg	Rat						
	inhalation (4 h) vapour	LC50 11 mg/l	Rat						
	inhalation dust/mist	ATE 1,5 mg/l							

### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

## Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction



## **Safety Data Sheet**

according to UK REACH Regulation

### 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 10 of 16

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

#### Specific effects in experiment on an animal

No information available.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

Endocrine disrupting properties: 2,6-di-tert-butyl-p-cresol.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

# 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 11 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
4742-48-9	Hydrocarbons, C10-C13,	n-alkanes, is	soalkanes, c	yclics, <2	2% aromatics		
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	96 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna		
'8-83-1	2-methylpropan-1-ol; iso-l	outanol					
	Acute fish toxicity	LC50 mg/l	1430	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	1250		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	1439	48 h	Daphnia magna		
27247-96-7	2-Ethylhexyl nitrate						
	Acute fish toxicity	LC50	2 mg/l	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 12,6	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 12,6	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209
64742-48-9	Hydrocarbons, C10-C13,	n-alkanes, is	soalkanes, c	ycles, < 2	2% aromatics		
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	96 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna		
128-37-0	2,6-di-tert-butyl-p-cresol						
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACh Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ( )	> 10000	3 h	Activated sludge	Study report (2000)	OECD Guideline 209
104-76-7	2-Ethylhexan-1-ol			-			



## **Safety Data Sheet**

according to UK REACH Regulation

	984	Injecto	r Direct Pr	otecti	on Diesel MF98400	500AB	
1	Revision date: 12.08.2024		Pro	duct co	de: 1102614		Page 12 of 16
	Acute fish toxicity	LC50 mg/l	17,1		Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 mg/l	11,5	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50	39 mg/l	48 h	Daphnia magna		

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name						
	Method	Method Value d Source					
	Evaluation						
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
	OECD Guideline 301 F 89,8 28 ECHA						
	Readily biodegradable (according to OECD criteria).						
104-76-7	2-Ethylhexan-1-ol						
	OECD Guideline 301 C	79 – 99,9 %	14				

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79
27247-96-7	2-Ethylhexyl nitrate	5,24
128-37-0	2,6-di-tert-butyl-p-cresol	5,03
104-76-7	2-Ethylhexan-1-ol	2,9

### **BCF**

CAS No	Chemical name	BCF	Species	Source
128-37-0	2,6-di-tert-butyl-p-cresol	465	fish	REACh Registration D

#### 12.4. Mobility in soil

The product has not been tested.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

### List of Wastes Code - residues/unused products

070704

WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste



## **Safety Data Sheet**

according to UK REACH Regulation

### 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 13 of 16

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (iso-butanol)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 **Special Provisions:** 274 601 Limited quantity: 5 I Excepted quantity: E1 Transport category: 3 Hazard No: 30 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (iso-butanol)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Special Provisions:274 601Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (iso-butanol)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Marine pollutant:no

Special Provisions: 223, 274, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (iso-butanol)

14.3. Transport hazard class(es): 3
14.4. Packing group: |||



### **Safety Data Sheet**

according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 14 of 16

Hazard label: 3
Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial

emissions:

No information available.

Directive 2004/42/EC on VOC in

paints and varnishes:

No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,9,11,15.



according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 15 of 16

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL: Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

ATEL (EC): Short Term Exposure Limit

LC50: Lethal Concentration

EC50:half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Olassification for mixtures at	Olassinication for mixtures and asca evaluation method according to OB OLI Acquiation				
Classification Classification procedure					
Flam. Liq. 3; H226	On basis of test data				
Asp. Tox. 1; H304	Calculation method				
Eye Dam. 1; H318	Calculation method				
Aquatic Chronic 3; H412	Calculation method				

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be





# **Safety Data Sheet**

according to UK REACH Regulation

## 984 Injector Direct Protection Diesel MF98400500AB

Revision date: 12.08.2024 Product code: 1102614 Page 16 of 16

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)