

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

984 Injector Direct Protection Diesel MF98400500AB

UFI: ONY2-90HD-P00E-KFNE

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Additive

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: TUNAP GmbH & Co. KG
Street: Bürgermeister-Seidl-Str. 2
Place: D-82515 Wolfratshausen
Telephone: + 49 (0) 8171/1600 - 0
e-mail: sdb@tunap.com
Internet: www.tunap.com

Telefax: + 49 (0) 8171/1600 - 40

Supplier

Company name: TUNAP UK Limited
Street: Unit L4 Deacon Trading Estate, Morley Road
Place: GB Tonbridge, Kent. TN9 1RA
Telephone: +44 (0)1732 365163
e-mail: sdb@tunap.com
Internet: www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226
Asp. Tox. 1; H304
Eye Dam. 1; H318
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
2-methylpropan-1-ol; iso-butanol

Signal word: Danger**Pictograms:****Hazard statements**

H226 Flammable liquid and vapour.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 2 of 14

H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P280	Wear eye protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - < 100 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
78-83-1	2-methylpropan-1-ol; iso-butanol			5 - < 10 %
	201-148-0	603-108-00-1		
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			
27247-96-7	2-Ethylhexyl nitrate			5 - < 10 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H332 H312 H302 H411 EUH044 EUH066			
64742-48-9	Naphtha Petroleum Hydro treated Heavy			1 - < 3 %
	918-481-9			
	Flam. Liq. 3, Asp. Tox. 1; H226 H304			
128-37-0	2,6-di-tert-butyl-4-kresol			1 - < 3 %
	204-881-4		01-2119555270-46	
	Aquatic Chronic 1; H410			
104-76-7	2-Ethylhexan-1-ol			1 - < 3 %
	203-234-3		01-2119487289-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H332 H315 H319 H335			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 100 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = >8000 mg/kg	
78-83-1	201-148-0	2-methylpropan-1-ol; iso-butanol	5 - < 10 %
		inhalation: LC50 = > 24 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2830 mg/kg	
27247-96-7	248-363-6	2-Ethylhexyl nitrate	5 - < 10 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >4820 mg/kg; oral: LD50 = >9640 mg/kg	
64742-48-9	918-481-9	Naphtha Petroleum Hydro treated Heavy	1 - < 3 %
		inhalation: LC50 = > 4951 mg/l (vapours); dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 5000 mg/kg	
104-76-7	203-234-3	2-Ethylhexan-1-ol	1 - < 3 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 3000 mg/kg; oral: LD50 = 2047 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous



Safety Data Sheet

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 4 of 14

products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 5 of 14

Additive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
104-76-7	2-ethylhexan-1-ol	1	5.4		TWA (8 h)	WEL
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
27247-96-7	2-Ethylhexyl nitrate				
		Worker DNEL, long-term	inhalation	systemic	0,35 mg/m ³
		Worker DNEL, long-term	dermal	systemic	1 mg/kg bw/day
		Consumer DNEL, long-term	dermal	systemic	0,52 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	0,025 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
27247-96-7	2-Ethylhexyl nitrate		
		Freshwater	0,0008 mg/l
		Marine water	0,00008 mg/l
		Freshwater sediment	0,00074 mg/kg
		Marine sediment	0,00074 mg/kg
		Micro-organisms in sewage treatment plants (STP)	10 mg/l
		Soil	0,000191 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)

Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 6 of 14

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	green
Odour:	solvent like

Test method**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	100 °C
Sublimation point:	No information available.
Softening point:	No information available.
:	No information available.
Flash point:	33 °C ISO 3679

Flammability

Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	0,5 vol. %
Upper explosion limits:	7 vol. %
Auto-ignition temperature:	No information available.

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

pH-Value (at 20 °C): DIN 19268

Viscosity / dynamic: No information available. DIN 53019-1

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 7 of 14

Viscosity / kinematic: (at 40 °C)	20,5 mm ² /s	DIN EN ISO 3104
Flow time: (at 20 °C)	No information available.	DIN EN ISO 2431
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,8 g/cm ³	DIN 51757
Relative vapour density:	not determined	

9.2. Other information**Information with regard to physical hazard classes**

Oxidizing properties
Not oxidising.

Other safety characteristics

Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	not determined
Evaporation rate:	not determined

Further Information**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 8 of 14

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >8000 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 24 mg/l	Rat		
27247-96-7	2-Ethylhexyl nitrate				
	oral	LD50 >9640 mg/kg	Rat		
	dermal	LD50 >4820 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
64742-48-9	Naphtha Petroleum Hydro treated Heavy				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat		
104-76-7	2-Ethylhexan-1-ol				
	oral	LD50 2047 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 9 of 14

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 1430 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 1250 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 1439 mg/l	48 h	Daphnia magna		
27247-96-7	2-Ethylhexyl nitrate					
	Acute fish toxicity	LC50 2 mg/l	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 12,6 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 12,6 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Acute bacteria toxicity	(EC50 > 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (2010)	OECD Guideline 209
64742-48-9	Naphtha Petroleum Hydro treated Heavy					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
104-76-7	2-Ethylhexan-1-ol					
	Acute fish toxicity	LC50 17,1 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 11,5 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 39 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 11 of 14

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79
27247-96-7	2-Ethylhexyl nitrate	5,24
104-76-7	2-Ethylhexan-1-ol	2,9

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (iso-butanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 12 of 14

Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Marine pollutant: no
Special Provisions: 223, 274, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 13 of 14

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,5,6.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Dam. 1; H318	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.

**Safety Data Sheet**

according to UK REACH Regulation

984 Injector Direct Protection Diesel MF98400500AB

Revision date: 19.04.2022

Product code: 1102614

Page 14 of 14

H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)