



according to Regulation (EC) No 1907/2006

BIKELINE Multifunktionsöl 125ml D-GB

Print date: 24.01.2021

Product code: 1103006

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

BIKELINE Multifunktionsöl 125ml D-GB

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant, lubricants and release products

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+ 49 (0) 8171/1600 - 0	Telefax: + 49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

Supplier

Company name:	TUNAP UK Limited
Street:	Unit L4 Deacon Trading Estate, Morley Road
Place:	GB Tonbridge, Kent. TN9 1RA
Telephone:	+44 (0)1732 365163
e-mail:	sdb@tunap.com
Internet:	www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger**Pictograms:**

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 2 of 13

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container according to the official regulations.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			25 - < 50 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			0.1 - < 1 %
	939-603-7		01-2119978241-36	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 3 of 13

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean



BIKELINE Multifunktionsöl 125ml D-GB

Print date: 24.01.2021

Product code: 1103006

Page 4 of 13

contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			
Worker DNEL, long-term		inhalation	systemic	35,26 mg/m ³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Worker DNEL, acute		dermal	local	1,04 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, acute		dermal	local	0,518 mg/cm ²
Consumer DNEL, long-term		oral	systemic	2,5 mg/kg bw/day

PNEC values

CAS No	Substance	Value
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	
Environmental compartment		
Freshwater		0,1 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,1 mg/l
Freshwater sediment		45211 mg/kg
Marine sediment		45211 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		36739,74 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 6 of 13

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min
Thickness of the glove material 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	brown
Odour:	sweetish

pH-Value (at 20 °C):	not determined	Test method DIN 19268
----------------------	----------------	---------------------------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-11,7 °C
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Flash point:	> 23 °C
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	0,5 vol. %
Upper explosion limits:	15 vol. %
Ignition temperature:	> 200 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 7 of 13

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,7828 g/cm³ DIN 51757

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / kinematic: < 7 mm²/s

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 8 of 13

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1993)
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat	
75-28-5	isobutane			
	inhalation vapour	LC50 1237 mg/l	Mouse.	
106-97-8	butane			
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			
	oral	LD50 > 10000 - < 20000 mg/kg	Rat	Study report (1972)
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 9 of 13

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna	
	Fish toxicity	NOEC 0,182 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
	Crustacea toxicity	NOEC 0,317 mg/l	21 d	Daphnia magna	Company report (2010)
75-28-5	isobutane				
	Acute fish toxicity	LC50 91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
74-98-6	propane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
106-97-8	butane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts				
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 10 of 13

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	> 6,91

BCF

CAS No	Chemical name	BCF	Species	Source
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	144,3	calculated	Other company data (
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	70,8	Fish, not further specified.	Study report (2013)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 11 of 13

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS, flammable
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards


BIKELINE Multifunktionsöl 125ml D-GB

Print date: 24.01.2021

Product code: 1103006

Page 12 of 13

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional informationSafety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol directive (75/324/EEC)**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,6,7,9,14,15.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

**BIKELINE Multifunktionsöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103006

Page 13 of 13

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)