

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

BIKELINE Kettenöl 125ml D-GB

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricating agent

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+ 49 (0) 8171/1600 - 0	Telefax: + 49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

Supplier

Company name:	TUNAP UK Limited
Street:	Unit L4 Deacon Trading Estate, Morley Road
Place:	GB Tonbridge, Kent. TN9 1RA
Telephone:	+44 (0)1732 365163
e-mail:	sdb@tunap.com
Internet:	www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Precautionary statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 2 of 13

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container according to the official regulations.

Special labelling of certain mixtures

EUH208	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.
--------	---

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
106-97-8	butane	50 - <= 100 %
	203-448-7	601-004-00-0
	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280	
68037-01-4	Dec-1-ene, homopolymer, hydrogenated	20 - < 25 %
	500-183-1	01-2119486452-34
	Asp. Tox. 1; H304	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	0.1 - < 1 %
	271-529-4	01-2119492627-25
	Skin Sens. 1B; H317	
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	0.1 - < 1 %
	274-263-7	01-2119492616-28
	Skin Sens. 1B; H317	
61789-86-4	Sulfonic acids, petroleum, calcium salts	0.1 - < 1 %
	263-093-9	01-2119488992-18
	Skin Sens. 1B; H317	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 3 of 13

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 4 of 13

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 5 of 13

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts		
Worker DNEL, long-term	inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term	oral	systemic	0,833 mg/kg bw/day
61789-86-4	Sulfonic acids, petroleum, calcium salts		
Worker DNEL, long-term	inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term	oral	systemic	0,833 mg/kg bw/day

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
61789-86-4	Sulfonic acids, petroleum, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

- blood (B)
- Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

EN ISO 374

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 7 of 13

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	yellow-brown
Odour:	characteristic

	Test method
pH-Value (at 20 °C):	not determined DIN 19268

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-0,5 °C
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Flash point:	-15 °C
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	1,4
Upper explosion limits:	9,4
Ignition temperature:	>200 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.

Vapour pressure:	not determined
------------------	----------------

Density (at 20 °C):	0,853 g/cm ³ DIN 51757
---------------------	-----------------------------------

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

Solubility in other solvents

not determined

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 8 of 13

Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 9 of 13

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
106-97-8	butane			
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS
68037-01-4	Dec-1-ene, homopolymer, hydrogenated			
	oral	LD50 > 5000 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rabbit	
	inhalation (4 h) aerosol	LC50 > 5,2 mg/l	Rat	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts			
	oral	LD50 >5000 mg/kg	Rat	
	dermal	LD50 >5000 mg/kg	Rat	
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat	
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat	
61789-86-4	Sulfonic acids, petroleum, calcium salts			
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.



according to Regulation (EC) No 1907/2006

BIKELINE Kettenöl 125ml D-GB

Print date: 24.01.2021

Product code: 1103380

Page 10 of 13

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
106-97-8	butane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
68037-01-4	Dec-1-ene, homopolymer, hydrogenated				
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
	Acute fish toxicity	LC50 >10000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna	
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts				
	Acute fish toxicity	LC50 >10000 mg/l	96 h	Cyprinus carpio (Common Carp)	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	REACH Registration Dossier
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier
61789-86-4	Sulfonic acids, petroleum, calcium salts				
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	18,05
61789-86-4	Sulfonic acids, petroleum, calcium salts	> 4,46



BIKELINE Kettenöl 125ml D-GB

Print date: 24.01.2021

Product code: 1103380

Page 11 of 13

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 12 of 13

Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Marine pollutant: no
 Special Provisions: 63, 190, 277, 327, 344, 381,959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

National regulatory information

**BIKELINE Kettenöl 125ml D-GB**

Print date: 24.01.2021

Product code: 1103380

Page 13 of 13

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
EUH208	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts, Sulfonic acids, petroleum, calcium salts, Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)