



Safety Data Sheet

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1021 Underbody Protection Spray 500 ml AB

UFI: EK68-V093-A00S-49P3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: TUNAP GmbH & Co. KG
Street: Bürgermeister-Seidl-Str. 2
Place: D-82515 Wolfratshausen
Telephone: + 49 (0) 8171/1600 - 0 Telefax: + 49 (0) 8171/1600 - 40
E-mail: sdb@tunap.com
Internet: www.tunap.com

Supplier

Company name: TUNAP (UK) Limited
Street: Unit 12 Tonbridge Trade Park, Ingot Way
Place: GB Tonbridge, Kent. TN9 1GN
Telephone: +44 (0)1732 365163
E-mail: sdb@tunap.com
Internet: www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates
xylene
ethyl acetate

Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised

Signal word: Danger

Pictograms:





Safety Data Sheet

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 2 of 18

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 3 of 18

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
115-10-6	dimethyl ether			25 - < 50 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates			10 - < 20 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
1330-20-7	xylene			10 - < 20 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics			3 - < 5 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised			1 - < 3 %
	701-299-7		01-2119555292-40	
	Skin Sens. 1A, Aquatic Chronic 3; H317 H412			
100-41-4	ethylbenzene			1 - < 3 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
111-84-2	Nonane			0.1 - < 1 %
	203-913-4		01-2119463259-31	
	Flam. Liq. 3, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H226 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-48-9	919-857-5	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	10 - < 20 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
1330-20-7	215-535-7	xylene	10 - < 20 %
		inhalation: LC50 = 19,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 5000 mg/kg	
141-78-6	205-500-4	ethyl acetate	5 - < 10 %
		inhalation: LC50 = 29 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5600 mg/kg	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics	3 - < 5 %
		inhalation: LC50 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
71302-83-5	701-299-7	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised	1 - < 3 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 3 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
111-84-2	203-913-4	Nonane	0.1 - < 1 %
		inhalation: LC50 = 17 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet



Safety Data Sheet

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 5 of 18

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 6 of 18

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 7 of 18

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
115-10-6	dimethyl ether			
Worker DNEL, long-term		inhalation	systemic	1894 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	471 mg/m ³
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates			
Worker DNEL, long-term		inhalation	systemic	1500 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	900 mg/m ³
Consumer DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	300 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m ³
Worker DNEL, acute		inhalation	systemic	442 mg/m ³
Worker DNEL, long-term		inhalation	local	221 mg/m ³
Worker DNEL, acute		inhalation	local	442 mg/m ³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m ³
Consumer DNEL, acute		inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m ³
Consumer DNEL, acute		inhalation	local	260 mg/m ³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised			
Worker DNEL, long-term		inhalation	systemic	1,41 mg/m ³
Worker DNEL, long-term		dermal	systemic	3,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,348 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,42 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,2 mg/kg bw/day
111-84-2	Nonane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 8 of 18

PNEC values

CAS No	Substance	Value
Environmental compartment		
115-10-6	dimethyl ether	
Freshwater		0,155 mg/l
Freshwater (intermittent releases)		1,549 mg/l
Marine water		0,016 mg/l
Freshwater sediment		0,681 mg/kg
Marine sediment		0,069 mg/kg
Micro-organisms in sewage treatment plants (STP)		160 mg/l
Soil		0,045 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised	
Freshwater		0,0258 mg/l
Freshwater (intermittent releases)		0,258 mg/l
Marine water		0,00258 mg/l
Freshwater sediment		3137 mg/kg
Marine sediment		314 mg/kg
Secondary poisoning		8,89 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,2 mg/l
Soil		625 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.
EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 9 of 18

chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol
Colour: black
Odour: solvent like

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-24,8 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	0,6 vol. %
Flash point:	32 vol. %
Auto-ignition temperature:	-80 °C
Decomposition temperature:	> 200 °C
pH-Value (at 20 °C):	not determined
Water solubility:	not determined
Solubility in other solvents:	The study does not need to be conducted because the substance is known to be insoluble in water.
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,115 g/cm ³
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Oxidizing properties

Not oxidising.



Safety Data Sheet

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 10 of 18

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 11 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
1330-20-7	xylene				
	oral	LD50 5000 mg/kg	Rat	GESTIS	
	dermal	ATE 1100 mg/kg			
	inhalation (4 h) vapour	LC50 19,8 mg/l	Rat	GESTIS	
	inhalation dust/mist	ATE 1,5 mg/l			
141-78-6	ethyl acetate				
	oral	LD50 5600 mg/kg	Rat		
	dermal	LD50 20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 29 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat		
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2009)	OECD Guideline 402
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
111-84-2	Nonane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 17 mg/l	Rat	Toxicology and Applied Pharmacology 44:	OECD Guideline 403

Irritation and corrosivity

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 12 of 18

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna		
1330-20-7	xylene					
	Acute algae toxicity	ErC50 3,2 mg/l	72 h	Selenastrum capricornutum	Galassi et al. 1988	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 5540 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised					
	Acute fish toxicity	LL50 25,8 mg/l	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 54 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50 3,6 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA	
111-84-2	Nonane					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 ca. 2,4 mg/l	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 14 of 18

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates				
	OECD Guideline 301 F		80%	28	ECHA
	leicht biologisch abbaubar				
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics				
	OECD Guideline 301 F		89 %	28	ECHA

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	5
1330-20-7	xylene	3,15
141-78-6	ethyl acetate	-0,24
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised	3,67
100-41-4	ethylbenzene	3,15
111-84-2	Nonane	5,65

BCF

CAS No	Chemical name	BCF	Species	Source
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	144,3	calculated	Other company data (
71302-83-5	Naphtha (petroleum), steam-cracked, C8-10 aromatic hydrocarbon fraction, alkylated and oligomerised	ca. 0,074	Pimephales promelas	REACH Registration D
111-84-2	Nonane	198,7	Mytilus edulis	REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 15 of 18

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1
Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1
Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Marine pollutant: no
Special Provisions: 63, 190, 277, 327, 344, 381,959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 16 of 18

14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol Directive (75/324/EEC)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,9,11,15,16.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 17 of 18

Abbreviations and acronyms

Flam. Gas: Flammable gases
Aerosol: Aerosols
Liquefied gas
Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA: International Air Transport Association
IMDG: International Maritime Code for Dangerous Goods
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level
WEL (UK): Workplace Exposure Limits
TWA (EC): Time-Weighted Average
ATE: Acute Toxicity Estimate
STEL (EC) Short Term Exposure Limit
LC50: Lethal Concentration
EC50: half maximal Effective Concentration
ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

**Safety Data Sheet**

according to UK REACH Regulation

1021 Underbody Protection Spray 500 ml AB

Revision date: 18.11.2024

Product code: 1103662

Page 18 of 18

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)