

according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

138 Intake System Cleaner 400 ml AB

UFI: 7YY7-W04H-R00P-60T4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Acute Tox. 4; H332 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d

STOT SE 3; H335 H336 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Acetone

4-hydroxy-4-methylpentan-2-one, diacetone alcohol

xylene ethylbenzene

Signal word: Danger

Pictograms:







Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 2 of 15

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves and eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP R	egulation)	-	
67-64-1	Acetone			25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2,	STOT SE 3; H225 H319 H336 EUH	066	
123-42-2	4-hydroxy-4-methylpenta	n-2-one, diacetone alcohol		25 - < 50 %
	204-626-7		01-2119473975-21	
	Flam. Liq. 3, Repr. 2, Eye	Irrit. 2, STOT SE 3; H226 H361d I	H319 H335	
1330-20-7	xylene			20 - < 25 %
	215-535-7	601-022-00-9	01-2119488216-32	
		, Acute Tox. 4, Skin Irrit. 2, Eye Irri ; H226 H332 H312 H315 H319 H3	t. 2, STOT SE 3, STOT RE 2, Asp. 35 H373 H304 H412	
124-38-9	carbon dioxide			5 - < 10 %
	204-696-9			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4 H332 H315 H319 H335 F	, Skin Irrit. 2, Eye Irrit. 2, STOT SE 1373 H304	3, STOT RE 2, Asp. Tox. 1; H225	
108-88-3	toluene			0.1 - < 1 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Ski H373 H304			

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	Limits, M-factors and ATE	
67-64-1	200-662-2	Acetone	25 - < 50 %
	inhalation: L0	C50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	25 - < 50 %
	dermal: LD50) = 13630 mg/kg; oral: LD50 = 3002 mg/kg	
1330-20-7	215-535-7	xylene	20 - < 25 %
		C50 = 19,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE; oral: LD50 = 5000 mg/kg	
100-41-4	202-849-4	ethylbenzene	5 - < 10 %
		C50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: 0 mg/kg; oral: LD50 = 3500 mg/kg	
108-88-3	203-625-9	toluene	0.1 - < 1 %
	inhalation: L0	C50 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 4 of 15

area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 5 of 15

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol		Post shift



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 6 of 15

DNEL/DMEL values

	_ 14.400			
CAS No	Substance			
DNEL type		Exposure route	Effect	Value
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone	alcohol		
Worker DNE	L, long-term	inhalation	systemic	32,6 mg/m³
Worker DNE	L, acute	inhalation	local	240 mg/m³
Worker DNE	L, long-term	dermal	systemic	467 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	5,8 mg/m³
Consumer D	NEL, long-term	dermal	systemic	167 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,67 mg/kg bw/day
1330-20-7	xylene		•	
Worker DNE	L, long-term	inhalation	systemic	221 mg/m³
Worker DNE	L, acute	inhalation	systemic	442 mg/m³
Worker DNE	L, long-term	inhalation	local	221 mg/m³
Worker DNE	L, acute	inhalation	local	442 mg/m³
Worker DNE	L, long-term	dermal	systemic	212 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	65,3 mg/m³
Consumer D	NEL, acute	inhalation	systemic	260 mg/m³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, acute		inhalation	local	260 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	12,5 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental	Environmental compartment	
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	
Freshwater		2 mg/l
Freshwater (in	termittent releases)	1 mg/l
Marine water		0,2 mg/l
Freshwater se	diment	7,4 mg/kg
Marine sedime	nt	0,74 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,31 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (in	termittent releases)	0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment 12,46		12,46 mg/kg
Marine sediment 12,46 m		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP) 6,58 mg/l		
Soil		2,31 mg/kg



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 7 of 15

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

-78 °C

boiling range:

Flammability: not applicable

Lower explosion limits: 0,9 vol. %
Upper explosion limits: 14,3 vol. %
Flash point: -80 °C
Auto-ignition temperature: >200 °C
Decomposition temperature: not determined

Print date: 03.11.2024



Safety Data Sheet

according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 8 of 15

pH-Value (at 20 °C): not determined DIN 19268

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,85 g/cm³ DIN 51757

Relative vapour density: not determined

9.2. Other information

Water solubility:

Information with regard to physical hazard classes

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined Sublimation point: not determined Softening point: not determined Pour point: not determined not determined not determined

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 9 of 15

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if inhaled.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-64-1	Acetone							
	oral	LD50 mg/kg	5800	Rat	RTECS			
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat				
123-42-2	4-hydroxy-4-methylpenta	an-2-one, di	acetone alcol	nol				
	oral	LD50 mg/kg	3002	Rat	Study report (1978)	OECD Guideline 401		
	dermal	LD50 mg/kg	13630	Rabbit				
1330-20-7	xylene							
	oral	LD50 mg/kg	5000	Rat	GESTIS			
	dermal	ATE mg/kg	1100					
	inhalation (4 h) vapour	LC50	19,8 mg/l	Rat	GESTIS			
	inhalation dust/mist	ATE	1,5 mg/l					
100-41-4	ethylbenzene							
	oral	LD50 mg/kg	3500	Rat	GESTIS			
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS			
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat				
	inhalation dust/mist	ATE	1,5 mg/l					
108-88-3	toluene							
	dermal	LD50 mg/kg	12200	Rabbit	GESTIS			
	inhalation (4 h) vapour	LC50	49 mg/l	Rat	GESTIS			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (4-hydroxy-4-methylpentan-2-one, diacetone alcohol; toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

Print date: 03.11.2024



Safety Data Sheet

according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 10 of 15

STOT-single exposure

May cause respiratory irritation. (4-hydroxy-4-methylpentan-2-one, diacetone alcohol; xylene) May cause drowsiness or dizziness. (Acetone)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 11 of 15

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
67-64-1	Acetone								
	Acute fish toxicity	LC50 mg/l	5540	96 h	Oncorhynchus mykiss				
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna				
123-42-2	4-hydroxy-4-methylpentar	n-2-one, dia	cetone alcoh	ol					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oryzias latipes	REACh Registration Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1997)	OECD Guideline 202		
	Algae toxicity	NOEC mg/l	1000	3 d	Pseudokirchneriella subcapitata				
	Crustacea toxicity	NOEC	100 mg/l	14 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211		
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	activated sludge, domestic	Study report (2012)	OECD Guideline 209		
1330-20-7	xylene								
	Acute algae toxicity	ErC50	3,2 mg/l	72 h	Selenastrum capricornutum	Galassi et al. 1988			
100-41-4	ethylbenzene								
	Acute fish toxicity	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA			
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA			
108-88-3	toluene								
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID			
	Acute algae toxicity	ErC50 mg/l	12,5	72 h	Selenastrum capricornutum	Galassi et al. 1988			

12.2. Persistence and degradability

The product has not been tested.

The product has not been tested.				
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation		-	•
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetor	4-hydroxy-4-methylpentan-2-one, diacetone alcohol		
	OECD 301 A	98,51%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

The product has not been tested.



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	Acetone	-0,24
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	-0,09
1330-20-7	xylene	3,15
100-41-4	ethylbenzene	3,15
108-88-3	toluene	2,73

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 13 of 15

Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 48, Entry 75

Directive 2010/75/EU on industrial

No information available.

emissions:

Print date: 03.11.2024



Safety Data Sheet

according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 14 of 15

Directive 2004/42/EC on VOC in

No information available.

paints and varnishes:

Information according to Directive

P3b FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,11,13,15.

Abbreviations and acronyms

Aerosol: Aerosols

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate



according to UK REACH Regulation

138 Intake System Cleaner 400 ml AB

Revision date: 22.10.2024 Product code: 1103665 Page 15 of 15

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Aerosol 1; H222-H229	On basis of test data	
Acute Tox. 4; H332	Bridging principle "Aerosols"	
Asp. Tox. 1; H304	Calculation method	
Skin Irrit. 2; H315	Bridging principle "Aerosols"	
Eye Irrit. 2; H319	Bridging principle "Aerosols"	
Repr. 2; H361d	Calculation method	
STOT SE 3; H335	Bridging principle "Aerosols"	
STOT SE 3; H336	Bridging principle "Aerosols"	
STOT RE 2; H373	Bridging principle "Aerosols"	

Relevant H and EUH statements (number and full text)

Relevant H and EUH stat	ements (number and full text)
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)