



**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 2 of 17

**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 3 of 17

**Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-64-1	Acetone			25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol			25 - < 50 %
	204-626-7		01-2119473975-21	
	Flam. Liq. 3, Repr. 2, Eye Irrit. 2, STOT SE 3; H226 H361d H319 H335			
1330-20-7	xylene			20 - < 25 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
124-38-9	carbon dioxide			5 - < 10 %
	204-696-9			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H332 H315 H319 H335 H373 H304			
108-88-3	toluene			0.1 - < 1 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-64-1	200-662-2	Acetone	25 - < 50 %
	inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg		
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	25 - < 50 %
	dermal: LD50 = 13630 mg/kg; oral: LD50 = 3002 mg/kg		
1330-20-7	215-535-7	xylene	20 - < 25 %
	inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg		
100-41-4	202-849-4	ethylbenzene	5 - < 10 %
	inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg		
108-88-3	203-625-9	toluene	0.1 - < 1 %
	inhalation: LC50 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg; oral: LD50 = 5580 mg/kg		

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an



## Safety Data Sheet

according to UK REACH Regulation

### 138 Intake System Cleaner 400 ml AB

Revision date: 11.10.2023

Product code: 1103665

Page 4 of 17

unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

#### For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

### 6.3. Methods and material for containment and cleaning up



## Safety Data Sheet

according to UK REACH Regulation

### 138 Intake System Cleaner 400 ml AB

Revision date: 11.10.2023

Product code: 1103665

Page 5 of 17

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

##### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

##### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

##### Further information on handling

Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

##### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

##### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 6 of 17

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 7 of 17

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol			
Worker DNEL, long-term		inhalation	systemic	32,6 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	240 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	467 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,8 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	167 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,67 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	442 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	
Environmental compartment		
Freshwater		2 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,2 mg/l
Freshwater sediment		7,4 mg/kg
Marine sediment		0,74 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,31 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg



# Safety Data Sheet

according to UK REACH Regulation

## 138 Intake System Cleaner 400 ml AB

Revision date: 11.10.2023

Product code: 1103665

Page 8 of 17

### Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)  
Urine (U)

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

##### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.  
Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
Thickness of the glove material 0,45 mm  
EN ISO 374

##### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: A  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

##### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-78 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	0,9 vol. %
Flash point:	14,3 vol. %
Auto-ignition temperature:	-80 °C
	>200 °C



**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 9 of 17

Decomposition temperature:	not determined
pH-Value (at 20 °C):	not determined DIN 19268
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,85 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined

**9.2. Other information****Information with regard to physical hazard classes**

Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

**Other safety characteristics**

Evaporation rate:	not determined
Solid content:	not determined
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined

**Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**10.6. Hazardous decomposition products**Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information**

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 10 of 17

**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Harmful if inhaled.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) 4,527 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	Acetone				
	oral	LD50 5800 mg/kg	Rat		
	dermal	LD50 20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol				
	oral	LD50 3002 mg/kg	Rat	Study report (1978)	OECD Guideline 401
	dermal	LD50 13630 mg/kg	Rabbit		
1330-20-7	xylene				
	oral	LD50 3523 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6700 mg/l	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat		
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat	GESTIS	

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 11 of 17

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (4-hydroxy-4-methylpentan-2-one, diacetone alcohol; toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

May cause respiratory irritation. (4-hydroxy-4-methylpentan-2-one, diacetone alcohol; xylene)

May cause drowsiness or dizziness. (Acetone)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

**Specific effects in experiment on an animal**

No information available.

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

No information available.

**Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

The product is not: Ecotoxic.



## Safety Data Sheet

according to UK REACH Regulation

### 138 Intake System Cleaner 400 ml AB

Revision date: 11.10.2023

Product code: 1103665

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	Acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	5000	96 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oryzias latipes	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1997) OECD Guideline 202
	Algae toxicity	NOEC mg/l	1000	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC	100 mg/l	14 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	activated sludge, domestic	Study report (2012) OECD Guideline 209
1330-20-7	xylene					
	Acute fish toxicity	LC50	8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety. OECD Guideline 203
	Acute algae toxicity	ErC50	4,9 mg/l	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety. OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l	> 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l	1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 other: US EPA 600/4-91-003
	Acute bacteria toxicity	EC50 mg/l ( )	> 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 ( ) OECD Guideline 209
100-41-4	ethylbenzene					
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Pseudokirchneriella subcapitata	GESTIS
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 13 of 17

	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	GESTIS	
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna		

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol				
	OECD 301 A		98,51%	28	
	Easily biodegradable (concerning to the criteria of the OECD)				

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	Acetone	-0,24
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	-0,09
1330-20-7	xylene	3,2
100-41-4	ethylbenzene	3,15
108-88-3	toluene	2,73

**BCF**

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 14 of 17

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 15 of 17

Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P3b FLAMMABLE AEROSOLS

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol Directive (75/324/)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 9,11,13,16.

**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 16 of 17

**Abbreviations and acronyms**

Aerosol: Aerosols

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Acute Tox. 4; H332	Bridging principle "Aerosols"
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"

**Relevant H and EUH statements (number and full text)**

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.



**Safety Data Sheet**

according to UK REACH Regulation

**138 Intake System Cleaner 400 ml AB**

Revision date: 11.10.2023

Product code: 1103665

Page 17 of 17

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*