

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

354 Electric 250 ml AB

UFI: XN25-F00W-J001-AVS8

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: TUNAP GmbH & Co. KG  
Street: Bürgermeister-Seidl-Str. 2  
Place: D-82515 Wolfratshausen  
Telephone: + 49 (0) 8171/1600 - 0      Telefax: + 49 (0) 8171/1600 - 40  
E-mail: sdb@tunap.com  
Internet: www.tunap.com

**Supplier**

Company name: TUNAP (UK) Limited  
Street: Unit 12 Tonbridge Trade Park, Ingot Way  
Place: GB Tonbridge, Kent. TN9 1GN  
Telephone: +44 (0)1732 365163  
E-mail: sdb@tunap.com  
Internet: www.tunap.co.uk

**1.4. Emergency telephone number:** 111 NHS (National Health Service)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
Skin Sens. 1; H317  
STOT RE 1; H372  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)  
Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic  
Dihydro-3-(tetrapropenyl)furan-2,5-dione

**Signal word:** Danger

**Pictograms:****Hazard statements**

H222      Extremely flammable aerosol.  
H229      Pressurised container: May burst if heated.  
H317      May cause an allergic skin reaction.



# Safety Data Sheet

according to UK REACH Regulation

## 354 Electric 250 ml AB

Revision date: 11.01.2023

Product code: 1103674

Page 2 of 13

H372 Causes damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P211 Do not spray on an open flame or other ignition source.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe Aerosol.  
P280 Wear protective gloves.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-82-1	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)	25 - < 50 %		
	919-164-8		01-2119473977-17	
	STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H372 H304 H412 EUH066			
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic	25 - < 50 %		
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			
75-28-5	isobutane	25 - < 50 %		
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane	3 - < 5 %		
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane	1 - < 3 %		
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	0.1 - < 1 %		
	247-781-6			
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 4; H319 H317 H413			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 3 of 13

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-82-1	919-164-8	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)	25 - < 50 %
		inhalation: LC50 = > 13,1 mg/l (vapours); inhalation: LC50 = 13,1 mg/l (dusts or mists); dermal: LD50 = >3400 mg/kg; oral: LD50 = > 15000 mg/kg	
64742-53-6	265-156-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic	25 - < 50 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
26544-38-7	247-781-6	Dihydro-3-(tetrapropenyl)furan-2,5-dione	0.1 - < 1 %
		inhalation: LC50 = 1220 mg/l (vapours); inhalation: LC50 = 5,3 mg/l (dusts or mists); dermal: LD50 = 6250-7500 mg/kg; oral: LD50 = 2900 mg/kg	

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Danger of bursting container.

**SECTION 6: Accidental release measures**



## Safety Data Sheet

according to UK REACH Regulation

### 354 Electric 250 ml AB

Revision date: 11.01.2023

Product code: 1103674

Page 4 of 13

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

##### **For non-emergency personnel**

First aider: Pay attention to self-protection!

##### **For emergency responders**

Fight fire with normal precautions from a reasonable distance.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

##### **Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

##### **Further information on handling**

Avoid contact with skin and eyes.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

##### **Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

##### **Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 5 of 13

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic	
Secondary poisoning		9,33 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)  
Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min



## Safety Data Sheet

according to UK REACH Regulation

### 354 Electric 250 ml AB

Revision date: 11.01.2023

Product code: 1103674

Page 6 of 13

Thickness of the glove material 0,45 mm  
EN ISO 374

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: AX  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

#### Environmental exposure controls

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid		
Colour:	light yellow		
			<b>Test method</b>
Melting point/freezing point:		not determined	
Boiling point or initial boiling point and boiling range:		40- °C	
Flammability:		not applicable	
		not applicable	
Lower explosion limits:		0,6	
Upper explosion limits:		15	
Flash point:		-80 °C	
Auto-ignition temperature:		>200 °C	
Decomposition temperature:		not determined	
pH-Value (at 20 °C):		not determined	DIN 19268
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.		
Solubility in other solvents			
not determined			
Partition coefficient n-octanol/water:		not determined	
Vapour pressure:		not determined	
Density (at 20 °C):		0,855 g/cm <sup>3</sup>	DIN 51757
Relative vapour density:		not determined	

### 9.2. Other information

#### Information with regard to physical hazard classes

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

#### Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Sublimation point:

not applicable

Softening point:

not applicable

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 7 of 13

Pour point:

not applicable

**Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**10.6. Hazardous decomposition products**Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-82-1	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)				
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 >3400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 13,1 mg/l	Rat	Study report (1977)	OECD Guideline 403
	inhalation (4 h) dust/mist	LC50 13,1 mg/l	Rat		
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione				
	oral	LD50 2900 mg/kg	Rat		
	dermal	LD50 6250-7500 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 1220 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 5,3 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

May cause an allergic skin reaction. (Dihydro-3-(tetrapropenyl)furan-2,5-dione)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %))

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

**Specific effects in experiment on an animal**

No information available.

**11.2. Information on other hazards**

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 9 of 13

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

No information available.

**Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-82-1	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)					
	Acute algae toxicity	ErC50 4,1 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l 10 - 22	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC mg/l 0,13	28 d	Oncorhynchus mykiss	REACH Registration Dossier	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l 0,28	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic					
	Acute fish toxicity	LL50 mg/l > 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC mg/l >= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione					
	Acute fish toxicity	LC50 mg/l > 100	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 110 mg/l	96 h	Selenastrum capricornutum		

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-82-1	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)			
	OECD Guideline 301 F	77,05%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

**12.3. Bioaccumulative potential**

The product has not been tested.

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 10 of 13

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64742-82-1	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, aromates (2-25 %)	4,2
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	>=4,39

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.  
The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 11 of 13

Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial emissions: No information available.

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 12 of 13

Directive 2004/42/EC on VOC in  
paints and varnishes: No information available.

Information according to Directive  
2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)  
Aerosol Directive (75/324/EEC)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile  
work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,6,7,8,9,10,11,13,14,15,16.

**Abbreviations and acronyms**

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Asp. Tox: Aspiration hazard

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement  
concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer  
(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT RE 1; H372	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

**Safety Data Sheet**

according to UK REACH Regulation

**354 Electric 250 ml AB**

Revision date: 11.01.2023

Product code: 1103674

Page 13 of 13

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*