

**Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB**

Print date: 24.01.2021

Product code: 1103840

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

No information available.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+ 49 (0) 8171/1600 - 0	Telefax: + 49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

Supplier

Company name:	TUNAP UK Limited
Street:	Unit L4 Deacon Trading Estate, Morley Road
Place:	GB Tonbridge, Kent. TN9 1RA
Telephone:	+44 (0)1732 365163
e-mail:	sdb@tunap.com
Internet:	www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.


Textil-/Material-/Schuh- u. Heimdeco 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 2 of 12

P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
 The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
64-17-5	ethanol			25 - < 50 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
68424-85-1	Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides			< 0.1 %
	270-325-2			
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB**

Print date: 24.01.2021

Product code: 1103840

Page 3 of 12

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.**Unsuitable extinguishing media**

Full water jet

5.2. Special hazards arising from the substance or mixtureIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.


Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 4 of 12

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls
Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.


Textil-/Material-/Schuh- u. Heimdeco 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 5 of 12

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 When exceeding the relevant workplace exposure limits, note the following:
 Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
 Filtering device with filter or ventilator filtering device of type: AX
 Observe the wear time limits as specified by the manufacturer.
 Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colorless, clear
Odour:	perfume-like

pH-Value (at 20 °C):

Test method

DIN 19268

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-11,7 °C
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Flash point:	-80 °C
Sustaining combustion:	No data available

Flammability

Solid:	No information available.
Gas:	No information available.

Lower explosion limits: 3,5

Upper explosion limits: 15

Ignition temperature: >200 °C

Auto-ignition temperature

Solid:	No information available.
Gas:	No information available.

Decomposition temperature: No information available.

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,73 g/cm³ DIN 51757

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined


Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 6 of 12

9.2. Other information

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity
10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products
Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.
Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information
11.1. Information on toxicological effects
Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
75-28-5	isobutane			
	inhalation vapour	LC50 1237 mg/l	Mouse.	
64-17-5	ethanol			
	oral	LD50 6200 mg/kg	Rat	IUCLID
	dermal	LD50 >20000 mg/kg	Rat	
	inhalation (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS
106-97-8	butane			
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS
68424-85-1	Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides			
	oral	LD50 344 mg/kg	Rat	
	dermal	LD50 3340 mg/kg	Rabbit	

**Textil-/Material-/Schuh- u. Heimdeco 300ml D-GB**

Print date: 24.01.2021

Product code: 1103840

Page 7 of 12

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.


Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 8 of 12

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
75-28-5	isobutane				
	Acute fish toxicity	LC50 91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
64-17-5	ethanol				
	Acute fish toxicity	LC50 14200 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute crustacea toxicity	EC50 mg/l 9268 - 14221	48 h	Daphnia magna	IUCLID
74-98-6	propane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
106-97-8	butane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
68424-85-1	Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides				
	Acute fish toxicity	LC50 0,28 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 0,049 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 0,016 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.



Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 9 of 12

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
64-17-5	ethanol	-0,31
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number:	UN 1950
-------------------------	---------


Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 10 of 12

14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1
 Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Marine pollutant: no
 Special Provisions: 63, 190, 277, 327, 344, 381,959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.


Textil-/Material-/Schuh- u. Heimdeo 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 11 of 12

Information according to 2012/18/EU
(SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol directive (75/324/EEC)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 7,9,10,13,14,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Textil-/Material-/Schuh- u. Heimdeco 300ml D-GB

Print date: 24.01.2021

Product code: 1103840

Page 12 of 12

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)