



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

114S Bremsenfrühling

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

SECTION 2: Hazards identification

2.2. Label elements

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 2 of 15

Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regu	ılation)	•	
64742-49-0	Hydrocarbons, C6-C7, n-alka	anes, isoalkanes, cyclics, < 5% n	-hexane	25 - < 50 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, ST0 H411	OT SE 3, Asp. Tox. 1, Aquatic Cl	nronic 2; H225 H315 H336 H304	
115-10-6	dimethyl ether			20 - < 25 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas;	H220 H280	•	
141-78-6	ethyl acetate			3 - < 5 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STC	OT SE 3; H225 H319 H336 EUH	066	
64-17-5	ethanol			1 - < 3 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H22			
7440-66-6	zinc powder - zinc dust (stab	ilized)		1 - < 3 %
	231-175-3	030-001-01-9	01-2119485044-40	
	Aquatic Acute 1, Aquatic Chi			
67-64-1	Acetone			1 - < 3 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STC			
124-38-9	carbon dioxide			1 - < 3 %
	204-696-9			
			•	
7779-90-0	trizinc bis(orthophosphate)			1 - < 3 %
	231-944-3	030-011-00-6		
	Aquatic Acute 1, Aquatic Chi	onic 1; H400 H410	•	
1330-20-7	xylene	0.1 - < 1 %		
	215-535-7	601-022-00-9	01-2119488216-32	
		cute Tox. 4, Skin Irrit. 2, Eye Irrit 226 H332 H312 H315 H319 H33	. 2, STOT SE 3, STOT RE 2, Asp. 5 H373 H304 H412	
13463-67-7	titanium dioxide			0.1 - < 1 %
	236-675-5	022-006-00-2		
	Carc. 2; H351			

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	25 - < 50 %
	inhalation: LC5 5000 mg/kg	0 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >	
141-78-6	205-500-4	ethyl acetate	3 - < 5 %
	inhalation: LC5 mg/kg	0 = 1600 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620	
64-17-5	200-578-6	ethanol	1 - < 3 %
	inhalation: LC5	0 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg	
67-64-1	200-662-2	Acetone	1 - < 3 %
	inhalation: LC5	0 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
1330-20-7	215-535-7	xylene	0.1 - < 1 %
		0 = 19,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE oral: LD50 = 5000 mg/kg	
13463-67-7	236-675-5	titanium dioxide	0.1 - < 1 %
	inhalation: LC5 10000 mg/kg	0 = > 6,8 mg/l (dusts or mists); dermal: LD50 = > 10000 mg/kg; oral: LD50 = >	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high





according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 4 of 15

concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.





according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 5 of 15

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	I	Post shift



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <	5% n-hexane		
Worker DNEL	long-term	inhalation	systemic	2035 mg/m³
Worker DNEL	, long-term	dermal	systemic	773 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	608 mg/m³
Consumer DN	EL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day
115-10-6	dimethyl ether			
Worker DNEL	, long-term	inhalation	systemic	1894 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	471 mg/m³
7779-90-0	trizinc bis(orthophosphate)			
Worker DNEL	, long-term	dermal	systemic	83 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	2,5 mg/m³
Consumer DN	EL, long-term	dermal	systemic	83 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,83 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	5 mg/m³
1330-20-7	xylene			
Worker DNEL	, long-term	inhalation	systemic	221 mg/m³
Worker DNEL	, acute	inhalation	systemic	442 mg/m³
Worker DNEL	, long-term	inhalation	local	221 mg/m³
Worker DNEL	, acute	inhalation	local	442 mg/m³
Worker DNEL	, long-term	dermal	systemic	212 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	65,3 mg/m³
Consumer DN	EL, acute	inhalation	systemic	260 mg/m³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, acute		inhalation	local	260 mg/m³
Consumer DN	EL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	12,5 mg/kg bw/day



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 7 of 15

PNEC values

· ···	•	
CAS No	Substance	
Environmental	compartment	Value
115-10-6	dimethyl ether	
Freshwater		0,155 mg/l
Freshwater (in	termittent releases)	1,549 mg/l
Marine water		0,016 mg/l
Freshwater se	diment	0,681 mg/kg
Marine sedime	ent	0,069 mg/kg
Micro-organisn	ns in sewage treatment plants (STP)	160 mg/l
Soil		0,045 mg/kg
7779-90-0	trizinc bis(orthophosphate)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater se	diment	117,8 mg/kg
Marine sedime	ent	56,5 mg/kg
Micro-organisr	ns in sewage treatment plants (STP)	0,1 mg/l
Soil		35,6 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (in	termittent releases)	0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment 12		
Micro-organisr	ns in sewage treatment plants (STP)	6,58 mg/l
Soil		2,31 mg/kg

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.





according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 8 of 15

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type:

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol

Colour:

 Test method

 pH-Value (at 20 °C):
 DIN 19268

 Density (at 20 °C):
 DIN 51757

9.2. Other information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 9 of 15

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane							
	oral	LD50 mg/kg	> 5000	Rat				
	dermal	LD50 3100 mg/kg	> 2800 -	Rat				
	inhalation (4 h) vapour	LC50 mg/l	> 25,2	Rat				
141-78-6	ethyl acetate							
	oral	LD50 mg/kg	5620	Rat				
	dermal	LD50 mg/kg	>20000	Rabbit				
	inhalation (4 h) vapour	LC50	1600 mg/l	Rat				
64-17-5	ethanol							
	oral	LD50 mg/kg	6200	Rat	IUCLID			
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS			
67-64-1	Acetone							
	oral	LD50 mg/kg	5800	Rat	RTECS			
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat				
1330-20-7	xylene							
	oral	LD50 mg/kg	5000	Rat	GESTIS			
	dermal	ATE mg/kg	1100					
	inhalation (4 h) vapour	LC50	19,8 mg/l	Rat	GESTIS			
	inhalation dust/mist	ATE	1,5 mg/l					
13463-67-7	titanium dioxide							
	oral	LD50 mg/kg	> 10000	Rat				
	dermal	LD50 mg/kg	> 10000	Rabbit				
	inhalation (4 h) dust/mist	LC50 mg/l	> 6,8	Rat				

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.





according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 10 of 15

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information

12.1. **Toxicity**

There are no data available on the mixture itself.



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 11 of 15

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane								
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
141-78-6	ethyl acetate								
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)				
	Acute crustacea toxicity	EC50	165 mg/l	48 h	Daphnia magna				
64-17-5	ethanol								
	Acute crustacea toxicity	EC50 14221 mg/l	9268 -	48 h	Daphnia magna	IUCLID			
67-64-1	Acetone								
	Acute fish toxicity	LC50 mg/l	5540	96 h	Oncorhynchus mykiss				
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna				
1330-20-7	xylene								
	Acute algae toxicity	ErC50	3,2 mg/l	72 h	Selenastrum capricornutum	Galassi et al. 1988			
13463-67-7	titanium dioxide								
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50	61 mg/l	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	> 10	48 h	Daphnia pulex				
	Fish toxicity	NOEC mg/l	> 1000	2 d	Leuciscus idus (golden orfe)				
	Algae toxicity	NOEC	1 mg/l	3 d	Pseudokirchneriella subcapitata				
	Crustacea toxicity	NOEC	> 3 mg/l	30 d	Daphnia magna				

12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 12 of 15

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	OECD Guideline 301 F 98% 28 ECHA					
	Easily biodegradable (concerning to the criteria of the OECD)					
141-78-6	ethyl acetate					
	OECD Prüfrichtlinie 301D	79 %	20			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
115-10-6	dimethyl ether	0,1
141-78-6	ethyl acetate	-0,24
64-17-5	ethanol	-0,31
67-64-1	Acetone	-0,24
1330-20-7	xylene	3,15

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)



according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 13 of 15

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity:1 LExcepted quantity:E0Transport category:2Tunnel restriction code:D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%

n-hexane)

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:yes

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

SECTION 15: Regulatory information





according to UK REACH Regulation

114S Bremsenfrühling

Revision date: 24.02.2021 Product code: 1106049 Page 14 of 15

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial No information available.

emissions:

Directive 2004/42/EC on VOC in No information available.

paints and varnishes:

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Flam. Gas: Flammable gases

Liquefied gas

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.



according to UK REACH Regulation

	114S Bremsenfrühling	
Revision date: 24.02.2021	Product code: 1106049	Page 15 of 15
H226	Flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	

Further Information

H411

H412

EUH066

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

Repeated exposure may cause skin dryness or cracking.

Toxic to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)