



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

965 System-Wirkstoff Hybrid 200ml ALL

UFI: 7KC4-C0MV-T00V-A50P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Additive

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen
Telephone: +49 (0) 8171/1600-0
E-mail: sdb@tunap.com
Internet: www.tunap.com

Telefax: +49 (0) 8171/1600-40

1.4. Emergency telephone number:

111 NHS (National Health Service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Repr. 2; H361f
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

2-Propanol
Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 2 of 18

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container according to the official regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 3 of 18

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	2-Propanol			50 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates			20 - < 25 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane			10 - < 20 %
	216-653-1	603-181-00-X		
	Flam. Liq. 2, Skin Irrit. 2; H225 H315			
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene			3 - < 5 %
	270-128-1		01-2119491299-23	
	Repr. 2, Aquatic Chronic 3; H361f H412			
337367-30-3	1-Propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia)			1 - < 3 %
	Skin Irrit. 2, Aquatic Chronic 3; H315 H412			
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol			1 - < 3 %
	202-414-9		01-2119777867-13	
	Acute Tox. 4, Skin Corr. 1C, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H373 H400 H410			
128-37-0	2,6-di-tert-butyl-p-cresol			1 - < 3 %
	204-881-4		01-2119555270-46	
	Aquatic Chronic 1; H410			
67-56-1	methanol			0.1 - < 1 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	2-Propanol	50 - < 100 %
		inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5280 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	20 - < 25 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
1634-04-4	216-653-1	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	10 - < 20 %
		inhalation: LC50 = 85 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3866 mg/kg	
68411-46-1	270-128-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	3 - < 5 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	1 - < 3 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = ca. 1085 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	
67-56-1	200-659-6	methanol	0.1 - < 1 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 17100 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 5 of 18

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 6 of 18

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
1634-04-4	Methyl-tert-butyl ether	50	183.5		TWA (8 h)	WEL
		100	367		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 7 of 18

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates			
Worker DNEL, long-term		inhalation	systemic	1500 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	900 mg/m ³
Consumer DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	300 mg/kg bw/day
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene			
Worker DNEL, long-term		inhalation	systemic	0,6 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,08 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,14 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,04 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol			
Worker DNEL, long-term		inhalation	systemic	0,46 mg/m ³
Worker DNEL, acute		inhalation	systemic	14 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,06 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	2 mg/kg bw/day
67-56-1	methanol			
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 8 of 18

PNEC values

CAS No	Substance	Value
Environmental compartment		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Freshwater		0,034 mg/l
Freshwater (intermittent releases)		0,51 mg/l
Marine water		0,003 mg/l
Freshwater sediment		0,446 mg/kg
Marine sediment		0,045 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1,76 mg/kg
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	
Freshwater		0 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0 mg/l
Freshwater sediment		0,376 mg/kg
Marine sediment		0,038 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,27 mg/l
Soil		0,075 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

- blood (B)
- Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.
EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 9 of 18

must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: a

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:		
Odour:	solvent like	
		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	55 °C	
Flammability:	not applicable	
	not applicable	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	13 vol. %	
Flash point:	-28 °C	ISO 3679
Auto-ignition temperature:	<200 °C	
Decomposition temperature:	not determined	
pH-Value (at 20 °C):		DIN 19268
Viscosity / kinematic: (at 40 °C)	< 20,5 mm ² /s	DIN EN ISO 3104
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,788 g/cm ³	DIN 51757
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 10 of 18

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Sublimation point:	not applicable
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic:	DIN 53019-1
Flow time: (at 20 °C)	DIN EN ISO 2431

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 47133 mg/kg; ATE (dermal) 250000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 416,7 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 11 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	2-Propanol				
	oral	LD50 5280 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat		
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane				
	oral	LD50 3866 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 85 mg/l	Rat		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
	oral	LD50 ca. 1085 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 >2000 mg/kg	Rabbit		
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	LD50 17100 mg/kg	Kaninchen		
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 12 of 18

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility. (Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (2-Propanol; Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	2-Propanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna		
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane					
	Acute fish toxicity	LC50 672 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 > 800 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 651 mg/l	48 h	Daphnia magna		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Danio rerio	Study report (1988)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EC50 51 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol					
	Acute fish toxicity	LC50 0,3 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 0,03 mg/l	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,163 mg/l	48 h	Daphnia magna	Study report (2010)	OECD Guideline 202
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 14 of 18

	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
--	--------------------	------	----------	------	---------------	---------------------------------------	--

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	2-Propanol	0,05
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	5
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	0,94
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	> 6
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	8,4
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
64742-48-9	Hydrocarbons, C9 - C11, n-alkanes, iso-alkanes, cyclics, < 2 % aromates	144,3	calculated	Other company data (
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	411	Cyprinus carpio	Study report (2000)
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	371,8		EPIWIN calculation (
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 15 of 18

List of Wastes Code - used product

070710 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other filter cakes and spent absorbents; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL); tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640C
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL); tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640C
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL); tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine pollutant:	no
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 16 of 18

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL); ; tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,11.



Safety Data Sheet

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 17 of 18

Abbreviations and acronyms

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Safety Data Sheet**

according to UK REACH Regulation

965 System-Wirkstoff Hybrid 200ml ALL

Revision date: 08.05.2023

Product code: 1106757

Page 18 of 18

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361f	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)