

according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Product code: 1107095 Revision date: 10.03.2023 Page 1 of 18

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

100 Multifunktionsöl 150ml DUM

4J85-C0N9-P006-YEYQ

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant

### 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Skin Sens. 1: H317 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## **GB CLP Regulation**

## Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Polysulfides, di-tert-dodecyl

Signal word: Danger

Pictograms:





## **Hazard statements**

Extremely flammable aerosol. H222

Pressurised container: May burst if heated. H229

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 2 of 18

## **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 3 of 18

## Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation	)	<u> </u>	
75-28-5	isobutane			50 - < 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220	H280	·	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes,	soalkanes, cyclics, < 5%	n-hexane	5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	3, Asp. Tox. 1, Aquatic C	hronic 2; H225 H315 H336 H304	
	Hydrocarbons, C9-C10, n-alkanes	isoalkanes, cyclenes, <2	% aromatics	5 - < 10 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	1, Aquatic Chronic 3; H2	26 H336 H304 H412 EUH066	
64742-49-0	Hydrocarbons, C7, n-alkanes, isoa	lkanes, cyclics		5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	3, Asp. Tox. 1, Aquatic C	hronic 2; H225 H315 H336 H304	
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220	H280		
106-97-8	butane	1 - < 3 %		
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220	H280		
1474044-79-5	Calcium bis(di C8-C10, branched,	0.1 - < 1 %		
	939-717-7		01-2119980985-16	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
68425-15-0	Polysulfides, di-tert-dodecyl			0.1 - < 1 %
	270-335-7		01-2119540516-41	
	Skin Sens. 1B; H317			
68602-85-7	Hydrocarbon waxes (petroleum), c	xidized, Me esters		0.1 - < 1 %
	271-626-1		01-2120749916-39	
	Eye Irrit. 2; H319			
68784-12-3	2,5-Furandione, dihydro-, mono-C	0.1 - < 1 %		
	272-221-2		01-2119533117-46	
	Skin Sens. 1B; H317			
	Molybdenum trioxide, reaction prod	0.1 - < 1 %		
	947-946-9		01-2120772600-59	
	Skin Irrit. 2, Skin Sens. 1B, Aquation	Chronic 4; H315 H317 H	413	

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

#### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. I	Limits, M-factors and ATE				
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	5 - < 10 %			
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg					
	927-241-2 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics					
	inhalation: LC5 mg/kg	0 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000				
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	5 - < 10 %			
	inhalation: LC5 5500 mg/kg	0 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 =				
1474044-79-5	939-717-7	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	0.1 - < 1 %			
	inhalation: LC5	0 = > 18 mg/l (vapours)				
68425-15-0	270-335-7	Polysulfides, di-tert-dodecyl	0.1 - < 1 %			
	inhalation: LC5	0 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg				
68602-85-7	271-626-1	Hydrocarbon waxes (petroleum), oxidized, Me esters	0.1 - < 1 %			
	oral: LD50 = >	2000 mg/kg				
68784-12-3	272-221-2	2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.	0.1 - < 1 %			
	dermal: LD50 =	= > 2000 mg/kg; oral: LD50 = > 2000 mg/kg				

### Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

## After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.





according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 5 of 18

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

## 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

### For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

## 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.





according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 6 of 18

## Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

### Further information on handling

Avoid contact with skin and eyes.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

## Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

## 7.3. Specific end use(s)

Lubricant

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 7 of 18

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%	n-hexane		
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	608 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Worker DNEL,	long-term	inhalation	systemic	2085 mg/m³
Worker DNEL,	long-term	dermal	systemic	300 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	447 mg/m³
Consumer DN	EL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	149 mg/kg bw/day
1474044-79- 5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalen	esulphonate)		
Worker DNEL,	long-term	inhalation	systemic	70 mg/m³
Worker DNEL,	long-term	dermal	systemic	10 mg/kg bw/day
68602-85-7	Hydrocarbon waxes (petroleum), oxidized, Me esters			
Worker DNEL,	long-term	inhalation	systemic	1000 mg/m³
Worker DNEL,	long-term	dermal	systemic	1000 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	1000 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	1000 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	1000 mg/kg bw/day
68784-12-3	2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.			
Worker DNEL,	long-term	dermal	systemic	1 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,5 mg/kg bw/day
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-	ethylhexyl)] hydrogen d	ithiophosphate	
Worker DNEL,	long-term	inhalation	systemic	4,93 mg/m³
Worker DNEL,	long-term	dermal	systemic	1,4 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	0,87 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	0,5 mg/kg bw/day



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 8 of 18

### **PNEC values**

CAS No	Substance		
Environmenta	I compartment	Value	
1474044-79- 5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)		
Freshwater		0,004 mg/l	
Freshwater (ir	ntermittent releases)	0,0027 mg/l	
Marine water		0,0004 mg/l	
Freshwater se	ediment	69 mg/kg	
Marine sedime	ent	6,9 mg/kg	
Secondary po	isoning	22,2 mg/kg	
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l	
Soil		13,9 mg/kg	
68602-85-7	Hydrocarbon waxes (petroleum), oxidized, Me esters		
Freshwater		100 mg/l	
Marine water		10 mg/l	
Freshwater se	ediment	100 mg/kg	
Marine sedime	ent	10 mg/kg	
Secondary po	isoning	100 mg/kg	
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l	
Soil		100 mg/kg	
68784-12-3	2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.		
Freshwater		0,01 mg/l	
Freshwater (in	ntermittent releases)	0,1 mg/l	
Marine water 0,00			
Micro-organis	ms in sewage treatment plants (STP)	8 mg/l	
Soil		19,2 mg/kg	

## Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

## 8.2. Exposure controls

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous



according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 9 of 18

substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

### **Environmental exposure controls**

Observe legal regulations and provisions.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol

Colour: greenish-brown, milky

Odour: characteristic

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

-42 °C

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 9,4 vol. %
Flash point: -80 °C
Decomposition temperature: not determined

pH-Value (at 20 °C): DIN 19268

Viscosity / kinematic: < 20,5 mm²/s

(at 40 °C)

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,77 g/cm³ DIN 51757

Relative vapour density: not determined

## 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

Heating may cause an explosion.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

The product is not: oxidising.





according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 10 of 18

### Other safety characteristics

Evaporation rate: not determined Solid content: not determined

#### **Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

## 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

## **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

## **Acute toxicity**

Based on available data, the classification criteria are not met.

### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 11 of 18

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane							
	oral	LD50 > mg/kg	> 5000	Rat				
	dermal	LD50 > 3100 mg/kg	2800 -	Rat				
	inhalation (4 h) vapour	LC50 >	25,2	Rat				
	Hydrocarbons, C9-C10, r	ı-alkanes, isoal	lkanes, cy	clenes, <2% aromatics				
	oral	LD50 > mg/kg	5000	Rat				
	dermal	LD50 > mg/kg	> 5000	Rabbit				
	inhalation (4 h) vapour	LC50 >	<b>4</b> 951	Rat				
64742-49-0	Hydrocarbons, C7, n-alka	nes, isoalkane	es, cyclics					
	oral	LD50 5 mg/kg	5500	Rat				
	dermal	LD50 > 3100 mg/kg	> 2800 -	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de		
	inhalation (4 h) vapour	LC50 >	23,3	Rat	Study report (1988)	OECD Guideline 403		
1474044-79- 5	Calcium bis(di C8-C10, b	ranched, C9 rid	ch, alkylna	phthalenesulphonate)				
	inhalation (1 h) vapour	LC50 >	→ 18 mg/l	Rat	Study report (1978)	other: FHSLA, CFR, Title 21 J para. 191.		
68425-15-0	Polysulfides, di-tert-dode	cyl						
	oral	LD50 > mg/kg	2000	Rat				
	dermal	LD50 > mg/kg	2000	Rabbit				
	inhalation (4 h) vapour	LC50 >	20 mg/l	Rat				
68602-85-7	Hydrocarbon waxes (petr	oleum), oxidize	ed, Me est	ers				
	oral	LD50 > mg/kg	2000	Rat	Study report (2017)	OECD Guideline 420		
68784-12-3	2,5-Furandione, dihydro-	mono-C15-20	-alkenyl de	erivs.				
	oral	LD50 > mg/kg	2000	Rat	Study report (2009)	OECD Guideline 423		
	dermal	LD50 > mg/kg	2000	Rat	Study report (2009)	OECD Guideline 402		

## Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

May cause an allergic skin reaction. (Polysulfides, di-tert-dodecyl; 2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.; Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate)

## Carcinogenic/mutagenic/toxic effects for reproduction





according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 12 of 18

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

## Specific effects in experiment on an animal

No information available.

### 11.2. Information on other hazards

### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Other information

No information available.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 13 of 18

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
64742-49-0	Hydrocarbons, C6-C7, n-a	alkanes, isc	alkanes, cycl	ics, < 5%	n-hexane				
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
	Hydrocarbons, C9-C10, n	-alkanes, is	oalkanes, cy	clenes, <	2% aromatics				
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna				
64742-49-0	Hydrocarbons, C7, n-alka	nes, isoalka	anes, cyclics						
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203		
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	>1 - 10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	1,534	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
1474044-79- 5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)								
-	Acute algae toxicity	ErC50 mg/l	> 1,2	72 h	Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	>= 0,18	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202		
	Crustacea toxicity	NOEC	4,6 mg/l	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211		
8425-15-0	Polysulfides, di-tert-doded	cyl							
	Acute fish toxicity	LC50 mg/l	>100	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Selenastrum capricornutum				
	Acute crustacea toxicity	EC50 mg/l	>100		Daphnia magna (Big water flea)				



according to UK REACH Regulation

## 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 14 of 18

68602-85-7	Hydrocarbon waxes (petro	oleum), oxid	dized, Me este	ers			
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Oncorhynchus mykiss	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2017)	OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ( )	> 100	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209
68784-12-3	2,5-Furandione, dihydro-,	mono-C15-	-20-alkenyl de	erivs.			
	Acute fish toxicity	LC50 mg/l	> 10	96 h	Leuciscus idus	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	85,1	72 h		REACh Registration Dossier	OECD Guideline 201
	Molybdenum trioxide, rea	ction produc	cts with bis[O	,O-bis(2-	ethylhexyl)] hydrogen dit	hiophosphate	
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute bacteria toxicity	EC50 mg/l ( )	> 1000	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-he	xane				
	OECD Guideline 301 F	98%	28	ECHA		
	Easily biodegradable (concerning to the criteria of the OECD)					
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics					
	OECD Guideline 301 F	89 %	28	ECHA		

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	2,36
106-97-8	butane	2,89
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	> 6,6
68602-85-7	Hydrocarbon waxes (petroleum), oxidized, Me esters	> 10
68784-12-3	2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.	6,74



according to UK REACH Regulation

#### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 15 of 18

#### BCF

CAS No	Chemical name	BCF	Species	Source
	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	3,16	fish	Study report (2013)
	2,5-Furandione, dihydro-, mono-C15-20-alkenyl derivs.	63,79	fish	Study report (2014)

#### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

## List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

## List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

## Inland waterways transport (ADN)



according to UK REACH Regulation

100 Multifunktionsöl 150ml DUM

Product code: 1107095 Revision date: 10.03.2023 Page 16 of 18

UN 1950 14.1. UN number or ID number: 14.2. UN proper shipping name: **AEROSOLS** 

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1 Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 I Excepted quantity: E0

Marine transport (IMDG)

UN 1950 14.1. UN number or ID number: **AEROSOLS** 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2 1 Marine pollutant: no

**Special Provisions:** 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D. S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

AEROSOLS, flammable 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 2.1 14.4. Packing group: Hazard label: 2.1

**Special Provisions:** A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger: 203 75 kg IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: 203 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial No information available.

emissions:

Directive 2004/42/EC on VOC in

No information available. paints and varnishes:



according to UK REACH Regulation

### 100 Multifunktionsöl 150ml DUM

Revision date: 10.03.2023 Product code: 1107095 Page 17 of 18

Information according to Directive

P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

**Additional information** 

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Aerosol 1; H222-H229	On basis of test data	
Asp. Tox. 1; H304	Calculation method	
Skin Irrit. 2; H315	Bridging principle "Aerosols"	
Skin Sens. 1; H317		
STOT SE 3; H336	Bridging principle "Aerosols"	
Aquatic Chronic 3; H412	Calculation method	

## Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas. H222 Extremely flammable aerosol.



according to UK REACH Regulation

100 Multifunktionsöl 150ml DUM			
Revision date: 10.03.2023	Product code: 1107095	Page 18 of 18	
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
EUH066	Repeated exposure may cause skin dryness or cracking.		

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)