

according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Aerosol TUNPRO WK mit Fluoreszenzfarbsto

UFI: 2W99-A0CV-U00Q-RURW

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

No information available.

### 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

**1.4. Emergency telephone** 1774 / +356 2559 4600

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## Regulation (EC) No 1272/2008

# Hazard components for labelling

Hydrocarbons C7-C9, iso-alkanes

Signal word: Danger

Pictograms:







# **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.



Revision date: 11.03.2025

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Aerosol TUNPRO WK mit Fluoreszenzfarbsto	
Product code: 1108357	Page 2 of 11

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulat	ion (EC) No 1272/2008)		
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied	gas; H220 H280	•	
64741-66-8	Hydrocarbons C7-C9,	iso-alkanes		25 - < 50 %
	921-728-3		01-2119471305-42	
	Flam. Liq. 2, Skin Irrit. H411	2, STOT SE 3, Asp. Tox. 1, Aquatic C	hronic 2; H225 H315 H336 H304	
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied	gas; H220 H280	•	
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied	gas; H220 H280	•	

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

	<u></u>		
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64741-66-8	921-728-3	Hydrocarbons C7-C9, iso-alkanes	25 - < 50 %
	1	0 = > 21 mg/l (vapours); inhalation: LC50 = >9,4 mg/l (dusts or mists); dermal: - 2500 mg/kg; oral: LD50 = > 7100 - 7800 mg/kg	

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

## After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.





according to Regulation (EC) No 1907/2006

# **Aerosol TUNPRO WK mit Fluoreszenzfarbsto**

Revision date: 11.03.2025 Product code: 1108357 Page 3 of 11

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Water mist. Foam. Carbon dioxide (CO2). Extinguishing powder.

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

### Additional information

Danger of bursting container.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

# General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

### For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

# 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

# For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7



according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 4 of 11

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Further information on handling

Avoid contact with skin and eyes.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

# Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

# Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## **DNEL/DMEL values**

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
64741-66-8	Hydrocarbons C7-C9, iso-alkanes			
Worker DNEL, long-term inhalation systemic 2035 mg/r		2035 mg/m³		
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift



according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 5 of 11

blood (B) Urine (U)

### 8.2. Exposure controls

# Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

# **Environmental exposure controls**

Observe legal regulations and provisions.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: yellow-brown Odour: characteristic

Test method

Melting point/freezing point: not determined

Boiling point or initial boiling point and -42 °C

boiling range:

Flammability: not determined Lower explosion limits: 0,7 vol. % Upper explosion limits: 9,4 vol. % Flash point: -80 °C Auto-ignition temperature: not determined Decomposition temperature: not determined

pH-Value (at 20 °C): DIN 19268

Viscosity / kinematic: < 20,5 mm²/s

(at 40 °C)

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined





according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 6 of 11

Vapour pressure: not determined

Density (at 20 °C):

Relative vapour density: not determined Particle characteristics: not applicable

## 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

Heating may cause an explosion.

Oxidizing properties

The product is not: oxidising.

#### **Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

## 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

## 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

## 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

## **Further information**

Do not mix with other chemicals.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

## **Acute toxicity**

Based on available data, the classification criteria are not met.

## **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l





according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64741-66-8	Hydrocarbons C7-C9, iso	-alkanes			
	oral	LD50 > 7100 - 7800 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	dermal	LD50 > 2200 - 2500 mg/kg	Rabbit		Standard acute method, applying 4 differ
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Study report (1985)	OECD Guideline 403
	inhalation (4 h) dust/mist	LC50 >9,4 mg/l	Rat		

### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

## STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C7-C9, iso-alkanes)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

# Specific effects in experiment on an animal

No information available.

### 11.2. Information on other hazards

# **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. No information available.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 8 of 11

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64741-66-8	Hydrocarbons C7-C9, iso-	alkanes					
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l		Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	ca. 2,4	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC mg/l	0,778	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	QSAR
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211

## 12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
64741-66-8	Hydrocarbons C7-C9, iso-alkanes	4,5
74-98-6	propane	2,36
106-97-8	butane	2,89

## BCF

CAS No	Chemical name	BCF	Species	Source
64741-66-8	Hydrocarbons C7-C9, iso-alkanes	198,7	Mytilus edulis	REACh Registration D

# 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

## **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.



according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Revision date: 11.03.2025 Product code: 1108357 Page 9 of 11

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

# **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2

14.4. Packing group:
Hazard label: 2.1

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

Classification code:

14.1. UN number or ID number: UN 1950

**14.2. UN proper shipping name:** AEROSOLS (Hydrocarbons C7-C9, iso-alkanes)

5F

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:yes

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1
14.4. Packing group:





according to Regulation (EC) No 1907/2006

# Aerosol TUNPRO WK mit Fluoreszenzfarbsto

Product code: 1108357 Revision date: 11.03.2025 Page 10 of 11

Hazard label: 2.1

A145 A167 A802 **Special Provisions:** 

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger: 203 IATA-max. quantity - Passenger: 75 kg IATA-packing instructions - Cargo: 203 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** 

Danger releasing substance: Hydrocarbons C7-C9, iso-alkanes

14.6. Special precautions for user Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial No information available.

emissions:

Directive 2004/42/EC on VOC in No information available.

paints and varnishes:

Information according to Directive P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Additional information: E2

**Additional information** 

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

National regulatory information

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**





according to Regulation (EC) No 1907/2006

# **Aerosol TUNPRO WK mit Fluoreszenzfarbsto**

Revision date: 11.03.2025 Product code: 1108357 Page 11 of 11

## Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosol Liquefied gas

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits
TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

# Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
11004	Mary by fatal if any lland and antana simular

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)