



**902 Maintenance Oil+ 400 ml HT1**

Revision: 25.02.2026

Product code: 1108518

Page 2 of 16

P410+P412  
P501Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container according to the official regulations.**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
75-28-5	isobutane	50 - < 100 %
	200-857-2	601-004-00-0
	01-2119485395-27	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280	
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	20 - < 25 %
	918-167-1	01-2119472146-39
	Flam. Liq. 3, Asp. Tox. 1; H226 H304 EUH066	
64742-54-7	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic	10 - < 20 %
	265-157-1	01-2119484627-25
	Asp. Tox. 1; H304	
74-98-6	propane	5 - < 10 %
	200-827-9	601-003-00-5
	01-2119486944-21	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280	
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes	3 - < 5 %
	921-728-3	01-2119471305-42
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
106-97-8	butane	1 - < 3 %
	203-448-7	601-004-00-0
	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280	
1809-14-9	dioctyl phosphonate	< 0.1 %
	217-315-6	01-2120792463-47
	Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2; H319 H400 H411	
68187-67-7	Amines, C12-14 alkyl, iso-octyl phosphates	< 0.1 %
	269-119-5	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H314 H318 H400 H411	
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts	< 0.1 %
	307-593-8	01-2119985174-30
	Skin Sens. 1B; H317	

Full text of H and EUH statements: see section 16.



## Safety Data Sheet

## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 3 of 16

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
90622-57-4	918-167-1	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics inhalation: LC50 = >25 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	20 - < 25 %
64742-54-7	265-157-1	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	10 - < 20 %
64741-66-8	921-728-3	Hydrocarbons, C7-C9, iso-alkanes inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >9,4 mg/l (dusts or mists); dermal: LD50 = > 2200 - 2500 mg/kg; oral: LD50 = > 7100 - 7800 mg/kg	3 - < 5 %
1809-14-9	217-315-6	dioctyl phosphonate dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=10	< 0.1 %
68187-67-7	269-119-5	Amines, C12-14 alkyl, iso-octyl phosphates dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg	< 0.1 %
97675-24-6	307-593-8	Benzene, C9-C13-alkyl derivs., distr. residues, sulfonated, calcium salts inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	< 0.1 %

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 4 of 16

concentrations or in enclosed spaces.

### **5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

#### **For non-emergency personnel**

First aider: Pay attention to self-protection!

#### **For emergency responders**

Fight fire with normal precautions from a reasonable distance.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

### **6.3. Methods and material for containment and cleaning up**

#### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

#### **Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### **Further information on handling**

Avoid contact with skin and eyes.



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 5 of 16

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes			
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	608 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
1809-14-9	dioctyl phosphonate			
	Worker DNEL, long-term	inhalation	systemic	4,9 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,75 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,5 mg/kg bw/day
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts			
	Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,33 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,833 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	0,66 mg/m <sup>3</sup>



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 6 of 16

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
1809-14-9	dioctyl phosphonate	
Freshwater		0,00287 mg/l
Freshwater (intermittent releases)		0,0287 mg/l
Marine water		0,000287 mg/l
Freshwater sediment		33,4 mg/kg
Marine sediment		3,34 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		6,66 mg/kg
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		723500000 mg/kg
Marine sediment		723500000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		868700000 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

- blood (B)
- Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
Thickness of the glove material 0,45 mm  
EN ISO 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**902 Maintenance Oil+ 400 ml HT1**

Revision: 25.02.2026

Product code: 1108518

Page 7 of 16

When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: AX  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow
Odour:	characteristic

		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	-42 °C	
Flammability:	not determined	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	10,8 vol. %	
Flash point:	-80 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value (at 20 °C):	not determined	DIN 19268
Viscosity / kinematic: (at 40 °C)	27 mm <sup>2</sup> /s	
Water solubility:	easily soluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,768 g/cm <sup>3</sup>	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

**9.2. Other information****Information with regard to physical hazard classes**

Explosive properties

Heating may cause an explosion.

Oxidizing properties

The product is not: oxidising.

**Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 8 of 16

### **10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### **10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

### **10.6. Hazardous decomposition products**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes**

#### **Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



## Safety Data Sheet

## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 9 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 >25 mg/l	Rat		
64742-54-7	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes				
	oral	LD50 > 7100 - 7800 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	dermal	LD50 > 2200 - 2500 mg/kg	Rabbit	Study report (1961)	Standard acute method, applying 4 differ
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Study report (1985)	OECD Guideline 403
	inhalation (4 h) dust/mist	LC50 >9,4 mg/l	Rat		
1809-14-9	dioctyl phosphonate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1994)	Exploratory acute oral study on rats: th
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1994)	OECD Guideline 402
68187-67-7	Amines, C12-14 alkyl, isooctyl phosphates				
	oral	ATE 500 mg/kg			
	dermal	ATE 1100 mg/kg			
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1998)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 10 of 16

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

### Specific effects in experiment on an animal

No information available.

## 11.2. Information on other hazards

### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.



## Safety Data Sheet

## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 11 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics						
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	Study report; company data (1995)	OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,209	28 d	Oncorhynchus mykiss	Company report (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	> 1 mg/l	21 d	Daphnia magna	Study report; company data (2012)	OECD Guideline 211
64742-54-7	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic						
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)		
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes						
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	ca. 2,4	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC mg/l	0,778	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	QSAR
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
1809-14-9	dioctyl phosphonate						
	Acute fish toxicity	LC50 mg/l	ca. 6,8	96 h	Danio rerio	Study report (1994)	EU Method C.1
	Acute algae toxicity	ErC50 mg/l	18,4	72 h	Desmodesmus subspicatus	Study report (2017)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	ca. 2,87	48 h	Daphnia magna	Study report (2017)	OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ( )	> 100	3 h	Activated sludge	Study report (1994)	other: 87/302 EEC page 118-122
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts						
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Cyprinodon variegatus	Study report (1986)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300

## 12.2. Persistence and degradability



## Safety Data Sheet

## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 12 of 16

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes	4,5
106-97-8	butane	2,89
1809-14-9	dioctyl phosphonate	ca. 6,13
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts	10,68

**BCF**

CAS No	Chemical name	BCF	Species	Source
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	144,3	calculated	Other company data (
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes	198,7	Mytilus edulis	REACH Registration D

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the

**902 Maintenance Oil+ 400 ml HT1**

Revision: 25.02.2026

Product code: 1108518

Page 13 of 16

substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63 190 277 327 344 381 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, FLAMMABLE
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----



## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 14 of 16

### **14.6. Special precautions for user**

Warning: Flammable gases.

### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

#### **Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol Directive (75/324/EEC)

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**



## Safety Data Sheet

## 902 Maintenance Oil+ 400 ml HT1

Revision: 25.02.2026

Product code: 1108518

Page 15 of 16

**Abbreviations and acronyms**

Flam. Gas 1: Flammable gases, hazard category 1  
Aerosol 1: Aerosols, hazard category 1  
Press. Gas (Liq.): Gases under pressure: Liquefied gas  
Flam. Liq. 2: Flammable liquids, hazard category 2  
Flam. Liq. 3: Flammable liquids, hazard category 3  
Acute Tox. 4: Acute toxicity, hazard category 4  
Asp. Tox. 1: Aspiration hazard, hazard category 1  
Skin Corr. 1C: Skin corrosion, sub-category 1C  
Skin Irrit. 2: Skin irritation, hazard category 2  
Eye Dam. 1: Serious eye damage, hazard category 1  
Eye Irrit. 2: Eye irritation, hazard category 2  
Skin Sens. 1B: Skin sensitisation, hazard category 1B  
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA: International Air Transport Association  
IMDG: International Maritime Code for Dangerous Goods  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
ATE: Acute Toxicity Estimate  
STEL (EC) Short Term Exposure Limit  
LC50: Lethal Concentration  
EC50: half maximal Effective Concentration  
ErC50: means EC50 in terms of reduction of growth rate

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.

**Safety Data Sheet****902 Maintenance Oil+ 400 ml HT1**

Revision: 25.02.2026

Product code: 1108518

Page 16 of 16

H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*