

**Safety Data Sheet****908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 2 of 15

P101	If medical advice is needed, have product container or label at hand.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container according to the official regulations.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**



Safety Data Sheet

908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 3 of 15

Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
75-28-5	isobutane			50 - < 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes			10 - < 20 %
	921-728-3		01-2119471305-42	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
68037-01-4	Dec-1-ene, homopolymer, hydrogenated			5 - < 10 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
97675-24-6	Benzene, C9-C13-alkyl derivs., distrn. residues, sulfonated, calcium salts			1 - < 3 %
	307-593-8		01-2119985174-30	
	Skin Sens. 1B; H317			
84989-14-0	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., calcium salts			0.1 - < 1 %
	284-903-7		01-2120771873-43	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H302 H315 H318 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64741-66-8	921-728-3	Hydrocarbons, C7-C9, iso-alkanes	10 - < 20 %
	inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >9,4 mg/l (dusts or mists); dermal: LD50 = > 2200 - 2500 mg/kg; oral: LD50 = > 7100 - 7800 mg/kg		
68037-01-4	500-183-1	Dec-1-ene, homopolymer, hydrogenated	5 - < 10 %
	inhalation: LC50 = > 5,2 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
97675-24-6	307-593-8	Benzene, C9-C13-alkyl derivs., distrn. residues, sulfonated, calcium salts	1 - < 3 %
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
84989-14-0	284-903-7	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., calcium salts	0.1 - < 1 %
	oral: ATE = 500 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.



908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 4 of 15

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

**908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 5 of 15

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL



908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 6 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,33 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,66 mg/m ³

PNEC values

CAS No	Substance	Value
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		723500000 mg/kg
Marine sediment		723500000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		868700000 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

- blood (B)
- Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.
EN 166

**908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 7 of 15

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	white
Odour:	characteristic

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	120 °C
Flammability:	not determined
Lower explosion limits:	0,7 vol. %
Upper explosion limits:	9,4 vol. %
Flash point:	-80 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	not determined DIN 19268
Viscosity / kinematic:	not determined
Water solubility:	easily soluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,795 g/cm ³ DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

Heating may cause an explosion.

Oxidizing properties

The product is not: oxidising.

**Safety Data Sheet****908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 8 of 15

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Safety Data Sheet

908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 9 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes				
	oral	LD50 > 7100 - 7800 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	dermal	LD50 > 2200 - 2500 mg/kg	Rabbit	Study report (1961)	Standard acute method, applying 4 differ
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Study report (1985)	OECD Guideline 403
	inhalation (4 h) dust/mist	LC50 >9,4 mg/l	Rat		
68037-01-4	Dec-1-ene, homopolymer, hydrogenated				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 > 5,2 mg/l	Rat		
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1998)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
84989-14-0	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., calcium salts				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, iso-alkanes)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.



Safety Data Sheet

908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 10 of 15

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes						
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	ca. 2,4	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC mg/l	0,778	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	QSAR
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
68037-01-4	Dec-1-ene, homopolymer, hydrogenated						
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna		
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts						
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Cyprinodon variegatus	Study report (1986)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.



Safety Data Sheet

908 Maintenance Grease+ 400 ml HT2

Revision: 25.02.2026

Product code: 1108532

Page 11 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes	4,5
74-98-6	propane	2,36
106-97-8	butane	2,89
97675-24-6	Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts	10,68

BCF

CAS No	Chemical name	BCF	Species	Source
64741-66-8	Hydrocarbons, C7-C9, iso-alkanes	198,7	Mytilus edulis	REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number or ID number:** UN 1950
14.2. UN proper shipping name: AEROSOLS

**908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 12 of 15

14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63 190 277 327 344 381 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

**908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 13 of 15

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Aerosol Directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

**Safety Data Sheet****908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 14 of 15

Abbreviations and acronyms

Flam. Gas 1: Flammable gases, hazard category 1
Aerosol 1: Aerosols, hazard category 1
Press. Gas (Liq.): Gases under pressure: Liquefied gas
Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1B: Skin sensitisation, hazard category 1B
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
EC/EEC: European Community/European Economic Community
EU: European Union
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
M-factor: Multiplying factor
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
DGR: Dangerous Goods Regulations
ICAO: International Civil Aviation Organization
TI: Technical Instructions
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations).

**908 Maintenance Grease+ 400 ml HT2**

Revision: 25.02.2026

Product code: 1108532

Page 15 of 15

Classification for mixtures and used evaluation method

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Benzene, C9-C13-alkyl derivs., distn. residues, sulfonated, calcium salts. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)