





## 921 Adhesive Lubricant+ 400ml HT1

Revision: 18.02.2026

Product code: 1108567

Page 2 of 13

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
75-28-5	isobutane			50 - < 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
68037-01-4	Dec-1-ene, homopolymer, hydrogenated			10 - < 20 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
1809-14-9	dioctyl phosphonate			0.1 - < 1 %
	217-315-6		01-2120792463-47	
	Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2; H319 H400 H411			
68187-67-7	Amines, C12-14 alkyl, isooctyl phosphates			0.1 - < 1 %
	269-119-5			
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H314 H318 H400 H411			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68037-01-4	500-183-1	Dec-1-ene, homopolymer, hydrogenated	10 - < 20 %
	inhalation: LC50 = > 5,2 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
1809-14-9	217-315-6	dioctyl phosphonate	0.1 - < 1 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=10		
68187-67-7	269-119-5	Amines, C12-14 alkyl, isooctyl phosphates	0.1 - < 1 %
	dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg		

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

## After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.



## Safety Data Sheet

### 921 Adhesive Lubricant+ 400ml HT1

Revision: 18.02.2026

Product code: 1108567

Page 3 of 13

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## SECTION 5: Firefighting measures

**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

**For non-emergency personnel**

First aider: Pay attention to self-protection!

**For emergency responders**

Fight fire with normal precautions from a reasonable distance.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 4 of 13

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1809-14-9	diocetyl phosphonate			
	Worker DNEL, long-term	inhalation	systemic	4,9 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,75 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,5 mg/kg bw/day

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 5 of 13

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
1809-14-9	dioctyl phosphonate	
Freshwater		0,00287 mg/l
Freshwater (intermittent releases)		0,0287 mg/l
Marine water		0,000287 mg/l
Freshwater sediment		33,4 mg/kg
Marine sediment		3,34 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		6,66 mg/kg

**Additional advice on limit values**

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

- blood (B)
- Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 6 of 13

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	white
Odour:	characteristic

		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	not determined	
Lower explosion limits:	1,5 vol. %	
Upper explosion limits:	9,4 vol. %	
Flash point:	-80 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value (at 20 °C):	not determined	DIN 19268
Viscosity / kinematic: (at 40 °C)	612 mm <sup>2</sup> /s	
Water solubility:	easily soluble	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,855 g/cm <sup>3</sup>	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

**9.2. Other information****Information with regard to physical hazard classes**

## Explosive properties

Heating may cause an explosion.

## Oxidizing properties

The product is not: oxidising.

**Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 7 of 13

**10.6. Hazardous decomposition products**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68037-01-4	Dec-1-ene, homopolymer, hydrogenated				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 > 5,2 mg/l	Rat		
1809-14-9	dioctyl phosphonate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1994)	Exploratory acute oral study on rats: th
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1994)	OECD Guideline 402
68187-67-7	Amines, C12-14 alkyl, isoctyl phosphates				
	oral	ATE 500 mg/kg			
	dermal	ATE 1100 mg/kg			

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 8 of 13

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

**Specific effects in experiment on an animal**

No information available.

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

No information available.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
68037-01-4	Dec-1-ene, homopolymer, hydrogenated					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna		
1809-14-9	dioctyl phosphonate					
	Acute fish toxicity	LC50 ca. 6,8 mg/l	96 h	Danio rerio	Study report (1994)	EU Method C.1
	Acute algae toxicity	ErC50 18,4 mg/l	72 h	Desmodesmus subspicatus	Study report (2017)	OECD Guideline 201
	Acute crustacea toxicity	EC50 ca. 2,87 mg/l	48 h	Daphnia magna	Study report (2017)	OECD Guideline 202
	Acute bacteria toxicity	EC50 > 100 mg/l ( )	3 h	Activated sludge	Study report (1994)	other: 87/302 EEC page 118-122

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89
1809-14-9	dioctyl phosphonate	ca. 6,13

**921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 9 of 13

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Completely emptied packages can be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-



## Safety Data Sheet

## 921 Adhesive Lubricant+ 400ml HT1

Revision: 18.02.2026

Product code: 1108567

Page 10 of 13

Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63 190 277 327 344 381 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

**Additional information**

Aerosol Directive (75/324/EEC).

**Safety Data Sheet****921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 11 of 13

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Safety Data Sheet****921 Adhesive Lubricant+ 400ml HT1**

Revision: 18.02.2026

Product code: 1108567

Page 12 of 13

**Abbreviations and acronyms**

Flam. Gas 1: Flammable gases, hazard category 1  
Aerosol 1: Aerosols, hazard category 1  
Press. Gas (Liq.): Gases under pressure: Liquefied gas  
Acute Tox. 4: Acute toxicity, hazard category 4  
Asp. Tox. 1: Aspiration hazard, hazard category 1  
Skin Corr. 1C: Skin corrosion, sub-category 1C  
Eye Dam. 1: Serious eye damage, hazard category 1  
Eye Irrit. 2: Eye irritation, hazard category 2  
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
EC/EEC: European Community/European Economic Community  
EU: European Union  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
M-factor: Multiplying factor  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Regulations concerning the international carriage of dangerous goods by rail  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
IMDG: International Maritime Code for Dangerous Goods  
EmS: Emergency Schedules  
MFAG: Medical First Aid Guide  
IATA: International Air Transport Association  
DGR: Dangerous Goods Regulations  
ICAO: International Civil Aviation Organization  
TI: Technical Instructions  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern  
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data



## 921 Adhesive Lubricant+ 400ml HT1

Revision: 18.02.2026

Product code: 1108567

Page 13 of 13

### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*