

according to Regulation (EC) No 1907/2006

#### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**TUNGREASE CF-33** 

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Lubricants, greases, release products

## 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Bürgermeister-Seidl-Str. 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600 - 0 Telefax: +49 (0) 8171/1600 - 40

e-mail: sdb@tunap.com Internet: www.tunap.com

**1.4. Emergency telephone** +49 (0) 30 30 686 790 (Giftnotruf Berlin)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 3 Hazard Statements:

Pressurised container: May burst if heated.

### 2.2. Label elements

## Regulation (EC) No. 1272/2008

Signal word: Warning

**Hazard statements** 

H229 Pressurised container: May burst if heated.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts; Sulfonic acids,

petroleum, calcium salts; Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts.

May produce an allergic reaction.

## 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures



according to Regulation (EC) No 1907/2006

#### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 2 of 11

## Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•	•		
68584-23-6	Benzenesulfonic acid, C10-16-alky	3 - < 5 %			
	271-529-4		01-2119492627-25		
	Skin Sens. 1B; H317				
61789-86-4	Sulfonic acids, petroleum, calcium	1 - < 3 %			
	263-093-9		01-2119488992-18		
	Skin Sens. 1B; H317				
70024-69-0	Benzenesulfonic acid, mono-C16-2	1 - < 3 %			
	274-263-7		01-2119492616-28		
	Skin Sens. 1B; H317				

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

## 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.



according to Regulation (EC) No 1907/2006

#### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 3 of 11

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### Advice on protection against fire and explosion

Heating causes rise in pressure with risk of bursting.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

## Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

## 7.3. Specific end use(s)

No information available.

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



according to Regulation (EC) No 1907/2006

## **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 4 of 11

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
61789-86-4	Sulfonic acids, petroleum, calcium salts					
Worker DNEL,	long-term	inhalation	systemic	11,75 mg/m³		
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day		
Worker DNEL,	long-term	dermal	local	1,03 mg/cm <sup>2</sup>		
Consumer DN	EL, long-term	inhalation	systemic	2,9 mg/m³		
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day		
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>		
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day		
70024-69-0	24-69-0 Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts					
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³		
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day		
Worker DNEL, long-term		dermal	local	1,03 mg/cm <sup>2</sup>		
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³		
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day		
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>		
Consumer DN	EL, long-term	oral	systemic	0,833 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

## **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 5 of 11

#### **PNEC values**

CAS No	Substance				
Environmental	compartment	Value			
61789-86-4	Sulfonic acids, petroleum, calcium salts				
Freshwater		1 mg/l			
Freshwater (in	Freshwater (intermittent releases)				
Marine water		1 mg/l			
Freshwater se	diment	226000000 mg/kg			
Marine sedime	nt	226000000 mg/kg			
Secondary poi	16,667 mg/kg				
Micro-organism	1000 mg/l				
Soil	271000000 mg/kg				
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts				
Freshwater		1 mg/l			
Freshwater (intermittent releases)		10 mg/l			
Marine water		1 mg/l			
Freshwater sediment		226000000 mg/kg			
Marine sediment		226000000 mg/kg			
Secondary poisoning		16,667 mg/kg			
Micro-organism	Micro-organisms in sewage treatment plants (STP)				
Soil 27					

## Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B)

Urine (U)

## 8.2. Exposure controls

### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

**DIN EN 166** 

## **Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 



according to Regulation (EC) No 1907/2006

### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 6 of 11

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

## Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

## **Environmental exposure controls**

Observe legal regulations and provisions.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: blue

Odour: characteristic

Test method

pH-Value (at 20 °C): not applicable DIN 19268

Changes in the physical state

Initial boiling point and boiling range: 200 °C Flash point: >200 °C

**Flammability** 

Solid: not determined
Gas: not applicable

Auto-ignition temperature

Solid: not determined Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidising.

Density: 1,2 g/cm³ DIN 51757

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

## Solubility in other solvents

not determined

## 9.2. Other information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

## 10.2. Chemical stability

The product is stable under normal conditions.

## 10.3. Possibility of hazardous reactions



according to Regulation (EC) No 1907/2006

### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 7 of 11

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

## 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source		
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts						
	oral	LD50	>5000 mg/kg	Rat			
	dermal	LD50	>5000 mg/kg	Rat			
	inhalation (4 h) aerosol	LC50	>5 mg/l	Rat			
61789-86-4	Sulfonic acids, petroleum, calcium salts						
	oral	LD50 mg/kg	> 16000	Rat	Study report (1981)		
	dermal	LD50	> 5000 mg/kg	Rabbit	Study report (1981)		
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts						
	oral	LD50 mg/kg	> 16000	Rat	Study report (1981)		
	dermal	LD50	> 4000 mg/kg	Rabbit	Study report (1986)		
	inhalation (4 h) aerosol	LC50	>5 mg/l	Rat			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

## Sensitising effects

Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts; Sulfonic acids, petroleum, calcium salts; Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

### STOT-single exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

## **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 8 of 11

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Specific effects in experiment on an animal

No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

The product is not: Ecotoxic

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source		
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts							
	Acute fish toxicity	LC50	>10000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50	>1000 mg/l	96 h	Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna			
61789-86-4	Sulfonic acids, petroleum, calcium salts							
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)		
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	Study report (1993)		
	Acute bacteria toxicity	(> 10000	(> 10000 mg/l)		activated sludge of a predominantly domestic sewag	Study report (1994)		
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts							
	Acute fish toxicity	LC50	>10000 mg/l	96 h	Cyprinus carpio (Common Carp)			
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier		
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	REACh Registration Dossier		
	Acute bacteria toxicity	(> 10000	O mg/l)	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier		

## 12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
61789-86-4	Sulfonic acids, petroleum, calcium salts	> 4,46
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	18,05

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

This substance does not meet the criteria for classification as PBT or vPvB.



according to Regulation (EC) No 1907/2006

### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 9 of 11

#### 12.6. Other adverse effects

No information available.

#### **Further information**

No special environmental measures are necessary.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.2

Classification code: 5A Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 3
Tunnel restriction code: E

Inland waterways transport (ADN)

**14.1. UN number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.2

Special Provisions: 190 327 344 625

5A

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

Classification code:

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS



according to Regulation (EC) No 1907/2006

 TUNGREASE CF-33

 Print date: 22.11.2020
 Product code: 11ACF13066A0400
 Page 10 of 11

14.3. Transport hazard class(es):2.214.4. Packing group:-Hazard label:2.2Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950

14.2. UN proper shipping name: AEROSOLS, non-flammable

14.3. Transport hazard class(es):2.214.4. Packing group:-Hazard label:2.2

Special Provisions: A98 A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## 14.6. Special precautions for user

No information available.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

## **Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2.



according to Regulation (EC) No 1907/2006

### **TUNGREASE CF-33**

Print date: 22.11.2020 Product code: 11ACF13066A0400 Page 11 of 11

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Relevant H and EUH statements (number and full text)

H229 Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction.

EUH208 Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts; Sulfonic acids,

petroleum, calcium salts; Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts.

May produce an allergic reaction.

## **Further Information**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)