

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TUNPRO TR -Trockenschmierstoff

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant, lubricants and release products

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+ 49 (0) 8171/1600 - 0	Telefax: + 49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

Supplier

Company name:	TUNAP UK Limited
Street:	Unit L4 Deacon Trading Estate, Morley Road
Place:	GB Tonbridge, Kent. TN9 1RA
Telephone:	+44 (0)1732 365163
e-mail:	sdb@tunap.com
Internet:	www.tunap.co.uk

1.4. Emergency telephone number: 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Signal word: Danger



according to Regulation (EC) No 1907/2006

TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 2 of 14

Pictograms:**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P350	IF ON SKIN: Gently wash with plenty of soap and water.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH208	Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.
--------	--

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			20 - < 25 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			20 - < 25 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			0.1 - < 1 %
	274-263-7		01-2119492616-2	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 4 of 14

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities


TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 5 of 14

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

Lubricant, lubricants and release products

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 6 of 14

PNEC values

CAS No	Substance	
	Environmental compartment	Value
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	
	Freshwater	1 mg/l
	Freshwater (intermittent releases)	10 mg/l
	Marine water	1 mg/l
	Freshwater sediment	226000000 mg/kg
	Marine sediment	226000000 mg/kg
	Secondary poisoning	16,667 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1000 mg/l
	Soil	271000000 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

- blood (B)
- Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min
Thickness of the glove material 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.


TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 7 of 14

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: beige
 Odour: Solvent

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: -40 °C

Flash point: -80 °C ISO 3679

Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 1 vol. %

Upper explosion limits: 11 vol. %

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,715 g/cm³ DIN 51757

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: DIN 53019-1

Viscosity / kinematic:
(at 40 °C) DIN EN ISO 3104

Flow time:
(at 20 °C) DIN EN ISO 2431

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity
10.2. Chemical stability

The product is stable under normal conditions.

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 8 of 14

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
75-28-5	isobutane			
	inhalation vapour	LC50 1237 mg/l	Mouse.	
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	oral	LD50 > 5000 mg/kg	Rat	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
	oral	LD50 5500 mg/kg	Rat	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)
106-97-8	butane			
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 9 of 14

Sensitising effects

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane;

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 10 of 14

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
75-28-5	isobutane				
	Acute fish toxicity	LC50 91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	Acute fish toxicity	LC50 > 1-10 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)
	Acute crustacea toxicity	EC50 > 1-10 mg/l	48 h	Daphnia magna	
	Fish toxicity	NOEC 2,045 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	Acute fish toxicity	LC50 >1 - 10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM
	Acute crustacea toxicity	EC50 >1 - 10 mg/l	48 h	Daphnia magna	
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM
74-98-6	propane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
106-97-8	butane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)



according to Regulation (EC) No 1907/2006

TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 11 of 14

	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts					
	Acute fish toxicity	LC50	>10000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	RECh Registration Dossier
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	RECh Registration Dossier
	Acute bacteria toxicity		(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	RECh Registration Dossier

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	OECD Guideline 301 F	98%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	18,05

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste


TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 12 of 14

List of Wastes Code - used product

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1
 Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1
 Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane)
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Marine pollutant: yes
 Special Provisions: 63, 190, 277, 327, 344, 959
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
 Hazard label: 2.1
 Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203



according to Regulation (EC) No 1907/2006

TUNPRO TR -Trockenschmierstoff

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 13 of 14

IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,10,11,12,13,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

**TUNPRO TR -Trockenschmierstoff**

Print date: 28.01.2021

Product code: 11ACH12400A0400

Page 14 of 14

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)