

according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TUNPRO WK - colorless

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer		
Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+ 49 (0) 8171/1600 - 0	Telefax: + 49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	
Supplier		
Company name:	TUNAP UK Limited	
Street:	Unit L4 Deacon Trading Estate, Morley Road	
Place:	GB Tonbridge, Kent. TN9 1RA	
Telephone:	+44 (0)1732 365163	
e-mail:	sdb@tunap.com	
Internet:	www.tunap.co.uk	
1.4. Emergency telephone	111 NHS (National Health Service)	
number:		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Danger

Signal word:



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless Product code: 11ACH29821A0400 Print date: 28.01.2021 Page 2 of 13 **Pictograms:** Hazard statements H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. H411 **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves. IF ON SKIN: Wash with plenty of water. P302+P352 P332+P313 If skin irritation occurs: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 3 of 13

Hazardous components

Chemical name					
EC No	Index No	REACH No			
GHS Classification		·			
isobutane			25 - < 50 %		
200-857-2	601-004-00-0	01-2119485395-27			
Flam. Gas 1, Liquefied g	as; H220 H280				
Hydrocarbons, C6-C7, n	-alkanes, isoalkanes, cyclics, < 5% r	-hexane	20 - < 25 %		
921-024-6		01-2119475514-35			
Flam. Liq. 2, Skin Irrit. 2, H411					
Hydrocarbons, C7, n-alk	10 - < 20 %				
927-510-4		01-2119475515-33			
Flam. Liq. 2, Skin Irrit. 2, H411					
propane			5 - < 10 %		
200-827-9	601-003-00-5	01-2119486944-21			
Flam. Gas 1, Liquefied g					
butane	1 - < 3 %				
203-448-7	601-004-00-0	01-2119474691-32			
Flam. Gas 1, Liquefied g					
	EC No GHS Classification isobutane 200-857-2 Flam. Gas 1, Liquefied g Hydrocarbons, C6-C7, n 921-024-6 Flam. Liq. 2, Skin Irrit. 2, H411 Hydrocarbons, C7, n-alk 927-510-4 Flam. Liq. 2, Skin Irrit. 2, H411 propane 200-827-9 Flam. Gas 1, Liquefied g butane 203-448-7	EC No Index No GHS Classification isobutane 200-857-2 601-004-00-0 Flam. Gas 1, Liquefied gas; H220 H280 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n	EC No Index No REACH No GHS Classification isobutane 200-857-2 601-004-00-0 01-2119485395-27 Flam. Gas 1, Liquefied gas; H220 H280 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 4 of 13

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 5 of 13

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%	n-hexane				
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³		
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	608 mg/m³		
Consumer DNI	EL, long-term	dermal	systemic	699 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	699 mg/kg bw/day		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
Worker DNEL,	long-term	inhalation	systemic	2085 mg/m³		
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³		
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	149 mg/kg bw/day		

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Product code: 11ACH29821A0400

Page 6 of 13

Print date: 28.01.2021

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. When exceeding the relevant workplace exposure limits, note the following: Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Filtering device with filter or ventilator filtering device of type: AX Observe the wear time limits as specified by the manufacturer. Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	brown	
Odour:	solvent like	
		Test method
pH-Value (at 20 °C):		DIN 19268
Changes in the physical state		
Melting point:	No information available.	
Initial boiling point and boiling range:	-40 °C	
Sublimation point:	No information available.	
Softening point:	No information available.	
Flash point:	-26 °C	
Lower explosion limits:	1 vol. %	
Upper explosion limits:	11 vol. %	
Ignition temperature:	No information available.	
Vapour pressure:	No information available.	
Vapour pressure:	No information available.	
Density (at 20 °C):	0,71 g/cm³	DIN 51757
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents		

Solubility in other solvents not determined

according to Regulation (EC) No 1907/2006



	TUNPRO WK - colorless	
Print date: 28.01.2021	Product code: 11ACH29821A0400	Page 7 of 13
Partition coefficient:	No information available.	
Viscosity / dynamic:	No information available.	
Viscosity / kinematic: (at 40 °C)	1,1 mm²/s	
Flow time:	No information available.	
Vapour density:	No information available.	
Evaporation rate:	No information available.	
Solvent separation test:	No information available.	
Solvent content:	No information available.	
9.2. Other information		
Solid content:	No information available.	

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 8 of 13

CAS No	Chemical name						
	Exposure route	Dose		Species	Source		
75-28-5	isobutane				_		
	inhalation vapour	LC50	1237 mg/l	Mouse.			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, is	oalkanes, c	yclics, < 5% n-hex	ane			
	oral	LD50	> 5000 mg/kg	Rat			
	dermal	LD50 mg/kg	> 2800 - 3100	Rat	Study report (1977)		
	inhalation (4 h) vapour	LC50	> 25,2 mg/l	Rat	Study report (1988)		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoal	kanes, cyclio	cs	•			
	oral	LD50	5500 mg/kg	Rat			
	dermal	LD50 mg/kg	> 2800 - 3100	Rat	Study report (1977)		
	inhalation (4 h) vapour	LC50	> 23,3 mg/l	Rat	Study report (1988)		
106-97-8	butane						
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless

Print date: 28.01.2021

Product code: 11ACH29821A0400

Page 9 of 13

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d]	Species	Source				
75-28-5	isobutane									
	Acute fish toxicity	LC50	91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A				
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200				
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200				
92128-66-0	Hydrocarbons, C6-C7, n-alka	anes, isoalkan	es, cyclics, < 5% r	n-hexane	_					
	Acute fish toxicity	LC50	> 1-10 mg/l	96 h	Pimephales promelas					
	Acute algae toxicity	ErC50	10 - 30 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)				
	Acute crustacea toxicity	EC50	> 1-10 mg/l	48 h	Daphnia magna					
	Fish toxicity	NOEC	2,045 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)				
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM				
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics									
	Acute fish toxicity	LC50	>1 - 10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)					
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM				
	Acute crustacea toxicity	EC50	>1 - 10 mg/l	48 h	Daphnia magna					
	Fish toxicity	NOEC	1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)				
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM				
74-98-6	propane									
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A				
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200				
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200				
106-97-8	butane									
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A				
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200				



according to Regulation (EC) No 1907/2006

		٦		colorless	;		
Print date:	28.01.2021	Pro	duct code: 11ACI	H29821A040	00	Page 10 of 13	3
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h Dap	ohnia sp.	USEPA OPPT Risk Assessment Division (200	
<u>12.2. Persi</u>	istence and degradability						
The	ere are no data available on th	e mixture its	elf. AOX (mg/l): 0				
CAS No	Chemical name						

CASINO	Chemical hame						
	Method	Value	d	Source			
	Evaluation	•	•	•			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
	OECD Guideline 301 F	98%	28				
	Easily biodegradable (concerning to the criteria of the OECD)						

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

	TUNPRO WK - colorless	
Print date: 28.01.2021	Product code: 11ACH29821A0400	Page 11 of 13
Land transport (ADR/RID)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	E0	
Transport category:	2	
Tunnel restriction code:	D	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
<u>14.3. Transport hazard class(es):</u>	2	
<u>14.4. Packing group:</u>	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1 L	
Excepted quantity:	E0	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5 n-hexane)	%
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Marine pollutant:	Ves	
Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity:	1000 mL	
Excepted quantity:	E0	
EmS:	F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS, flammable	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless				
Print date: 28.01.2021	Product code: 11ACH29821A0400	Page 12 of 13		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	Yes			
Danger releasing substance:	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane			
14.6. Special precautions for user				
Warning: Flammable gases.				
14.7. Transport in bulk according to Annex I	I of Marpol and the IBC Code			
not applicable				
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture				
EU regulatory information				
Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 29				
2010/75/EU (VOC):	No information available.			
2004/42/EC (VOC):	No information available.			
Additional information				
Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol directive (75/324/EEC)				
National regulatory information				
Water hazard class (D):	2 - obviously hazardous to water			
SECTION 16: Other information				
Changes This data sheet contains changes from	the previous version in section(s): 2,3,4,5,7,8,9,10,11,12,14,15,16.			
Abbreviations and acronyms				
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)				
PID: Padement international concernant le transport des marchandises dangerouses par chemin de for				

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.



according to Regulation (EC) No 1907/2006

TUNPRO WK - colorless				
Print date: 28.01.2021	Product code: 11ACH29821A0400	Page 13 of 13		
H304	May be fatal if swallowed and enters airways.			
H315	Causes skin irritation.			
H336	May cause drowsiness or dizziness.			
H411	Toxic to aquatic life with long lasting effects.			
Further Information				
Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:				
Calculation method.				
	tion describes exclusively the safety requirements of the product and is based on our edge. The information is intended to give you advice about the safe handling of the product	t		

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)