

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: TUNAP GmbH & Co. KG
Street: Bürgermeister-Seidl-Str. 2
Place: D-82515 Wolfratshausen
Telephone: + 49 (0) 8171/1600 - 0
e-mail: sdb@tunap.com
Internet: www.tunap.com Telefax: + 49 (0) 8171/1600 - 40

Supplier

Company name: TUNAP UK Limited
Street: Unit L4 Deacon Trading Estate, Morley Road
Place: GB Tonbridge, Kent. TN9 1RA
Telephone: +44 (0)1732 365163
e-mail: sdb@tunap.com
Internet: www.tunap.co.uk

1.4. Emergency telephone number:

111 NHS (National Health Service)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Respiratory or skin sensitisation: Skin Sens. 1
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Polysulfides, di-tert-butyl
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
Diisododecylphenyl phosphite
reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptylderivs.
Triisodecyl phosphite

Signal word: Warning**Pictograms:**



TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 2 of 13

Hazard statements

- H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/container according to the official regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
68937-96-2	Polysulfides, di-tert-butyl	1 - < 3 %
	273-103-3	01-2119540515-43
	Skin Sens. 1, Aquatic Chronic 3; H317 H412	
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	1 - < 3 %
	931-384-6	01-2119493620-38
	Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H302 H318 H317 H411	
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate	0.1 - < 1 %
	947-946-9	01-2120772600-59
	Skin Irrit. 2, Skin Sens. 1B, Aquatic Chronic 4; H315 H317 H413	
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	0.1 - < 1 %
	627-034-4	01-2119473797-19
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410	
25550-98-5	Diisododecylphenyl phosphite	0.1 - < 1 %
	247-098-3	01-2119962888-14
	Skin Sens. 1; H317	
	reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptylderivs.	0.1 - < 1 %
	939-460-0	01-2119971727-23
	Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H315 H318 H317 H412	
25448-25-3	Triisodecyl phosphite	0.1 - < 1 %
	246-998-3	01-2119964066-34
	Skin Sens. 1; H317	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 3 of 13

4.1. Description of first aid measures**General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 4 of 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**


TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
68937-96-2	Polysulfides, di-tert-butyl			
Worker DNEL, long-term		inhalation	systemic	3,29 mg/m ³
Worker DNEL, long-term		dermal	systemic	4,67 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,58 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,167 mg/kg bw/day
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate			
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,4 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines			
Worker DNEL, long-term		inhalation	systemic	0,38 mg/m ³
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Worker DNEL, acute		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,035 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day
25448-25-3	Triisodecyl phosphite			
Worker DNEL, long-term		inhalation	systemic	70,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35,3 mg/m ³
Consumer DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	5 mg/kg bw/day

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
68937-96-2	Polysulfides, di-tert-butyl	
Freshwater		0,00024 mg/l
Freshwater (intermittent releases)		0,002 mg/l
Marine water		0,000024 mg/l
Freshwater sediment		0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,51 mg/l
Soil		0,0181 mg/kg
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	
Freshwater		0,00026 mg/l
Freshwater (intermittent releases)		0,0016 mg/l
Marine water		0,000026 mg/l
Freshwater sediment		3,76 mg/kg
Marine sediment		0,376 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,55 mg/l
Soil		10 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min
Thickness of the glove material 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.


TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 7 of 13

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 When exceeding the relevant workplace exposure limits, note the following:
 Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
 Filtering device with filter or ventilator filtering device of type: A
 Observe the wear time limits as specified by the manufacturer.
 Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	brown, clear	
Odour:	characteristic	
		Test method
pH-Value (at 20 °C):	not determined	DIN 19268
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	> 200 °C	
Flash point:	> 200 °C	ISO 3679
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Auto-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties		
Not oxidising.		
Vapour pressure:	not determined	
Density (at 20 °C):	0,8975 g/cm ³	DIN 51757
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents		
not determined		
Partition coefficient:	not determined	
Viscosity / dynamic:		DIN 53019-1
Viscosity / kinematic: (at 40 °C)	220 mm ² /s	DIN EN ISO 3104
Flow time: (at 20 °C)		DIN EN ISO 2431
Vapour density:	not determined	
Evaporation rate:	not determined	

9.2. Other information

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 8 of 13

Solid content:

not determined

SECTION 10: Stability and reactivity**10.2. Chemical stability**

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

**TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl**

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 9 of 13

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
68937-96-2	Polysulfides, di-tert-butyl			
	oral	LD50 > 2000 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rat	
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)			
	oral	LD50 >2000 mg/kg	Rat	
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines			
	oral	LD50 1689 mg/kg	Rat	Study report (1993)
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat	
25550-98-5	Diisododecylphenyl phosphite			
	oral	LD50 >2000 mg/kg	Rat	
	dermal	LD50 >2000 mg/kg	Rat	
	reaction product of 1,3,4-thiadiazolidine-2,5-dithione,formaldehyde and phenol, heptylderivs.			
	oral	LD50 >2000 mg/kg	Rat	
	dermal	LD50 >2000 mg/kg	Rat	
25448-25-3	Triisodecyl phosphite			
	oral	LD50 13800 mg/kg	Rat	Study report (1964)
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1980)
	inhalation (4 h) aerosol	LC50 >12 mg/l	Rat	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Polysulfides, di-tert-butyl; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate; Diisododecylphenyl phosphite; reaction product of 1,3,4-thiadiazolidine-2,5-dithione,formaldehyde and phenol, heptylderivs.; Triisodecyl phosphite)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.


TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 10 of 13

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
68937-96-2	Polysulfides, di-tert-butyl				
	Acute fish toxicity	LC50 > 0,088 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50 0,838 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier
	Acute crustacea toxicity	EC50 63 mg/l	48 h	Daphnia magna	Study report (2013)
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)				
	Acute fish toxicity	LC50 24 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 15 mg/l	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 91,4 mg/l	48 h	Daphnia magna	
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate				
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines				
	Acute fish toxicity	LC50 0,84 mg/l	96 h	Danio rerio	Study report (2006)
	Acute algae toxicity	ErC50 0,39 mg/l	72 h	Desmodesmus subspicatus	Study report (2002)
	Acute crustacea toxicity	EC50 0,32 mg/l	48 h	Daphnia magna	Study report (2006)
	Crustacea toxicity	NOEC 0,013 mg/l	21 d	Daphnia magna	Study report (2002)
	Acute bacteria toxicity	(32 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1989)
25550-98-5	Diisododecylphenyl phosphite				
	Acute fish toxicity	LC50 >100 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50 45 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 > 2 mg/l	48 h	Daphnia magna	
	reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptylderivs.				
	Acute fish toxicity	LC50 26 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 9,2 mg/l	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 75 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.



according to Regulation (EC) No 1907/2006

TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 11 of 13

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines			
		44	28	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68937-96-2	Polysulfides, di-tert-butyl	5,6
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	5,16
25448-25-3	Triisodecyl phosphite	12,31

BCF

CAS No	Chemical name	BCF	Species	Source
68937-96-2	Polysulfides, di-tert-butyl	0,006	Lepomis macrochirus	Study report (2015)
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	173		Environmental Toxicology

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130208 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; other engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130208 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; other engine, gear and lubricating oils; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.


TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 12 of 13

SECTION 14: Transport information
Land transport (ADR/RID)

<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Marine pollutant:	no

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water


TUNGEAR 220 20I D-GB-F-I-E-PL Getriebeöl

Print date: 30.01.2021

Product code: 11ACI19003L0200

Page 13 of 13

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 2,14.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)