

Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

928 Scheibenklar Pure MP92800K30AB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

E-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Flammable liquids: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

GB CLP Regulation

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.
P280 Wear eye/face protection.
P233 Keep container tightly closed.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 2 of 11

Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
64-17-5	17-5 ethanol				
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319				
107-21-1	1 ethanediol, ethylene glycol			5 - < 10 %	
	203-473-3		01-2119456816-28		
	Acute Tox. 4, STOT RE 2; H302 H373				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE			
64-17-5	200-578-6	ethanol	50 - < 100 %		
	inhalation: LC50 = 95,6 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 6200 mg/kg Eye Irrit. 2; H319: >= 50 - 100				
107-21-1	203-473-3	ethanediol, ethylene glycol	5 - < 10 %		
	dermal: LD50 = >3500 mg/kg; oral: LD50 = 1600 mg/kg				

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % anionic surfactants, < 5 % non-ionic surfactants.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 3 of 11

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 4 of 11

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

Additional advice on limit values

a no restriction

b End of exposure or shift

c in long-term exposure: after several shifts

d prior to next shift

TWA (EC): time-weighted average

U: Urea B: Blood

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 5 of 11

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: colorless, clear
Odour: alcoholic

Test method

Print date: 15.10.2024

Melting point/freezing point:

Boiling point or initial boiling point and

78 °C

boiling range:

Lower explosion limits:

Flammability: not applicable

not applicable 3,5 vol. %

Upper explosion limits: 15 vol. %

Flash point: 21,5 °C ISO 3679

Auto-ignition temperature: 400 °C Decomposition temperature: not determined

pH-Value (at 20 °C): 11,08 DIN 19268

Viscosity / kinematic: < 7 mm²/s DIN EN ISO 3104

(at 40 °C)

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,8999 g/cm³ DIN 51757

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solvent separation test: No information available. Solvent content: No information available. Solid content: not determined Sublimation point: No information available. Softening point: No information available. No information available. No information available.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 6 of 11

Viscosity / dynamic: No information available. DIN 53019-1
Flow time: No information available. DIN EN ISO 2431

SECTION 10: Stability and reactivity

10.1. Reactivity

(at 20 °C)

Flammable.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol						
	oral	LD50 mg/kg	6200	Rat	IUCLID		
	dermal	LD50 mg/kg	>20000	Rat			
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS		
107-21-1	ethanediol, ethylene glycol						
	oral	LD50 mg/kg	1600	Rat			
	dermal	LD50 mg/kg	>3500	Rabbit			

Irritation and corrosivity



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 7 of 11

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 8 of 11

CAS No	Chemical name							
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method			
64-17-5	ethanol	ethanol						
	Acute fish toxicity	LC50 14200 mg/l	96 h Pimephales promelas (fathead minnow)					
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h Daphnia magna	IUCLID				
107-21-1	ethanediol, ethylene glyco	ethanediol, ethylene glycol						
	Acute fish toxicity	LC50 72860 mg/l	96 h Pimephales promelas					
	Acute algae toxicity	ErC50 6500 - 13000 mg/l	96 h Selenastrum capricornutum					
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h Daphnia magna					
	Fish toxicity	NOEC 72860 mg/l	7 d Pimephales promelas					
	Crustacea toxicity	NOEC 8590 mg/l	7 d Ceriodaphnia spec					

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name							
	Method	Value	d	Source				
	Evaluation		-					
64-17-5	ethanol							
	OECD 301 D	70 %	5					
107-21-1	ethanediol, ethylene glycol							
	OECD Guideline 301 A	90-100 %	10	ECHA				
	leicht biologisch abbaubar							
	OECD Guideline 301 C	>=83 %	14	ECHA				
	leicht biologisch abbaubar							

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
107-21-1	ethanediol, ethylene glycol	-1,36

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 9 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 **Special Provisions:** 144 601 Limited quantity: 1 I Excepted quantity: F2 Transport category: 2 Hazard No: 33 Tunnel restriction code: D/F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:144 601Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 10 of 11

Marine pollutant:

Special Provisions:

Limited quantity:

EmS:

No

144

Lthicker

1 L

F-E, S-D

Other applicable information (marine transport)

Limited quantity: E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3

Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial No information available.

emissions:

Directive 2004/42/EC on VOC in No information available.

paints and varnishes:

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

94/69/EC (21st ATP). The benzene content of the product is less than 0.1%. It applies the annotation P.

Classification and labeling as carcinogenic is not necessary.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



Safety Data Sheet

according to UK REACH Regulation

928 Scheibenklar Pure MP92800K30AB

Revision date: 08.04.2021 Product code: 11AMP92800K30AB Page 11 of 11

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,14,15,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Eye Irrit: Eye irritation

STOT RE: Specific target organ toxicity - repeated exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL: Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

ATEL (EC): Short Term Exposure Limit

LC50: Lethal Concentration

EC50:half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to kidneys through prolonged or repeated exposure in contact with

skin.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)