

according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1040 Multifunctional oil MP1040050AB

UFI:

QP96-N0SS-7009-C3WU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP GmbH & Co. KG	
Street:	Buergermeister-Seidl-Strasse 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600-0	Telefax: +49 (0) 8171/1600-40
E-mail:	sdb@tunap.com	
Internet:	www.tunap.com	
1.4. Emergency telephone	111 NHS (National Health Service)	
numbori		

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane nal word: Danger

Signal word: Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023	Product code: 1400233	Page 2 of 14
P251	Do not pierce or burn, even after use.	
P260	Do not breathe spray.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP F	Regulation)			
	Hydrocarbons, C9-C10,	n-alkanes, isoalkanes, cyclenes, <2%	6 aromatics	25 - < 50 %	
	927-241-2		01-2119471843-32		
	Flam. Liq. 3, STOT SE 3	, Asp. Tox. 1, Aquatic Chronic 3; H2	26 H336 H304 H412 EUH066		
75-28-5	isobutane			25 - < 50 %	
	200-857-2	601-004-00-0	01-2119485395-27		
	Flam. Gas 1, Press. Gas				
	Hydrocarbons, C6-C7, n	20 - < 25 %			
	921-024-6		01-2119475514-35		
	Flam. Liq. 2, Skin Irrit. 2, H411				
74-98-6	propane	3 - < 5 %			
	200-827-9	601-003-00-5	01-2119486944-21		
	Flam. Gas 1, Press. Gas				
106-97-8	butane	1 - < 3 %			
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Press. Gas				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc	. Limits, M-factors and ATE					
	927-241-2	927-241-2 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics					
	inhalation: LC50 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg						
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	20 - < 25 %				
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg						
106-97-8	06-97-8 203-448-7 butane						
	inhalation: LC	50 = 658 ppm (gases)					

SECTION 4: First aid measures



1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 3 of 14

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.



1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 4 of 14

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Revision No: 1,06 - Replaces version: 1,05



1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 5 of 14

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance							
DNEL type		Exposure route	Effect	Value				
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane								
Worker DNEL	, long-term	inhalation	systemic	2035 mg/m³				
Worker DNEL	, long-term	dermal	systemic	773 mg/kg bw/day				
Consumer DN	EL, long-term	inhalation	systemic	608 mg/m³				
Consumer DN	EL, long-term	dermal	systemic	699 mg/kg bw/day				
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day				

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 6 of 14

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state:	Aerosol	
	Colour:	light yellow	
	Odour:	solvent like	
			Test method
	Melting point/freezing point:	not determined	
	Boiling point or initial boiling point and	-42 °C	
	boiling range:		
	Flammability:	not applicable	
		not applicable	
	Lower explosion limits:	0,6 vol. %	
	Upper explosion limits:	9,4 vol. %	
	Flash point:	-80 °C	
	Auto-ignition temperature:	> 200 °C	
	Decomposition temperature:	not determined	DIN (49999
	pH-Value (at 20 °C):		DIN 19268
	Water solubility:	The study does not need to be conducted	
		because the substance is known to be	
	Solubility in other solvents	insoluble in water.	
	not determined		
	Partition coefficient n-octanol/water:	not determined	
	Vapour pressure:	not determined	
	Density (at 20 °C):	0,764 g/cm³	DIN 51757
	Relative vapour density:	not determined	
9.2	2. Other information		
	Information with regard to physical haza	ard classes	
	Self-ignition temperature		
	Solid:	not applicable	
	Gas:	not applicable	
	Oxidizing properties		
	Not oxidising.		
	Other safety characteristics		
	Evaporation rate:	not determined	
	Solid content:	not determined	
	Sublimation point:	not determined	
	Softening point:	not applicable	
	Pour point:	not applicable	
	Further Information		
	Data apply to technical substance: Relativ	e density, Colour, Odour, Viscosity, pH.	

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.



1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 7 of 14

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	Hydrocarbons, C9-C10, r	n-alkanes, isoa	lkanes, cy	clenes, <2% aromatics				
	dermal	LD50 > mg/kg	> 5000	Rabbit				
	inhalation (4 h) vapour	LC50 > mg/l	> 4951	Rat				
	Hydrocarbons, C6-C7, n-	alkanes, isoalk	kanes, cycl	lics, < 5% n-hexane				
	oral	LD50 > mg/kg	> 5000	Rat				
	dermal	LD50 > 3100 mg/kg	> 2800 -	Rat				
	inhalation (4 h) vapour	LC50 > mg/l	> 25,2	Rat				
106-97-8	butane							
	inhalation (4 h) gas	LC50 6	658 ppm	Rat	GESTIS			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 8 of 14

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact. Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 9 of 14

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
	Hydrocarbons, C9-C10, n	-alkanes, is	oalkanes, cy	clenes, <	2% aromatics				
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna				
75-28-5	isobutane								
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Hydrocarbons, C6-C7, n-a	alkanes, isc	alkanes, cyc	lics, < 5%	n-hexane				
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
74-98-6	propane					• •			
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023	Pr	oduct code: 1400233		Page 10 of 14
Acute crustacea toxicity	EC50 69,43 mg/l	48 h Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	OECD Guideline 301 F	98%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging



1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 11 of 14

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

and transport (ADR/RID)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
nland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
-	30 kg G
Limited quantity Passenger:	-
Limited quantity Passenger: Passenger LQ:	Y203
Passenger LQ:	F203
Passenger LQ: Excepted quantity:	
Passenger LQ:	E0



1040 Multifunctional oil MP1040050AB		
Revision date: 16.10.2023	Product code: 1400233	Page 12 of 14
IATA-max. quantity - Cargo:	150 kg	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user Warning: Flammable gases.		
14.7. Maritime transport in bulk according to	MO instruments	
not applicable		
SECTION 15: Regulatory information		
15.1 Safety health and environmental regul	ations/legislation specific for the substance or mixture	
to:n: ouloty, neutin and environmental regul		
EU regulatory information		
EU regulatory information Restrictions on use (REACH, annex XVII):	No information available.	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75 Directive 2010/75/EU on industrial		
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75 Directive 2010/75/EU on industrial emissions: Directive 2004/42/EC on VOC in paints	No information available.	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75 Directive 2010/75/EU on industrial emissions: Directive 2004/42/EC on VOC in paints and varnishes:	No information available. No information available.	
 EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75 Directive 2010/75/EU on industrial emissions: Directive 2004/42/EC on VOC in paints and varnishes: Additional information Safety Data Sheet according to Regular 	No information available. No information available.	
 EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75 Directive 2010/75/EU on industrial emissions: Directive 2004/42/EC on VOC in paints and varnishes: Additional information Safety Data Sheet according to Regular Aerosol Directive (75/324/) 	No information available. No information available.	nile

Changes

This data sheet contains changes from the previous version in section(s): 1,2,11.





according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 13 of 14

Abbreviations and acronyms

Flam. Gas: Flammable gases Aerosol: Aerosols Press. Gas (Liq.): Liquefied gas Flam. Lig: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA: International Air Transport Association IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate STEL (EC) Short Term Exposure Limit LC50: Lethal Concentration EC50: half maximal Effective Concentration ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing,



according to UK REACH Regulation

1040 Multifunctional oil MP1040050AB

Revision date: 16.10.2023

Product code: 1400233

Page 14 of 14

the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)