



Safety Data Sheet

according to UK REACH Regulation

2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2060 Scheibenklebstoff 310 ml AB

UFI:

UUMX-U0M1-N00K-2TXF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP GmbH & Co. KG	
Street:	Buergermeister-Seidl-Strasse 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600-0	Telefax: +49 (0) 8171/1600-40
E-mail:	sdb@tunap.com	
Internet:	www.tunap.com	
1.4. Emergency telephone	111 NHS (National Health Service)	

```
number:
```

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Resp. Sens. 1; H334

Full text of hazard statements: see SECTION 16.

Danger

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate

Signal word:

Pictograms:



Hazard statements

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

P260	Do not breathe vapours.
P262	Do not get in eyes, on skin, or on clothing.
P284	Wear respiratory protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Special labelling of certain mixtures

Contains isocyanates. May produce an allergic reaction.

EUH204 2.3. Other hazards

May cause sensitization by inhalation and skin contact.

SECTION 3: Composition/information on ingredients



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 2 of 10

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity				
	EC No Index No REACH No					
	Classification (GB CLP Regulation)					
101-68-8	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate					
	202-966-0 615-005-00-9 01-2119457014-47					
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	imits, M-factors and ATE	
101-68-8	202-966-0	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	0.1 - < 1 %
	> 9400 mg/kg; d	= 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 3 of 10

concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.





Safety Data Sheet

according to UK REACH Regulation

2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 4 of 10

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance		-	
DNEL type		Exposure route	Effect	Value
101-68-8	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'	-diisocyanate		
Worker DNEL, long-term		inhalation	local	0,05 mg/m³
Worker DNEL, acute		inhalation	local	0,1 mg/m³
Consumer DNEL, long-term		inhalation	local	0,025 mg/m³
Consumer DNEL, acute		inhalation	local	0,05 mg/m³

PNEC values

CAS No	Substance			
Environmental compartment Value				
101-68-8 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate				
Freshwater		0,0037 mg/l		
Freshwater (intermittent releases) 0,037				
Marine water 0,				
Freshwater sediment		11,7 mg/kg		
Marine sediment		1,17 mg/kg		
Soil		2,33 mg/kg		

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Individual protection measures, such as personal protective equipment



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 5 of 10

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min Thickness of the glove material 0,45 mm

EN ISO 374 Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. When exceeding the relevant workplace exposure limits, note the following: Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Filtering device with filter or ventilator filtering device of type: A Observe the wear time limits as specified by the manufacturer. Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and chen		
Physical state:	viskos	
Colour:	black	
Odour:	characteristic	
		Test method
Melting point/freezing point:	not determined	
Flammability:	not applicable	
	not applicable	
Flash point:	164 °C	ISO 3679
Decomposition temperature:	not determined	
pH-Value (at 20 °C):		DIN 19268
Viscosity / kinematic:		DIN EN ISO 3104
(at 40 °C)		
Water solubility:	The study does not need to be conducted	
-	because the substance is known to be	
	insoluble in water.	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	1,142 g/cm³	DIN 51757
Relative vapour density:	not determined	
9.2. Other information		
Information with regard to physical haza	rd classes	
Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	



Safety Data Sheet

according to UK REACH Regulation

2060	Scheibenklebs	stoff 310	ml AB
------	---------------	-----------	-------

Revision date: 11.10.2023

Product code: 1400436

not determined

not determined

DIN 53019-1

DIN EN ISO 2431

Page 6 of 10

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: Solid content: Viscosity / dynamic: Flow time: (at 20 °C)

SECTION 10: Stability and reactivity

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation

dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
101-68-8	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate						
	oral	LD50 mg/kg	> 2000	Rat	Study report (1990)		
	dermal	LD50 mg/kg	> 9400		Study report (1964)		
	inhalation vapour	ATE	11 mg/l				
	inhalation dust/mist	ATE	1,5 mg/l				

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 7 of 10

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate) Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact. Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
101-68-8	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate							
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Danio rerio	Study report (2020)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus	Study report (2020)	OECD Guideline 201	
	Acute crustacea toxicity	EL50	9 mg/l	48 h	Daphnia magna	Study report (2019)	EU Method C.2	
	Crustacea toxicity	NOEC mg/l	>= 10	21 d		Study report (1986)		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 8 of 10

Partition coefficient n-octanol/water

CAS No Chemical name						
101-68-8 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate						
BCF						
CAS No Chemical name BCF Species Source						
101-68-8	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	92	Cyprinus carpio	Study repor	rt (2002)	

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. This substance does not meet the criteria for classification as PBT or vPvB.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.



	according to UK REACH Regulation		
2060 Scheibenklebstoff 310 ml AB			
Revision date: 11.10.2023	Product code: 1400436 Page 9	of 10	
14.4. Packing group:	No dangerous good in sense of this transport regulation.		
Inland waterways transport (ADN)			
<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.		
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.		
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.		
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.		
Marine transport (IMDG)			
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.		
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.		
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.		
<u>14.4. Packing group:</u> Marine pollutant:	no		
Air transport (ICAO-TI/IATA-DGR)			
<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.		
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.		
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.		
14.4. Packing group:	No dangerous good in sense of this transport regulation.		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user			
No dangerous good in sense of this tr	ansport regulation.		
14.7. Maritime transport in bulk according	to IMO instruments		
No dangerous good in sense of this tr	ansport regulation.		
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
EU regulatory information			
Restrictions on use (REACH, annex XVII)	r		
Entry 56			
Directive 2010/75/EU on industrial	No information available.		
emissions:			
Directive 2004/42/EC on VOC in paints and varnishes:	No information available.		
Additional information			
Safety Data Sheet according to Regul	lation (EC) No. 1907/2006 (REACH)		
National regulatory information			
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or pursing methods.		
Water hazard class (D):	nursing mothers. 1 - slightly hazardous to water		
15.2. Chemical safety assessment			
	atanaca in this mixture were not corriad out		

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,5,6,8,11,13,14,16.



2060 Scheibenklebstoff 310 ml AB

Revision date: 11.10.2023

Product code: 1400436

Page 10 of 10

Abbreviations and acronyms

Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Irrit: Eye irritation Resp. Sens: Respiratory sensitisation Skin Sens: Skin sensitisation Carc: Carcinogenicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA: International Air Transport Association IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level WEL: Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate ATEL (EC): Short Term Exposure Limit LC50: Lethal Concentration EC50:half maximal Effective Concentration ErC50: means EC50 in terms of reduction of growth rate Relevant H and EUH statements (number and full text) H315 Causes skin irritation

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.	
H310 Causes serious eve irritation	
H332 Harmful if inhaled.	
H334 May cause allergy or asthma symptoms or breathing difficulties if inl	naled.
H335 May cause respiratory irritation.	
H351 Suspected of causing cancer.	
H373 May cause damage to organs through prolonged or repeated expos	ure.
EUH204 Contains isocyanates. May produce an allergic reaction.	

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)