

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 2 of 13

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
37859-55-5	2-Pentanon, O, O', O'' - (Methylsilylidin) -trioxim			<3,5 %
	484-460-1		01-2120004323-76	
	Acute Tox. 4, Eye Irrit. 2; H302 H319			
58190-62-8	2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime			<3,5 %
	700-810-0		01-2120006148-66	
	Acute Tox. 4, Eye Irrit. 2; H302 H319			
623-40-5	2-Pentaoxim			<2,5 %
	484-470-6		01-2119980079-27	
	Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Chronic 3; H302 H319 H373 H412			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
75-28-5	isobutane			1 - < 3 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane			0.1 - < 1 %
	273-028-6		01-2120770324-57	
	Acute Tox. 3, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H301 H315 H317 H411			
74-98-6	propane			0.1 - < 1 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
37859-55-5	484-460-1	2-Pentanon, O, O', O'' - (Methylsilylidin) -trioxim	<3,5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = ca. 1234 mg/kg		
58190-62-8	700-810-0	2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime	<3,5 %
	oral: ATE = 500 mg/kg		
623-40-5	484-470-6	2-Pentaoxim	<2,5 %
	oral: LD50 = 1133 mg/kg		
68928-76-7	273-028-6	Dimethylbis[(1-oxoneodecyl)oxy]stannane	0.1 - < 1 %
	oral: LD50 = 190 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.



Safety Data Sheet

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 3 of 13

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 4 of 13

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Take up mechanically, placing in appropriate containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
37859-55-5	2-Pentanon, O, O', O'' - (Methylsilylidin) -trioxim			
Worker DNEL, long-term		inhalation	systemic	0,229 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,065 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,057 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,033 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,033 mg/kg bw/day
623-40-5	2-Pentaoxim			
Worker DNEL, long-term		inhalation	systemic	25 mg/m ³
Worker DNEL, acute		inhalation	systemic	75 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,208 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	0,624 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	6,22 mg/m ³
Consumer DNEL, acute		inhalation	systemic	18,66 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,125 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	0,375 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,125 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,375 mg/kg bw/day

PNEC values

CAS No	Substance	Value
37859-55-5	2-Pentanon, O, O', O'' - (Methylsilylidin) -trioxim	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		0,569 mg/kg
Marine sediment		0,057 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,15 mg/l
Soil		0,044 mg/kg
623-40-5	2-Pentaoxim	
Freshwater		0,088 mg/l
Freshwater (intermittent releases)		0,88 mg/l
Marine water		0,009 mg/l
Freshwater sediment		0,5 mg/kg
Marine sediment		0,05 mg/kg
Micro-organisms in sewage treatment plants (STP)		2 mg/l
Soil		0,05 mg/kg

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 6 of 13

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.
EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min
Thickness of the glove material 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Paste
Colour: black
Odour: characteristic

Test method

Melting point/freezing point:	not determined
Flammability:	not determined not applicable
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	15 vol. %
Auto-ignition temperature:	not applicable
Decomposition temperature:	not determined
pH-Value (at 20 °C):	DIN 19268

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 7 of 13

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,0275 g/cm ³ DIN 51757
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**

Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not determined
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 8 of 13

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
37859-55-5	2-Pentanone, O, O', O''- (Methylsilylidin) -trioxim				
	oral	LD50 ca. 1234 mg/kg	Rat	Study report (2008)	OECD Guideline 425
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1995)	EU Method B.3
58190-62-8	2-Pentanone, O, O', O''-(ethenylsilyldyne)trioxime				
	oral	ATE 500 mg/kg			
623-40-5	2-Pentaoxim				
	oral	LD50 1133 mg/kg	Rat	Study report (2008)	OECD Guideline 425
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane				
	oral	LD50 190 mg/kg	Rat	Study report (1979)	OECD Guideline 401

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 9 of 13

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Aquatic toxicity: The classification criteria for this hazard class are not met by definition.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
37859-55-5	2-Pentanon, O, O', O' '- (Methylsilylidin) -trioxim					
	Acute fish toxicity	LC50 > 113 mg/l	96 h		REACH Registration Dossier	
	Acute algae toxicity	ErC50 100 mg/l	72 h		REACH Registration Dossier	
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
623-40-5	2-Pentaoxim					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 ca. 54 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 100 mg/l				
	Algae toxicity	NOEC 36 mg/l				
	Crustacea toxicity	NOEC 100 mg/l				
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane					
	Acute algae toxicity	ErC50 7,6 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 39 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
37859-55-5	2-Pentanon, O, O', O' '- (Methylsilylidin) -trioxim	ca. 1,25
623-40-5	2-Pentaoxim	1,43
106-97-8	butane	2,89
75-28-5	isobutane	2,8
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane	5,503
74-98-6	propane	2,36

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 10 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
37859-55-5	2-Pentanon, O, O', O''-(Methylsilylidin)-trioxim	3,103		REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

No special environmental measures are necessary.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 11 of 13

14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Additional informationSafety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol Directive (75/324/EEC)

**Safety Data Sheet**

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 12 of 13

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Acute Tox: Acute toxicity

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be



Safety Data Sheet

according to UK REACH Regulation

159 Silicone Sealant MP15900200AB

Revision date: 25.03.2025

Product code: 1400454

Page 13 of 13

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)