



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

937 Injektor Intensiv-Reiniger Benzin MF93700500AB

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Cleaner

**1.3. Details of the supplier of the safety data sheet**

Company name:	TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

**1.4. Emergency telephone number:** +49 (0) 30 30 686 790 (Giftnotruf Berlin)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Indications of danger: F+ - Extremely flammable, Xn - Harmful, Xi - Irritant

R phrases:

Extremely flammable.

Harmful by inhalation and in contact with skin.

Irritating to respiratory system and skin.

Risk of serious damage to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:

Aerosol: Aerosol 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye damage.

Harmful if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

**2.2. Label elements**



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 2 of 14

**Hazard components for labelling**

Solvent naphtha (petroleum), aromatic, light  
xylene  
n-propanol  
morpholine

Signal word:

Danger

Pictograms:

GHS02-GHS05-GHS08

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P260	Do not breathe Aerosol.
P280	Wear Eye/face protection.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**



## 937 Injektor Intensiv-Reiniger Benzin MF93700500AB

Print date: 22.06.2016

Product code: 1100470

Page 3 of 14

## Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
215-535-7	xylene	25 - < 50 %
1330-20-7	Xn - Harmful, Xi - Irritant R10-20/21-36/37/38-48/20-65	
601-022-00-9	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304	
200-746-9	n-propanol	10 - < 20 %
71-23-8	F - Highly flammable, Xi - Irritant R11-41-67	
603-003-00-0	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336	
01-2119486761-29		
918-668-5	Solvent naphtha (petroleum), aromatic, light	10 - < 20 %
64742-95-6	Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R10-37-51-53-65-66-67	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066	
01-2119455851-35		
202-849-4	ethylbenzene	10 - < 20 %
100-41-4	F - Highly flammable, Xn - Harmful R11-20-48/20-65	
601-023-00-4	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304	
203-815-1	morpholine	3 - < 5 %
110-91-8	C - Corrosive, Xn - Harmful R10-20/21/22-34	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H226 H311 H331 H302 H314 H318	
01-2119496057-30		
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich	1 - < 3 %
	Xi - Irritant, N - Dangerous for the environment R36/38-51-53	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411	
203-625-9	toluene	0.1 - < 1 %
108-88-3	Repr. Cat. 3, F - Highly flammable, Xn - Harmful, Xi - Irritant R11-63-48/20-65-38-67	
601-021-00-3	Flam. Liq. 2, Repr. 2, Asp. Tox. 1, STOT RE 2, Skin Irrit. 2, STOT SE 3; H225 H361d *** H304 H373 ** H315 H336	

Full text of R, H and EUH phrases: see section 16.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

## After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

## After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 4 of 14

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from sources of ignition. - No smoking. Vapours can form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on storage compatibility**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 5 of 14

**Further information on storage conditions**

Protect from frost. Protect against direct sunlight.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
110-91-8	Morpholine	10	36		TWA (8 h)	WEL
		20	72		STEL (15 min)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**Additional advice on limit values**

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

TWA (EC): time-weighted average

U: Urea

B: Blood

**8.2. Exposure controls**
**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Protective and hygiene measures**

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 6 of 14

function of the specific working place concentration and quantity of hazardous substances.  
 Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min  
 Thickness of the glove material 0,45 mm  
 DIN EN 374

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
 Suitable respiratory protection apparatus: Combination filtering device (EN 14387)  
 Filtering device with filter or ventilator filtering device of type: A  
 Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
 Colour: light yellow  
 Odour: solvent like

**Test method**

pH-Value (at 20 °C): not determined DIN 19268

**Changes in the physical state**

Melting point: not determined  
 Initial boiling point and boiling range: 120 °C  
 Sublimation point: No information available.  
 Softening point: No information available.  
 Flash point: 15 °C

**Flammability**

Solid: not applicable  
 Gas: not applicable

Lower explosion limits: 0,2 vol. %

Upper explosion limits: 13,5 vol. %

Ignition temperature: No information available.

**Auto-ignition temperature**

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidizing.

Vapour pressure: not determined

Vapour pressure: No information available.

Density (at 20 °C): 0,87 g/cm<sup>3</sup> DIN 51757

Bulk density: No information available.

Water solubility: insoluble

**Solubility in other solvents**

not determined

Partition coefficient: not determined



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 7 of 14

Viscosity / dynamic:	No information available.
Viscosity / kinematic:	< 7 mm <sup>2</sup> /s
Flow time:	No information available.
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	No information available.
Solvent content:	No information available.

**9.2. Other information**

Solid content: not determined

Density Data apply to the technically active substance.  
pressure - bar (20°C)

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable, Ignition hazard.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Harmful if inhaled.

**ATEmix calculated**

ATE (inhalative vapour) 18,47 mg/l; ATE (inhalative aerosol) 2,097 mg/l



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 8 of 14

**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
1330-20-7	xylene				
	oral	LD50	4300 mg/kg	Rat	
	dermal	LD50	1700 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	21,7 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
71-23-8	n-propanol				
	oral	LD50	8000 mg/kg	Rat	
	dermal	LD50	4032 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	> 33,8 mg/l	Rat	
64742-95-6	Solvent naphtha (petroleum), aromatic, light				
	oral	LD50	3592 mg/kg	Rat	
	dermal	LD50	> 3160 mg/kg	Rabbit	
100-41-4	ethylbenzene				
	oral	LD50	3500 mg/kg	Rat	GESTIS
	dermal	LD50	15400 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	17,2 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
110-91-8	morpholine				
	oral	LD50	1900 mg/kg	Rat	
	dermal	LD50	500 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	8 mg/l	Rat	
	inhalative aerosol	ATE	0,5 mg/l		
	inhalative (4 h) gas	LC50	8000 ppm	Rat	
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich				
	oral	LD50	> 5000 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rabbit	
108-88-3	toluene				
	dermal	LD50	12200 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	49 mg/l	Rat	GESTIS

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**STOT-single exposure**





according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 9 of 14

May cause respiratory irritation. (xylene), (Solvent naphtha (petroleum), aromatic, light)  
May cause drowsiness or dizziness. (n-propanol), (Solvent naphtha (petroleum), aromatic, light),  
(toluene)

**Severe effects after repeated or prolonged exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene), (ethylbenzene),  
(toluene)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.  
No indication of human carcinogenicity.  
No indications of human germ cell mutagenicity exist.  
No indications of human reproductive toxicity exist.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

This mixture is classified as hazardous according to 1999/45/EC.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
1330-20-7	xylene					
	Acute fish toxicity	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	> 100 mg/l		Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	1,8 - 2,9 mg/l	48 h	Daphnia magna	
71-23-8	n-propanol					
	Acute fish toxicity	LC50	4480 mg/l	96 h	Pimephales promelas	
64742-95-6	Solvent naphtha (petroleum), aromatic, light					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	2,6-2,9 mg/l	96 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna	
100-41-4	ethylbenzene					
	Acute algae toxicity	ErC50	3,6 mg/l	96 h		GESTIS
110-91-8	morpholine					
	Acute fish toxicity	LC50	179 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	58 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	45 mg/l	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC	10 mg/l	4 d	Desmodesmus subspicatus.	
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich					
	Acute fish toxicity	LC50	>1 - 10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	>1 mg/l	48 h	Daphnia magna	
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID
	Acute algae toxicity	ErC50	12,5 mg/l	72 h		GESTIS

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
110-91-8	morpholine			
	OECD 301E	93%	25	
	Easily biodegradable (concerning to the criteria of the OECD)			

**12.3. Bioaccumulative potential**

The product has not been tested.



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 11 of 14

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
71-23-8	n-propanol	0,29
100-41-4	ethylbenzene	3,15
110-91-8	morpholine	-2,55
108-88-3	toluene	2,73

**BCF**

CAS No	Chemical name	BCF	Species	Source
110-91-8	morpholine	< 2,8		

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances  
Classified as hazardous waste.

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 12 of 14

Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2, see SP63
Marine pollutant:	No
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	See SP277
EmS:	F-D, S-U

**Air transport (ICAO)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 13 of 14

1999/13/EC (VOC): No information available.

**Additional information**

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC , 2008/47/EC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

**Additional information**

94/69/EC (21st ATP). The benzene content of the product is less than 0.1%. It applies the annotation P. Classification and labeling as carcinogenic is not necessary.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant R phrases (number and full text)**

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20 Harmful by inhalation.
- 20/21 Harmful by inhalation and in contact with skin.
- 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- 34 Causes burns.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 36/38 Irritating to eyes and skin.
- 37 Irritating to respiratory system.
- 37/38 Irritating to respiratory system and skin.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 51 Toxic to aquatic organisms.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

**Relevant H and EUH statements (number and full text)**

- H222 Extremely flammable aerosol.



according to Regulation (EC) No 1907/2006

**937 Injektor Intensiv-Reiniger Benzin MF93700500AB**

Print date: 22.06.2016

Product code: 1100470

Page 14 of 14

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*