



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

974 Injektor Direkt-Schutz Benzin MF97400200Y3

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Additive

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

1.4. Emergency telephone number: +49 (0) 30 30 686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Indications of danger: F - Highly flammable, Xi - Irritant, N - Dangerous for the environment

R phrases:

Highly flammable.

Irritating to eyes.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Hazard components for labelling**

2-Propanol

Signal word:

Danger

Pictograms:

GHS02-GHS07

**Hazard statements**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 2 of 12

H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapour.
 P280 Wear eye/face protection..
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P314 Get medical advice/attention if you feel unwell.
 P273 Avoid release to the environment.
 P271 Use only outdoors or in a well-ventilated area.
 P501 Dispose of contents / container in accordance with local regulations

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
200-661-7	2-Propanol	50 - < 100 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
01-2119457558-25		
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich	5 - < 10 %
	Xi - Irritant, N - Dangerous for the environment R36/38-51-53	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411	
204-881-4	2,6-di-tert-butyl-p-cresol	1 - < 3 %
128-37-0	N - Dangerous for the environment R50-53	
	Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H400 H410	
01-2119565113-46		
203-749-3	N-Oleoyl-Sarcosid	0.1 - < 1 %
110-25-8	Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R20-38-41-50	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 1); H332 H315 H318 H400	
01-2119488991-20		
202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	0.1 - < 1 %
95-38-5	C - Corrosive, Xn - Harmful, N - Dangerous for the environment R22-34-48/22-50-53	
	Acute Tox. 4, Skin Corr. 1C, STOT RE 2, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 10); H302 H314 H373 H400 H410	
01-2119777867-13		

Full text of R, H and EUH phrases: see section 16.



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 3 of 12

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness, Headache, Irritation to eyes, Nausea

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 4 of 12

7.1. Precautions for safe handling**Advice on safe handling**

Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Vapours can form explosive mixtures with air.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

No information available.

7.3. Specific end use(s)

No information available. 9

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Additional advice on limit values

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

TWA (EC): time-weighted average

U: Urea

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 5 of 12

function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of inadequate ventilation wear respiratory protection. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	blue
Odour:	amine-like

	Test method
pH-Value (at 20 °C):	not determined DIN 19268

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	78 °C
--	-------

Sublimation point:	No information available.
--------------------	---------------------------

Softening point:	No information available.
------------------	---------------------------

:	No information available.
---	---------------------------

Flash point:	13 °C ISO 3679
--------------	----------------

Flammability

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Lower explosion limits:	2 vol. %
-------------------------	----------

Upper explosion limits:	12 vol. %
-------------------------	-----------

Ignition temperature:	No information available.
-----------------------	---------------------------

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

Not oxidizing.

Vapour pressure:	not determined
------------------	----------------

Density (at 20 °C):	0,799 g/cm ³
---------------------	-------------------------

Bulk density:	No information available.
---------------	---------------------------

Water solubility:	insoluble
-------------------	-----------

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 6 of 12

Viscosity / dynamic:	No information available.	DIN 53019-1
Viscosity / kinematic: (at 40 °C)	< 7 mm ² /s	DIN EN ISO 3104
Flow time: (at 20 °C)	No information available.	DIN EN ISO 2431
Vapour density:	not determined	
Evaporation rate:	not determined	
Solvent separation test:	No information available.	
Solvent content:	No information available.	

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 7 of 12

Acute toxicity

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
67-63-0	2-Propanol				
	oral	LD50	5280 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	47,5 mg/l	Rat	
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich				
	oral	LD50	> 5000 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rabbit	
128-37-0	2,6-di-tert-butyl-p-cresol				
	oral	LD50	2930 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rat	
110-25-8	N-Oleoyl-Sarcosid				
	oral	LD50	9200 mg/kg	Rat	
	inhalative vapour	ATE	11 mg/l		
	inhalative (4 h) aerosol	LC50	1,37 mg/l	Rat	
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
	oral	LD50	1265 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rabbit	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (2-Propanol)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 8 of 12

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
67-63-0	2-Propanol					
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	> 100 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h	Daphnia magna	
	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich					
	Acute fish toxicity	LC50	>1 - 10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	>1 mg/l	48 h	Daphnia magna	
128-37-0	2,6-di-tert-butyl-p-cresol					
	Acute fish toxicity	LC50	0,42 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	0,42 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	0,57 mg/l	48 h	Daphnia magna	
110-25-8	N-Oleoyl-Sarcosid					
	Acute fish toxicity	LC50	3,2-4,6 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50	5,1 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	0,53 mg/l	48 h	Daphnia magna	
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol					
	Acute fish toxicity	LC50	0,3 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	0,2989 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	0,136 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	2-Propanol	0,05
110-25-8	N-Oleoyl-Sarcosid	6,83

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.


974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 9 of 12

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Waste disposal number of used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Other applicable information (land transport)

Limited quantity: E2

Inland waterways transport (ADN)

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 10 of 12

Other applicable information (inland waterways transport)

Limited quantity: E2

Marine transport (IMDG)

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine pollutant:	Yes
Special Provisions:	-
Limited quantity:	1 L
EmS:	F-E, S-D

Other applicable information (marine transport)

Limited quantity: E2

Air transport (ICAO)

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A180
Limited quantity Passenger:	1 L
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

Other applicable information (air transport)

Limited quantity: E2

Passenger-LQ: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C 11-14-isoalkyl ethers, C13-rich

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

1999/13/EC (VOC): EU/CH: 90,998

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 11 of 12

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

Additional information

94/69/EC (21st ATP). The benzene content of the product is less than 0.1%. It applies the annotation P. Classification and labeling as carcinogenic is not necessary.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant R phrases (number and full text)

11	Highly flammable.
20	Harmful by inhalation.
22	Harmful if swallowed.
34	Causes burns.
36	Irritating to eyes.
36/38	Irritating to eyes and skin.
38	Irritating to skin.
41	Risk of serious damage to eyes.
48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
67	Vapours may cause drowsiness and dizziness.

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of

Safety Data Sheet



according to Regulation (EC) No 1907/2006

974 Injektor Direkt-Schutz Benzin MF97400200Y3

Print date: 22.06.2016

Product code: MF97400200Y3

Page 12 of 12

the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)