

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

102 Active oil MP10200400AB

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant

1.3. Details of the supplier of the safety data sheet

Company name:	TUNAP GmbH & Co. KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

1.4. Emergency telephone number: +49 (0) 30 30 686 790 (Giftnotruf Berlin)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane

2-Propanol

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 2 of 15

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P260 Do not breathe spray.
P280 Wear protective gloves.
P273 Avoid release to the environment.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P251 Do not pierce or burn, even after use.

Special labelling of certain mixtures

EUH208 Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane			10 - < 20 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-63-0	2-Propanol			3 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics			3 - < 5 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
110-54-3	n-hexane			0.1 - < 1 %
	203-777-6	601-037-00-0	01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			
61791-55-7	N-Tallowalkyl-1,3-propanediamine			0.1 - < 1 %
	263-189-0		01-2119487014-41	
	Acute Tox. 4, Skin Corr. 1B, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1 (M-Factor = 10); H302 H314 H372 H400 H410			
3115-49-9	4-Nonylphenoxyacetic acid			0.1 - < 1 %
	221-486-2			
	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H317 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 4 of 15

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse.
In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**


102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 5 of 15

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 6 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane			
Worker DNEL, long-term		inhalation	systemic	5306 mg/m ³
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1131 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1301 mg/kg bw/day
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)
Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min
Thickness of the glove material 0,45 mm
DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 7 of 15

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
 Filtering device with filter or ventilator filtering device of type: AX
 Observe the wear time limits as specified by the manufacturer.
 Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: yellow-brown
 Odour: solvent like

pH-Value (at 20 °C):

Test method
 DIN 19268

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: 51 °C
 Sublimation point: No information available.
 Softening point: No information available.
 Pour point: No information available.
 Flash point: -21 °C

Flammability

Solid: not applicable
 Gas: not applicable
 Lower explosion limits: 1 vol. %
 Upper explosion limits: 15 vol. %
 Ignition temperature: 250 °C

Auto-ignition temperature

Solid: not applicable
 Gas: not applicable
 Decomposition temperature: not determined

Oxidizing properties

Not oxidising.
 Vapour pressure: not determined

Density (at 20 °C): 0,76 g/cm³ DIN 51757

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined
 Partition coefficient: not determined
 Vapour density: not determined
 Evaporation rate: not determined

9.2. Other information

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 8 of 15

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 9 of 15

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
75-28-5	isobutane			
	inhalation vapour	LC50 1237 mg/l	Mouse.	
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane			
	oral	LD50 >5840 mg/kg	Rat	
	dermal	LD50 >2920 mg/kg	Rat	
	inhalation (4 h) vapour	LC50 73860 mg/l	Rat	Industrial Medicine, Vol. 39, No. 5, May
67-63-0	2-Propanol			
	oral	LD50 5280 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rabbit	
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat	
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics			
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1993)
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat	
106-97-8	butane			
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS
110-54-3	n-hexane			
	oral	LD50 > 2000 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rabbit	
	inhalation (4 h) vapour	LC50 > 31,86 mg/l	Rat	
61791-55-7	N-Tallowalkyl-1,3-propanediamine			
	oral	LD50 >300 - 2000 mg/kg	Rat	
3115-49-9	4-Nonylphenoxyacetic acid			
	oral	LD50 1674 mg/kg	Rat	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 10 of 15

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 11 of 15

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
75-28-5	isobutane				
	Acute fish toxicity	LC50 91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane				
	Acute fish toxicity	LC50 >10 -100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 13,56 mg/l	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)
	Acute crustacea toxicity	EC50 31,9 mg/l	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)
	Fish toxicity	NOEC 4,089 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)
	Crustacea toxicity	NOEC 7,138 mg/l	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)
74-98-6	propane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
67-63-0	2-Propanol				
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics				
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna	
	Fish toxicity	NOEC 0,182 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
	Crustacea toxicity	NOEC 0,317 mg/l	21 d	Daphnia magna	Company report (2010)
106-97-8	butane				
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A



102 Active oil MP10200400AB

Print date: 28.06.2019

Product code: 1103569

Page 12 of 15

	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200)
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200)
61791-55-7	N-Tallowalkyl-1,3-propanediamine					
	Acute fish toxicity	LC50	>0,02 - 0,1 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	>0,02 - 0,1 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	>0,02 - 0,1 mg/l	48 h	Daphnia magna (Big water flea)	
3115-49-9	4-Nonylphenoxyacetic acid					
	Acute fish toxicity	LC50	9 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute crustacea toxicity	EC50	0,88 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
3115-49-9	4-Nonylphenoxyacetic acid			
	OECD 301B; ISO 9439; 92/69/EWG, C.4-C	42 - 46 %	28	
	Moderately/partially biodegradable.			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane	3,6
74-98-6	propane	1,09
67-63-0	2-Propanol	0,05
106-97-8	butane	1,09
110-54-3	n-hexane	3,9

BCF

CAS No	Chemical name	BCF	Species	Source
64742-49-0	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane	501,187	Pimephales promelas	QSAR in Environmenta
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics	144,3	calculated	Other company data (

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 13 of 15

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS (Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane)
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 14 of 15

Hazard label:	2.1
Marine pollutant:	yes
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Hydrocarbons, C6, iso-alkanes, < 5 % n-hexane; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; butane

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional informationSafety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol directive (75/324/EEC)**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 14,16.

**102 Active oil MP10200400AB**

Print date: 28.06.2019

Product code: 1103569

Page 15 of 15

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IATA: International Air Transport Association
 IMDG: International Maritime Code for Dangerous Goods
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level
 WEL (UK): Workplace Exposure Limits
 TWA (EC): Time-Weighted Average
 ATE: Acute Toxicity Estimate
 STEL (EC) Short Term Exposure Limit
 LC50: Lethal Concentration
 EC50: half maximal Effective Concentration
 ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
 Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)