



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

138 Intake System Cleaner Premium MP13800400AB

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Cleaner

**1.3. Details of the supplier of the safety data sheet**

Company name:	TUNAP Deutschland Vertriebs GmbH & Co. Betriebs KG	
Street:	Bürgermeister-Seidl-Str. 2	
Place:	D-82515 Wolfratshausen	
Telephone:	+49 (0) 8171/1600 - 0	Telefax: +49 (0) 8171/1600 - 40
e-mail:	sdb@tunap.com	
Internet:	www.tunap.com	

**1.4. Emergency telephone number:** +49 (0) 30 30 686 790 (Giftnotruf Berlin)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

**2.2. Label elements**

**Regulation (EC) No. 1272/2008**

**Hazard components for labelling**

Acetone

4-hydroxy-4-methylpentan-2-one, diacetone alcohol

xylene

ethylbenzene

**Signal word:** Danger



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 2 of 12

**Pictograms:**



**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P260	Do not breathe Aerosol.
P280	Wear eye/face protection.
P262	Do not get in eyes, on skin, or on clothing.
P302+P352	IF ON SKIN: Wash with plenty of Water and soap..
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P251	Do not pierce or burn, even after use.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 3 of 12

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	Acetone			25 - < 50 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol			25 - < 50 %
	204-626-7		01-2119473975-21	
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3; H226 H319 H335			
1330-20-7	xylene			25 - < 50 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304			
124-38-9	carbon dioxide			5 - < 10 %
	204-696-9			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
108-88-3	toluene			0.1 - < 1 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Asp. Tox. 1, STOT RE 2, Skin Irrit. 2, STOT SE 3; H225 H361d *** H304 H373 ** H315 H336			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 4 of 12

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition. - No smoking. Vapours may form explosive mixtures with air.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 5 of 12

**Advice on storage compatibility**

Do not store together with: Material, rich in oxygen, oxidizing.

**Further information on storage conditions**

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**Additional advice on limit values**

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

STEL (EC) : Short Term Exposure Limit

TWA (EC): time-weighted average

U: Urea

B: Blood

**8.2. Exposure controls**

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 6 of 12

**Protective and hygiene measures**

Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
DIN EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min  
Thickness of the glove material 0,45 mm  
DIN EN 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
When exceeding the relevant workplace exposure limits, note the following:  
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
Filtering device with filter or ventilator filtering device of type: A  
Observe the wear time limits as specified by the manufacturer.  
Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	solvent like

pH-Value (at 20 °C):	No information available.
----------------------	---------------------------

**Changes in the physical state**

Melting point:	No information available.
----------------	---------------------------

Initial boiling point and boiling range:	56 °C
--	-------

Flash point:	-19 °C
--------------	--------

Lower explosion limits:	0,9 vol. %
-------------------------	------------

Upper explosion limits:	14,3 vol. %
-------------------------	-------------

Vapour pressure:	No information available.
------------------	---------------------------

Vapour pressure:	No information available.
------------------	---------------------------

Density (at 20 °C):	0,86 g/cm <sup>3</sup> DIN 51757
---------------------	----------------------------------

Bulk density:	not applicable
---------------	----------------

Partition coefficient:	No information available.
------------------------	---------------------------

Viscosity / dynamic:	No information available.
----------------------	---------------------------

Viscosity / kinematic:	No information available.
------------------------	---------------------------

Flow time:	not applicable
------------	----------------

**Test method**



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 7 of 12

Vapour density:

No information available.

**9.2. Other information**

Data apply to technical substance: Density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**10.6. Hazardous decomposition products**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Harmful if inhaled.

Acute toxicity, oral. Acute toxicity, inhalant.

**ATEmix calculated**

ATE (inhalative aerosol) 4,527 mg/l



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 8 of 12

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
67-64-1	Acetone			
	oral	LD50 5800 mg/kg	Rat	RTECS
	dermal	LD50 20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50 76 mg/l	Rat	
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol			
	oral	LD50 3002 mg/kg	Rat	
	dermal	LD50 13630 mg/kg	Rabbit	
1330-20-7	xylene			
	oral	LD50 4300 mg/kg	Rat	
	dermal	LD50 1700 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 21,7 mg/l	Rat	
	inhalative aerosol	ATE 1,5 mg/l		
100-41-4	ethylbenzene			
	oral	LD50 3500 mg/kg	Rat	GESTIS
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50 17,2 mg/l	Rat	
	inhalative aerosol	ATE 1,5 mg/l		
108-88-3	toluene			
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50 49 mg/l	Rat	GESTIS

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.  
Irritating to eyes. Following inhalation: Lung irritation. Coughing. shortage of breath. After skin contact: Irritant.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.  
No indication of human carcinogenicity.  
No indications of human germ cell mutagenicity exist.  
No indications of human reproductive toxicity exist.

**STOT-single exposure**

May cause respiratory irritation. ( (4-hydroxy-4-methylpentan-2-one, diacetone alcohol); (xylene))  
May cause drowsiness or dizziness. ( (Acetone))

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. ( (xylene))

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**SECTION 12: Ecological information**

**12.1. Toxicity**





**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 9 of 12

There are no data available on the mixture itself.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
67-64-1	Acetone				
	Acute fish toxicity	LC50 5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 6100 mg/l	48 h	Daphnia magna	
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol				
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	
	Algae toxicity	NOEC 1000 mg/l	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC 100 mg/l	21 d	Daphnia magna	
1330-20-7	xylene				
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Onchorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 > 100 mg/l		Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 1,8 - 2,9 mg/l	48 h	Daphnia magna	
100-41-4	ethylbenzene				
	Acute algae toxicity	ErC50 3,6 mg/l	96 h		GESTIS
108-88-3	toluene				
	Acute fish toxicity	LC50 13 mg/l	96 h	Carassius auratus	IUCLID
	Acute algae toxicity	ErC50 12,5 mg/l	72 h		GESTIS

**12.2. Persistence and degradability**

There are no data available on the mixture itself. AOX (mg/l): 0

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol			
	OECD 301 A	98,51%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	Acetone	-0,24
123-42-2	4-hydroxy-4-methylpentan-2-one, diacetone alcohol	1,03
100-41-4	ethylbenzene	3,15
108-88-3	toluene	2,73

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 10 of 12

**12.6. Other adverse effects**

No information available.

**Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances  
Classified as hazardous waste.

**Contaminated packaging**

Water (with cleaning agent). Completely emptied packages can be recycled.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 11 of 12

Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: No  
Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 48: toluene

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]:

Calculation method.

Aerosol directive (75/324/EEC)



**138 Intake System Cleaner Premium MP13800400AB**

Print date: 10.05.2017

Product code: 11AFX138040AB

Page 12 of 12

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,11.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

**Relevant H and EUH statements (number and full text)**

- |        |  |
|--------|--|
| H222   | Extremely flammable aerosol.                                       |
| H225   | Highly flammable liquid and vapour.                                |
| H226   | Flammable liquid and vapour.                                       |
| H229   | Pressurised container: May burst if heated.                        |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.  |
| H319   | Causes serious eye irritation.                                     |
| H332   | Harmful if inhaled.  |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H361d  | Suspected of damaging the unborn child.                            |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*