

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

903 Releaser Active MP90300400AB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

rust remover

1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Bürgermeister-Seidl-Str. 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600 - 0 Telefax: +49 (0) 8171/1600 - 40

e-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone +49 (0) 30 30 686 790 (Giftnotruf Berlin)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P260 Do not breathe Aerosol.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P302+P352 IF ON SKIN: Wash with plenty of Water and soap..

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P251 Do not pierce or burn, even after use.



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 2 of 13

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•	•		
90622-57-4	Hydrocarbons, C11-C12, isoalkane	s, <2% aromatics		25 - < 50 %	
	918-167-1		01-2119472146-39		
	Flam. Liq. 3, Asp. Tox. 1; H226 H30	04 EUH066	•		
75-28-5	isobutane			25 - < 50 %	
	200-857-2	601-004-00-0	01-2119485395-27		
	Flam. Gas 1, Liquefied gas; H220 I	H280			
74-98-6	propane			5 - < 10 %	
	200-827-9	601-003-00-5	01-2119486944-21		
	Flam. Gas 1, Liquefied gas; H220 H				
106-97-8	butane	1 - < 3 %			
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Liquefied gas; H220 H				
110-25-8	N-methyl-N-[C18-(unsaturated)alka	0.1 - < 1 %			
	701-177-3		01-2119488991-20		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam	. 1, Aquatic Acute 1; H332	H315 H318 H400		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-	0.1 - < 1 %			
	202-414-9		01-2119777867-13		
	Acute Tox. 4, Skin Corr. 1C, STOT RE 2, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 1); H302 H314 H373 H400 H410				

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, < 5 % phosphates.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 3 of 13

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.



according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 4 of 13

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Observe legal regulations and provisions.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine				
Worker DNEL	long-term	inhalation	systemic	0,8 mg/m³	
Worker DNEL	long-term	dermal	systemic	20 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	0,4 mg/m³	
Consumer DNEL, long-term		dermal	systemic	10 mg/kg bw/day	
Consumer DN	EL, long-term	oral	systemic	10 mg/kg bw/day	
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
Worker DNEL	long-term	inhalation	systemic	0,46 mg/m³	
Worker DNEL, acute		inhalation	systemic	14 mg/m³	
Worker DNEL, long-term		dermal	systemic	0,06 mg/kg bw/day	
Worker DNEL	acute	dermal	systemic	2 mg/kg bw/day	



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 5 of 13

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	
Freshwater		0,00043 mg/l
Freshwater	(intermittent releases)	0,0043 mg/l
Marine water	r	0,000043 mg/l
Freshwater	sediment	0,007 mg/kg
Marine sedi	ment	0,001 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		1,71 mg/kg
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	
Freshwater		0 mg/l
Freshwater	(intermittent releases)	0 mg/l
Marine water		0 mg/l
Freshwater sediment		0,376 mg/kg
Marine sediment		0,038 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,27 mg/l
Soil		0,075 mg/kg

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 6 of 13

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: yellow
Odour: solvent like

Test method

Revision date: 11.09.2018

pH-Value (at 20 °C): DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

-42 °C

Flash point:

-80 °C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 0,5
Upper explosion limits: 9,4

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,772 g/cm³ DIN 51757

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient:

Viscosity / kinematic:

Vapour density:

Evaporation rate:

not determined

not determined

not determined

9.2. Other information



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 7 of 13

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
90622-57-4	Hydrocarbons, C11-C12, isoalkane	es, <2% aron	natics		
	oral	LD50 mg/kg	> 15000	Rat	Study report (1977)
	dermal	LD50	> 5000 mg/kg	Rabbit	Study report (1993)
	inhalation (4 h) vapour	LC50	>25 mg/l	Rat	
75-28-5	isobutane				
	inhalation vapour	LC50	1237 mg/l	Mouse.	
106-97-8	butane				
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine				
	oral	LD50	> 5000 mg/kg	Rat	Study report (1981)
	inhalation vapour	ATE	11 mg/l		
	inhalation (4 h) aerosol	LC50	1,37 mg/l	Rat	
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-	1-yl)ethanol			
	oral	LD50 mg/kg	ca. 1085	Rat	Study report (1989)
	dermal	LD50	>2000 mg/kg	Rabbit	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source
0622-57-4	Hydrocarbons, C11-C12, isoa	alkanes, <2%	aromatics			
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report; company data (1995)
	Fish toxicity	NOEC	0,209 mg/l	28 d	Oncorhynchus mykiss	Company report (2010)
	Crustacea toxicity	NOEC	> 1 mg/l	21 d	Daphnia magna	Study report; company data (2012)
5-28-5	isobutane					
	Acute fish toxicity	LC50	91,42 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200
4-98-6	propane					
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200
06-97-8	butane					
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200
10-25-8	N-methyl-N-[C18-(unsaturate	ed)alkanoyl]gly	cine			
	Acute fish toxicity	LC50	> 0,43 mg/l	96 h	Leuciscus idus	REACh Registration Dossier
	Acute algae toxicity	ErC50	5,1 mg/l	72 h	Desmodesmus subspicatus	REACh Registration Dossier
	Acute crustacea toxicity	EC50	0,53 mg/l	48 h	Daphnia magna	REACh Registration Dossier
	Acute bacteria toxicity	(1300 m		3 h	Activated sludge	REACh Registration Dossier
5-38-5	2-(2-heptadec-8-enyl-2-imida	zolin-1-yl)etha			_	_
	Acute fish toxicity	LC50	0,3 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	0,03 mg/l	72 h	Desmodesmus subspicatus	Study report (2010)



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

	903 Re	leaser Active	MP90300400AB		
Print date: 28.06.2019		Product code: 1	1101545	Page 10 of	13
Acute crustacea toxicity	EC50	0.163 mg/l	48 h Daphnia magna	Study report (2010)	ſ

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoy/]glycine	>= 3,5
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	8,4

BCF

CAS No	Chemical name	BCF	Species	Source
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	144,3	calculated	Other company data (
110-25-8	N-methyl-N-[C18- (unsaturated)alkanoyl]glycine	1,98	fish	BCFBAF version 3.01
95-38-5	2- (2-heptadec-8-enyl-2-imidazolin-1-yl)et hanol	371,8		EPIWIN calculation (

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 11 of 13

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2, see SP63

Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger: 203



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Release	r Active	MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 12 of 13

IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user
Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Additional information

Aerosol directive (75/324/EEC). National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.



Revision date: 11.09.2018

according to Regulation (EC) No 1907/2006

903 Releaser Active MP90300400AB

Print date: 28.06.2019 Product code: 1101545 Page 13 of 13

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)