

TUNFLUID HTFG 260

Synthetic high-temperature oil for chain lubrication

Benefits

- ✓ Extremely economical consumption due to high degree of thermal stability and extremely low boil-off
- ✓ Very clean to use, as no residues are formed even at high operating temperatures
- ✓ Excellent wear protection for reliable chain operation

Properties

- ✓ Resistant to even extremely high temperatures
- ✓ Particularly resistant to high-energy UV radiation
- ✓ Excellent creeping properties
- ✓ Ideal for medium to high speeds
- ✓ NSF H1-registered
- ✓ ISO 21469, Kosher- and Halal-certified

Application area

- ✓ Drive, control and conveyor chains in high-temperature applications, e.g.:
- ✓ In baking lines and ovens
- ✓ Surface treatment, drying or coating of various industrial goods or packaging materials that follow the strictest hygiene standards.

Instructions

Observe the machine manufacturer's specifications. Can be applied using a drip oiler, brush or automatic central lubrication system.

If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is used as a corrosion-protection film for surfaces in contact with food, it must be completely removed before the equipment in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNFLUID HTFG 260	20 l	19.4 kg	20.28 kg	1100278	1 PCS





Technical Product Data	TUNFLUID HTFG 260
Density/conditions	0,97 g/cm ³ / bei 20°C
Colour spectrum	Yellowish
Oil basis	Ester
Kinematic viscosity / condition	260 mm ² /s / at 40°C
Rating copper corrosion/conditions	1-100 / after 24h at 100°C, nach DIN 51811
Min. flashing point /conditions	> 280°C / nach ISO 2592
Pour point	-18 °C
Min./max. temperature conditions	-10 to 250 °C