

## TUNGREASE H1/EP-000

Fully synthetic H1 multi-purpose grease for the food processing industry

### Benefits

- ✓ Versatile high-performance grease to help reduce the number of products required in the food, beverage and pharmaceutical industries
- ✓ Good corrosion protection reduces the risk of premature bearing failures

### Properties

- ✓ Easily deliverable
- ✓ Excellent corrosion protection
- ✓ Reduces friction and wear
- ✓ High load-bearing capacity
- ✓ Excellent resistance to water
- ✓ Excellent resistance to oxidation and ageing
- ✓ NSF H1 registered
- ✓ ISO 21469, Kosher and Halal certified

### Application area

- ✓ Specifically designed for use in areas where there is a risk of direct, technically unavoidable contact with food.
- ✓ For lubricating slide and roller bearings, lifting cylinders, joints, guide rods, cams etc.
- ✓ For use even in difficult conditions (low and high temperatures, high loads, shock and impact loads as well as exposure to water).

### Instructions

In accordance with technological standards for lubricating greases. Observe the machine manufacturer's specifications. Before filling or refilling the friction point, thoroughly clean the component and, if necessary, the lubrication point with TUNCLEAN 895 or appropriately registered products, e.g. TUNCLEAN FDB.

If the product is to be used in the food processing industry: Only the minimum quantity technically necessary may be used. If the product is used as a corrosion-protection film for surfaces in contact with foodstuffs, it must be completely removed before the device in question is used again.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNGREASE H1/EP-000	0 ml	25 kg	26.6 kg	1100566	1 PCS





<b>Technical Product Data</b>	<b>TUNGREASE H1/EP-000</b>
<b>Density/conditions</b>	0.86 g/cm <sup>3</sup> / at 20°C
<b>Colour spectrum</b>	White Yellowish
<b>Oil basis</b>	Synthetic
<b>Thickener</b>	Aluminium complex soap
<b>Base oil viscosity, kinematic/conditions</b>	350 mm <sup>2</sup> /s / at 40°C
<b>NLGI grade/conditions</b>	000 / with DIN 51818
<b>Min./max. temperature conditions</b>	-40 to 130 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.