

## TUNSLIP SF

Silicone-free release agent and lubricant with excellent plastic compatibility

### Benefits

- ✓ Transparent sliding, separating and maintenance oil
- ✓ The good compatibility with a wide range of elastomers and plastics and the broad temperature range is particularly noteworthy
- ✓ For reliable, silicone-free demoulding in plastic injection moulding

### Properties

- ✓ Protects against static charge on plastics
- ✓ Good wetting capacity
- ✓ Non-contaminating, non-greasy and transparent

### Application area

- ✓ Release agent and anti-static agent
- ✓ Mould release agent, particularly in the plastics processing industry
- ✓ Assembly of plastic components
- ✓ For the care and maintenance of plastic surfaces
- ✓ For lubricating slide rails, bearings and other machine elements
- ✓ Use in vehicle manufacturing:
- ✓ For cleaning and care of plastic components

### Instructions

From a distance of approx. 20 cm, spray on and wipe dry with a cloth if necessary.  
Do not spray on steering wheel and pedals!

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNSLIP SF	400 ml	0.265 kg	0.33 kg	1102060	12 PCS

# Product Information



<b>Technical Product Data</b>	<b>TUNSLIP SF</b>
<b>Density/conditions</b>	0.759 g/cm <sup>3</sup> / in accordance with DIN 51757
<b>Colour spectrum</b>	Colourless
<b>Min. flashing point /conditions</b>	0 / in accordance with ISO 2592
<b>Pour point</b>	-50 °C

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.

Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.

TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

PI 20250106

[TUNAP.com](https://www.tunap.com)