Product Information

CARGO logic®

685 Fuel Guard System Protection

Reliably kills microorganisms in diesel and bio-diesel fuels and prevents regeneration. Effective against a broad range of bacteria, yeasts and moulds.

Properties

- ✔ Reliably fights microorganisms
- ✔ Acts against bacteria, yeasts and moulds
- ✔ Reliably prevents the regeneration of microorganisms

Application area

- ✔ Diesel engines in commercial vehicles
- ✔ Diesel systems in ships
- ✔ Standing aggregates
- ✔ Home tank systems with a long storage time
- ✔ For preventative use with bio-diesel and high moisture levels

Instructions

For systems that are already affected, clean thoroughly and use a shock dosage. Can also be applied as a preventative measure. Avoid overdosing.

Dosing

Shock dosing:
500 ml for 600 litres
5,000 ml for 6,000 litres

Preventative use:
500 ml for 3,000 litres
5,000 ml for 30,000 litres

Product Description	Contents	Article Number	Packaging Unit
Fuel Guard System Protection	5 l	1102511	1 PCS




The information herein is the product of careful testing. It is to be considered a recommendation compliant with state of the art knowledge where use is concerned. We cannot accept any liability whatsoever in view of the multiplicity of possible uses and working methods. No contractual relationship is hence implied and no ancillary obligations arise from any contract of sale that may be made. Product information is only valid in its latest current form. TUNAP (U.K) Limited | Unit L4 Deacon Trading Estate, Morley Road, Tonbridge, Kent TN9 1RA | Telephone +44 (0) 1732 365163 | e-Mail: sales@tunap.co.uk