

TUNFLUID HTC 260

Fully synthetic high-temperature oil for chain lubrication

Benefits

- ✓ Very economical consumption due to high degree of thermal stability and extremely low boil-off
- ✓ Clean to use, as no varnish-like residues are formed even at increased operating temperatures.
- ✓ Excellent wear protection for reliable chain operation

Properties

- ✓ Excellent creeping properties
- ✓ Ideal for medium to high speeds
- ✓ No resin or bonding effect
- ✓ Reduces friction and wear

Application area

- ✓ Drive, control and conveyor chains in high-temperature applications, e.g. in surface treatment, drying or coating of various industrial goods
- ✓ Transport systems in automotive supply, metalworking and/or coating of household goods or packaging material manufacturing
- ✓ Conveyor chains in dryers, e.g. in the production of gypsum or mineral wool

Instructions

Observe the machine manufacturer's specifications. Can be applied using a drip oiler, brush or automatic central lubrication system.

H2 products must not be used in areas where foodstuffs are manufactured. H2 products can be used as lubricants, release agents or corrosion inhibitors for machine parts and equipment provided that they do not come into contact with foodstuffs.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNFLUID HTC 260	20 l	18.1 kg	19.13 kg	1103061	1 PCS



Nonfood Compounds
Program Listed H2
198 855



Technical Product Data	TUNFLUID HTC 260
Density/conditions	0.904 g/cm ³ / at 20°C
Colour spectrum	Yellowish Transparent
Oil basis	Ester
Kinematic viscosity / condition	260 mm ² /s / at 40°C
Min. flashing point /conditions	> 250°C / nach ISO 2592
Pour point	-27 °C
Min./max. temperature conditions	-25 to 250 °C