

## TUNTEX

# 1021 Underbody Protection Spray

Produces a perm. elastic, securely adherent underbody protective lining on a rubber/resin base, which reliably protects against corrosion, stone impact, road salt and moisture. For treatment of corners, edges, angles on motor vehicle floors and wheel arches. Especially suitable for treatment and repair work in difficult to access places.



### Properties

- ✓ Prevents moisture and road salt corrosion
- ✓ Highest level of abrasion resistance
- ✓ Can be painted over
- ✓ High coating thickness
- ✓ High level of resistance to ageing

### Application area

- ✓ All factory-fitted surfaces, except wax
- ✓ Ideal for underbody, wheel arch, front apron, rear apron, sills, new parts and repair sheet metal

### Instructions

Shake can well before use. Layer thickness per work process approx. 1mm wet film (= 700 µm dry film). For repainting with „water-based paint systems“ allow to dry for at least 3 hours per 500 µm dry film at 23°C / 55% humidity. For repainting with „solvent-containing paint systems“ allow to dry for at least 20 minutes. The drying time is dependent on the ambient temperature / humidity and layer thickness After processing, spray dry the aerosol riser tube to prevent a blockage in the nozzle.

### Notice

- ✓ Do not spray on axle, drive shaft, engine, gear, exhaust and brake system.

Product Description	Contents	Article Number	Packaging Unit
Underbody Protection Spray	500 ml	1103662	12 PCS

