

Professional 164 System Agent

Active agent concentrate for liquefied petroleum gas (LPG). Reduces valve wear (valve impact), thus extending the service life of the engine.



Properties

- ✓ Minimises valve wear
- ✓ Prevents oxidation of liquefied petroleum gas
- ✓ Corrosion protection for the entire gas system

Application area

- ✓ After the conversion to liquefied petroleum gas operation
- ✓ For all maintenance on the system
- ✓ For repairs on the system

Instructions

Remove the rubber plug from the bottom of the can and screw on the air connection adapter. Screw the LPG adapter onto the filling connection of the vehicle. Screw MP 164 into the LPG adapter. Connect the air pressure inspection device to the air connection adapter and pressurise the can with max. 10 bar. Once the can is empty, unscrew both the adapter and the can. Observe Service Information 164.

Dosing

One can is sufficient for a basic additivation of the liquefied petroleum gas. An additional dosage is only necessary in combination with MP 163 system agent LPG (petrol), at the latest after 10,000 km. We assume no liability for efficacy if MP 164 is used without MP 163.

Notice

- ✓ Caution: Already existing wear on valves and valve seats cannot be reversed! Using the system agents prevents further wear.

Product Description	Contents	Article Number	Packaging Unit
System Agent	100 ml	1103667	24 PCS

Required accessories	Article Number	Packaging Unit
System Agent, 375 ml	11AMP16300375AB	24 PCS
LPG Adapter M22 Thread, 0	1400212	1 PCS
Air Connection Adapter, 0	1400217	1 PCS
LPG Adapter M10 Thread, 0	1400662	1 PCS

