

Professional 582 A/C system agent

System agent for maintenance, protection and diagnostics of air conditioner refrigerant circuits. Suitable for air-conditioning units with R134a and HFO-1234yf refrigerants.



Properties

- ✓ Reduces friction and ensures consistent cooling performance
- ✓ Minimises signs of wear on the refrigerant compressor
- ✓ Protects the PAG oil against oxidation
- ✓ Rapid discovery of leaks thanks to special UV pigment particles
- ✓ Freshens up o-rings and seals, thereby protecting them against micro-leaks

Application area

- ✓ In conjunction with maintenance and air-conditioning unit checks
- ✓ Recommended for air-conditioning units with R134a and HFO-1234yf refrigerants
- ✓ Compatible with most PAG oils
- ✓ For rapid detection of leaks
- ✓ Preventative measure for all inspections

Instructions

Observe Service Information SI 582. Start the vehicle and switch on the air-conditioning unit to full power for 1 minute. Fit the appropriate filling adapter onto the can. Connect the filling adapter to the service connection on the low-pressure circuit. Increase the engine speed to 2000 rpm and maintain this speed. Press the can into the adapter and drain.

Notice

- ✓ Product does not contain sealing particles or substances that harden in the presence of moisture. Do not use more than once a year. Sufficient for up to 1000 g of refrigerant.

Product Description	Contents	Article Number	Packaging Unit
A/C system agent	50 ml	1103710	24 PCS

Required accessories	Article Number	Packaging Unit
Silverline UV pocket torch		
A/C Adapter R134a		
A/C Adapter R1234yf		
Filling adapter for 582		

