Product Information

TUNCLEAN 895

Quick degreaser and cleaner with excellent cleaning effect for maintenance, repair and assembly.

Benefits

- ✔ Residue-free cleaning for grease-free surfaces and easy follow-up processes
- ✔ Removes extreme dirt caused by oil, grease, resin, silicone and corrosion protection layers
- ✔ Dries quickly

Properties

- ✔ Very good cleaning effect
- ✔ Mean evaporation rate
- ✔ Cleans and leaves no residue
- ✔ Protects against immediate re-rusting

Application area

- ✔ For maintenance, repair and assembly in the case of extreme grease and resin deposits
- ✔ For degreasing and activating parts before gluing and painting
- ✔ Removes oils and encrusted resin, synthetic oil and silicone residues
- ✔ Ideal for residue-free cleaning
- ✔ Can be used as a brake cleaner

Instructions

Apply TUNCLEAN 895 to the parts to be cleaned by spraying or dipping. Leave to take effect briefly and wash off with a lint-free cloth. Check for compatibility with plastics and paints by preliminary tests.

Product Description	Contents	Weight of content	Gross weight	Article Number	Packaging Unit
TUNCLEAN 895	500 ml	0.382 kg	0.504 kg	1105999	12 PCS

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.

Product Information

Technical Product Data	TUNCLEAN 895
Density/conditions	0.755 g/cm³ / at 20°C
Colour spectrum	Colourless Clear
Evaporation number/conditions	3.9 / in accordance with DIN 53170

The information provided here is based on our general technical experience and knowledge related to printing. All specifications are guidelines based on product design, the specified use and mechanical and systems engineering. But the information does not represent any pledge about features or any assurance about the product's suitability for use in a particular case. The user is not released from the responsibility of testing the product.
Depending on the mechanical, dynamic, chemical and thermal stresses to which they are subjected, lubricants alter their technical values on a pressure- and time-dependent basis. The changes can have an impact on the function in the application.
TUNAP products are continuously refined. We reserve the right to change all technical data in this document at any time and without any prior notification. Obligations of any kind are in no way implied.