

microflex® 985 Fuel Guard System Protection

Patented microflex® 985 Fuel Guard System Protection reliably removes organic contaminants from diesel and bio-diesel fuels and prevents recontamination. In addition, microflex® 985 contains a cetane booster, antioxidants and corrosion protection. For greater protection and sustained improvement in engine performance.



Properties

- ✓ Prevents recontamination
- ✓ Tested in accordance with ASTM E 1259-10 and EN 15457:2014-11
- ✓ Protects metallic components in the fuel system using corrosion protection inhibitors
- ✓ Low toxicity: contains no substances which are carcinogenic, mutagenic or toxic for reproduction
- ✓ Biocide-free

Benefits

- ✓ Patented formulation
- ✓ Reliably removes organic contaminants
- ✓ Stabilises fuel quality through antioxidants
- ✓ Ensures optimal engine performance with cetane booster

Application area

- ✓ Diesel engines
- ✓ Diesel systems in ships
- ✓ Standing units
- ✓ Home tank systems with a long storage time

Instructions

If organic contaminants are present in the fuel systems, clean thoroughly and use a shock dosage of the product. Use regularly to prevent the formation of micro-organisms in the fuel.

Dosing

Preventive use:
500 ml for 2,000 l
5 l for 20,000 l

Shock dosage:
500 ml for 250 l
5 l for 2,500 l

Product Description	Contents	Article Number	Packaging Unit
Fuel Guard System Protection	5 l	1106153	1 PCS

