

microflex®

985 Fuel Guard System Protection

Reliably removes organic contaminants in diesel and bio-diesel fuels and prevents recontamination. Tested according to ASTM E 1259-10 and EN 15457:2014-11. Also contains cetane number boosters, antioxidants and corrosion protection.



Properties

- ✓ Reliably removes biological contaminants.
- ✓ Prevents recontamination.
- ✓ Tested according to ASTM E 1259-10 and EN 15457:2014-11.
- ✓ Stabilises fuel quality using antioxidants.
- ✓ Ensures optimum engine performance thanks to a cetane booster.
- ✓ Protects metallic components in the fuel system using corrosion protection inhibitors.
- ✓ Low toxicity: Contains no carcinogenic or mutagenic ingredients and no ingredients that are toxic for reproduction.
- ✓

Application area

- ✓ Diesel engines
- ✓ Diesel systems in ships
- ✓ Standing units
- ✓ Home tank systems with a long storage time

Instructions

If organic contaminants are present in the fuel systems, clean thoroughly and use a shock dosage of the product. Use regularly to prevent the formation of micro-organisms in the fuel.

Dosing

Preventative use:
500 ml for 2000 litres
5 litres for 20,000 litres

Shock dosing:
500 ml for 250 litres
5 litres for 2,500 litres

Product Description	Contents	Article Number	Packaging Unit
Fuel Guard System Protection	5 l	1106210	1 PCS

